DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO

Operator MERIDIAN OIL CO. Location: Unit A Sec. 13 Twp 30 Rng6
Name of Well/Wells or Pipeline Serviced SJ 30-6 #43 , #442
cps 189w
Elevation 6349 Completion Date 10-22-90 Total Depth 340 Land Type N/A
Casing Strings, Sizes, Types & Depths 20 feet of 8" PVC casing
If Casing Strings are cemented, show amounts & types used 1 bag cement
If Cement or Bentonite Plugs have been placed, show depths & amounts use
Depths & thickness of water zones with description of water: Fresh, Clea
Salty, Sulphur, Etc. 70 feet No water sample
Depths gas encountered: N/A
Ground bed depth with type & amount of coke breeze used: 150 feet with
Petroleum coke breeze.
Depths anodes placed: 305, 290, 255, 245,235,225,215,205,195,185
Depths vent pipes placed: 340 feet
/ent pipe perforations: 260 feet
Remarks:ab #3
OIL CON. DIV

If any of the above data is unavailable, please indicate so. Copies of a logs, including Drillers Log, Water Analyses & Well Bore Schematics shou be submitted when available. Unplugged abandoned wells are to be include

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.

22 - 1994 - 1942 - 1965

44Z 30-039-24460

5

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO (Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit NE Sec. 14 Twp 30 Rng 6		
Name of Well/Wells or Pipeline Serviced SAN JUAN 30-6 UNIT #43, #442		
cps 189w		
Elevation 6349'Completion Date 6/10/69 Total Depth 640' Land Type* N/A		
Casing, Sizes, Types & Depths N/A		
If Casing is cemented, show amounts & types used N/A		
If Cement or Bentonite Plugs have been placed, show depths & amounts used N/A		
Depths & thickness of water zones with description of water when possible:		
Fresh, Clear, Salty, Sulphur, Etc. 280'		
Depths gas encountered: N/A		
Type & amount of coke breeze used: 8550 lbs.		
Depths anodes placed: 522', 516', 416', 410', 404', 398', 392', 386', 376', 311'		
Depths vent pipes placed: 516' OF 3/4" HOSE		
Vent pipe perforations: 470'		
Remarks: gb #2 STYROFOAM MOLD USED ON CAPPING 7 ANODES. MASKING TAPE USED ON		
CAPPING 3 ANODES.		

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

^{*}Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.

43 30-039-07860

442 30-039-24460

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO (Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Loc	ation: Unit_NE Sec.14 Twp 30 Rng 6
Name of Well/Wells or Pipeline Serviced_	SAN JUAN 30-6 UNIT #43, #442
	189w
Elevation 6349 Completion Date 4/29/63 To	tal Depth <u>140'</u> Land Type* N/A
Casing, Sizes, Types & Depths N/A	
If Casing is cemented, show amounts & ty	pes used N/A
If Cement or Bentonite Plugs have been p	laced, show depths & amounts used
Depths & thickness of water zones with d	escription of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. N/	1
Depths gas encountered: N/A	
Type & amount of coke breeze used: 110	5 lbs.
Depths anodes placed: 123', 117', 80', 74',	68' A CRETWED
Depths vent pipes placed: N/A	11/1
Vent pipe perforations: N/A	
Remarks: gb #1	OIL CON. D''

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

^{*}Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.