

138E-30-039-25453

16-30-039-06927

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS - 5 1995
NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

RECEIVED

OIL CON. DIV.
DIST. 3

Operator Unocal Oil and Gas Operation Location: Unit P Sec. 25 Twp 27N Rng 7W

Name of Well/Wells or Pipeline Serviced Rincon Unit 138E Rincon Unit 16

Elevation 6666 Completion Date 02/11/95 Total Depth 300' Land Type* F

Casing, Sizes, Types & Depths NONE

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NONE

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. Damp at 250'

Depths gas encountered: NONE

Type & amount of coke breeze used: 3000 lbs. Carbo 40

Depths anodes placed: 150' 155' 165' 185' 190' 200' 205' 210' 220' 275'

Depths vent pipes placed: 0' to 300'

Vent pipe perforations: 140' thru 300'

Remarks: Lease 079321

First Ground Bed install at this location

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

Cathodic Protection Services

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	P/L NAME(s), NUMBER(s)					
751-00311	Rincon 138 E					
WG #	TOTAL	VOLTS	AMPS	= OHMS	DATE	NAME
	10 Anodes	12.47	9.2	1.36	2-11-95	Don L.

REMARKS (notes for construction log)

3,000 lb of Coke Breeze

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	
100			295			490			685			
105			300	THD		495			690			
110			305			500			695			
115			310			505			700			
120			315			510			ANODE	DEPTH	NO	FULL
125			320			515			#		COKE	COKE
130			325			520			1	275	.9	1.7
135	.6		330			525			2	220	1.0	3.3
140	.5		335			530			3	210	1.2	4.5
145	.2		340			535			4	205	1.5	4.8
150	.8		345			540			5	200	1.1	4.5
155	.9		350			545			6	190	1.0	4.3
160	.6		355			550			7	185	1.4	4.4
165	.8		360			555			8	165	.8	2.1
170	.3		365			560			9	155	.9	2.4
175	.2		370			565			10	150	.8	2.3
180	.6		375			570			11			
185	1.4		380			575			12			
190	1.0		385			580			13			
195	.8		390			585			14			
200	1.1		395			590			15			
205	1.5		400			595			16			
210	1.2		405			600			17			
215	.8		410			605			18			
220	1.0		415			610			19			
225	.7		420			615			20			
230	.4		425			620			21			
235	.2		430			625			22			
240	.2		435			630			23			
245	.2		440			635			24			
250	.2		445			640			25			
255	.2		450			645			26			
260	.4		455			650			27			
265	.4		460			655			28			
270	.9		465			660			29			
275	.9		470			665			30			
280	.2		475			670						
285	.2		480			675						
290	.1		485			680						

DISTRIBUTION - original - permanent CPS FILE

COPY

- Division Construction Services

BÜRGE CORROSION SYSTEMS, INC.

**P.O. BOX 1359 - PHONE 334-6141
AZTEC, NEW MEXICO 87410**

COMPANY Unicol DAILY DRILLING REPORT 2/11 19 95

WELL NAME: <u>Rincon 138 E</u> <u># 7th drilled</u>	WELL NUMBER: <u>7</u> <u>444</u>	SECTION: <u>25</u>	TOWNSHIP: <u>27N</u>	RANGE: <u>7W</u>
WATER AT: <u>N/A ? 200</u>		HOLE MADE: <u>300'</u>		

DESCRIPTION OF FORMATION

[illegible]

REMARKS: Dray all the way / Home moisture at 250'

Ernest E. Burge

Order

Test Drawer