

107-30-039-60093

174-30-039-06952

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator Union Oil Company of California Location: Unit Sec. 19 Twp 27N Rng 6WName of Well/Wells or Pipeline Serviced Rincon Unit #107 MV, Rincon Unit #174 DKElevation 6592' Completion Date 7/9/1970 Total Depth 610' Land Type* FCasing, Sizes, Types & Depths NoneIf Casing is cemented, show amounts & types used NoneIf Cement or Bentonite Plugs have been placed, show depths & amounts used
NoneDepths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. 340' deep Thickness ? Depths gas encountered: NAType & amount of coke breeze used: 8100 lbs Kind ^{unk} knownDepths anodes placed: 410' - 575'Depths vent pipes placed: ?Vent pipe perforations: 400'Remarks: El Paso Natural Gas was operator when this ground bed was installed.Second ground bed installed at this location.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

RECEIVED
MAY 18 1980
OIL CON. DIV.
DIST. 3

WELL CASING
CATHODIC PROTECTION CONSTRUCTION REPORT
DAILY LOG

Drilling Log (Attach Hereto) ☐

#2 GND BED
Contractor CPS.

Completion Date 7-9-70

Well Name Rivcon # 174		Location SW 19-27-6		CPS No. 689W	
Type & Size Bit Used 6 3/4				Work Order No. 184-53447-50-20	
Anode Hole Depth 610	Total Drilling Rig Time	Total Lbs. Coke Used	Lost Circulation Mat'l Used	No. Sacks Mud Used	
Anode Depth					
#1 575	#2 (525)	#3 515	#4 490	#5 480	#6 470
#7 460	#8 450	#9 440	#10 430		
Anode Output (Amps)					
#1 1.38	#2 3.7	#3 3.7	#4 1.32	#5 4.0	#6 4.0
#7 2.5	#8 2.5	#9 3.7	#10 3.7		
Anode Depth					
#11 420	#12 410	#13	#14	#15	#16
#17	#18	#19	#20		
Anode Output (Amps)					
#11 3.8	#12 3.8	#13	#14	#15	#16
#17	#18	#19	#20		
Total Circuit Resistance				No. 8 C.P. Cable Used	No. 2 C.P. Cable Used
Volts 12.5	Amps 10.8	Ohms 1.15			

Remarks: Wet at 340 Drill with air to 360
 Pump 55 Bags Coke Slurry 26 Bags 81 Total
 1" Hose perforated approx 400' to No. 1 Anode
 Anodes 1 & 4 are Single - others Dual

All Construction Completed

Farrell
(Signature)

GROUND BED LAYOUT SKETCH

