

134-30-039-20726

96-30-039-06625

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

232-30-039-22223

Operator UNOCAL Location: Unit Sec. 12 Twp 26 Rng 7

Name of Well/Wells or Pipeline Serviced Rincon Unit No. 134 DK, 96 PC, 232 CH,
& 270 FC

Elevation 6463' Completion Date 7-26-90 Total Depth 300' Land Type* F

Casing, Sizes, Types & Depths NONE

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NONE

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. 180 Ft., depth, less than 5' thick, damp, fresh.

Depths gas encountered: NONE

Type & amount of coke breeze used: 300', deep with carbo 60=99.9% carbon Coke breeze, 1500 lbs.

Depths anodes placed: 245', 255', 265', 275', 285', 295'

Depths vent pipes placed: 0 to 300 FT.

Vent pipe perforations: Perts from 180 FT. to 300 FT. depth.

Remarks: All vent - laser slotted vent pipe, PVC.

1st ground bed installed at this location.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

RECEIVED

JAN 30 1991

OIL CON. DIV

PAGE 1

COMPANY Unocal JOB NO. 751-00084 DATE: 7-26-90
 WELL: Lincoln Unit N° 134 PIPELINE: _____
 LOCATION: SEC. 12 TWP. 26 RGE. 7 CO. Go Arriba STATE NM
 ELEV. _____ FT: ROTARY 300 FT: CABLE TOOL _____ FT: ^{COKE} GASTING Carbo 60 _W
 GROUND BED: DEPTH 300' FT. DIA. 16" IN. GAS 1500 LBS. ANODES Lida-Gen 58116/SC

DEPTH, FT.	DRILLER'S LOG	EXPLORING ANODE TO STRUCTURE			NO COKE	WITH COKE	ANODE NO.	DEPTH, TOP OF ANODES
		E	I	R				
0-30'	Brown Grey Clay + Shale							
65 to 100	Frist water 180' Camp, 30-45' Grey shale, 45-65' Grey Sandstone							
100	Grey Sandstone, some shale							
5								
10								
15								
20								
25								
30								
35								
40								
45								
50								
55								
60								
65								
70								
75								
80								
85								
90								
95								
100								
105								
110								
115								
120								
125								
130								
135								
140								
145								
150								
155								
160								
165								
170								
175								
180								
185								
190								
195								
200								
205								
210								
215								
220								
225								
230								
235								
240								
245								
250								
255								
260								
265								
270								
275								
280								
285								
290								
295								
300								
305								
310								
315								
320								
325								
330								
335								
340								
345								
350								
355								
360								
365								
370								
375								
380								
385								
390								
395								
400								
405								
410								
415								
420								
425								
430								
435								
440								
445								
450								
455								
460								
465								
470								
475								
480								
485								
490								
495								
500								
505								
510								
515								
520								
525								
530								
535								
540								
545								
550								
555								
560								
565								
570								
575								
580								
585								
590								
595								
600								
605								
610								
615								
620								
625								
630								
635								
640								
645								
650								
655								
660								
665								
670								
675								
680								
685								
690								
695								
700								
705								
710								
715								
720								
725								
730								
735								
740								
745								
750								
755								
760								
765								
770								
775								
780								
785								
790								
795								
800								
805								
810								
815								
820								
825								
830								
835								
840								
845								
850								
855								
860								
865								
870								
875								
880								
885								
890								
895								
900								
905								
910								
915								
920								
925								
930								
935								
940								
945								
950								
955								
960								
965								
970								
975								
980								
985								
990								
995								
1000								

GROUND BED RESISTANCE: (1) VOLTS 12.58 - AMPS 6.9 - 1.82 OHMS

(2) VIBROGROUND _____ OHMS

GENERAL CATHODIC PROTECTION SERVICES CO.

MO-TE DRILLING, INC.

DAY Wednesday

DRILLER <u>B. B.</u>	LEFT TOWN <u>6:00</u> ARRIVED FIELD <u>7:20</u>
HELPER <u>T. P.</u>	LEFT FIELD <u>5:30</u> ARRIVED TOWN <u>7:00</u>
HELPER <u>W. M.</u>	TOTAL FOOTAGE TODAY _____

RIG NO. _____ DATE 7-25-90 CLIENT Umo-Cal

BEGIN WORK ON HOLE NO. Union #134 AT _____ FEET

BEGIN WORK ON HOLE NO. _____ AT _____ FEET

TIME		ACTIVITY
FROM	TO	
0	30	Brown, grey clay shale
30	45	grey shale
45	65	grey sandstone
65	760	grey sandstone, some shale
760	2400	hard grey sandstone with granules
2400	5000	hard grey to dark grey shale

BIT RECORD			
SIZE & MAKE	SERIAL NO.	FOOTAGE	
6" Special (New)			
5" Regular			
CIRCULATION MATERIAL			
QUAN.	UNIT	MATERIAL	

NO. OF LOADS OF WATER _____ SOURCE _____

