

#6A 30-045-24368

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO

Operator Meridian Oil INC Location: Unit D Sec. 01 Twp 31 Rng 09

Name of Well/Wells or Pipeline Serviced \_\_\_\_\_

Nordhaus #6A

Elevation 6581 Completion Date \_\_\_\_\_ Total Depth \_\_\_\_\_ Land Type F

Casing Strings, Sizes, Types & Depths 4/26 Set 99' of 8" PVC Casing.

NO GAS, WATER, OR Boulders Were ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 19 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. Damp AT 200'

Depths gas encountered: NO

Ground bed depth with type & amount of coke breeze used: 464' with

6600 lbs of Asbury 4518 Flo Coke

Depths anodes placed: 449, 442, 435, 428, 421, 414, 407, 400, 365, 355, 323, 314, 276, 269, 240

Depths vent pipes placed: 464'

Vent pipe perforations: bottom 260'

Remarks: \_\_\_\_\_

**RECEIVED**

JAN 31 1994

**OIL CON. DIV.**  
**DIST. 2**

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.  
If Federal or Indian, add Lease Number.