

30-045-28964

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit N Sec. 30 Twp 28 Rng 11

Name of Well/Wells or Pipeline Serviced _____

RHodes C#101

Elevation _____ Completion Date 9/12/93 Total Depth 390' Land Type I

Casing Strings, Sizes, Types & Depths 9/11 Set 58' of 8" PVC Casing.

No Gas, Water, or Boulders Were Encountered During Casing.

If Casing Strings are cemented, show amounts & types used Cemented

With 14 Sacks.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT A DAMP Layer AT 65', AND FRESH

Water AT 350'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 390' Depth

Used 106 Sacks of Asbury 218R (5300#)

Depths anodes placed: 325', 318', 311', 304', 297', 250', 238', 231', 224', 217', 210', 196', 189', 182', +176'

Depths vent pipes placed: SURFACE TO 390'

Vent pipe perforations: BOTTOM 280'

Remarks: _____

RECEIVED

JAN 31 1994

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.