

#6A 30-045-23077

#9 30-045 23711

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit P Sec. 20 Twp 31 Rng 08

Name of Well/Wells. or Pipeline Serviced \_\_\_\_\_

QUINN #6A AND #9

Elevation 6579 Completion Date \_\_\_\_\_ Total Depth \_\_\_\_\_ Land Type P

Casing Strings, Sizes, Types & Depths 4 1/2" SET 99' OF 8" PVC CASING

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING

If Casing Strings are cemented, show amounts & types used Cemented

WITH 20 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. NO

Depths gas encountered: NO

Ground bed depth with type & amount of coke breeze used: 486' with

7350 lbs of Asbury 4518 FLO COKE

Depths anodes placed: 475, 469, 463, 457, 451, 445, 439, 433, 427, 421, 410, 400, 390, 380, 370

Depths vent pipes placed: 486'

Vent pipe perforations: bottom 350

Remarks: \_\_\_\_\_

RECEIVED

JAN 31 1994

OIL CON. DIV.  
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.  
If Federal or Indian, add Lease Number.