

#44-A 30-045-28940

#91 30-045-22904

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit 0 Sec. 11 Twp 31 Rng 10

Name of Well/Wells or Pipeline Serviced _____

S.J. 32-9 UNITS #44A AND #91

Elevation 6197 Completion Date 10/19/93 Total Depth 427' Land Type F

Casing Strings, Sizes, Types & Depths 10/15 Set 59' of 8" PVC Casing.

NO GAS OR WATER, BUT 7' (23'-30') OF BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 17 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

.45' TO 110' CEMENT PLUG WAS PLACED TO STOP GAS. USED 23 SACKS (100#).

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT FRESH WATER AT 110', AND MORE WATER AT

160'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: 160'

Ground bed depth with type & amount of coke breeze used: 427' Depth.

USED 116 SACKS OF ASBURY 218R (5800#)

Depths anodes placed: 410', 403', 396', 389', 382', 375', 368', 361', 354', 347', 340', 333', 326', 318', 311', 295', 285', 225', 216', + 185'.

Depths vent pipes placed: SURFACE TO 427'.

Vent pipe perforations: BOTTOM 300'.

Remarks: _____

RECEIVED

JAN 31 1994

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.