

#1R 30-045-20125

#3 30-045-26489

#250 30-045-27036

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Co. Location: Unit A Sec. 13 Twp 30 Rng 09

Name of Well/Wells or Pipeline Serviced \_\_\_\_\_

SHAW #1R, #3 + #250

Elevation 5894 Completion Date \_\_\_\_\_ Total Depth \_\_\_\_\_ Land Type F

Casing Strings, Sizes, Types & Depths 1/27 Set 100' of 8" PVC CASING.

NO GAS OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 23 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

-0' plug 105' to 85'

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT FRESH WATER AT 78' DURING CASING.

Depths gas encountered: No

Ground bed depth with type & amount of coke breeze used: 470' with

7100 lbs Loresco Type SW

Depths anodes placed: 453, 444, 435, 420, 410, 400, 390, 380, 355, 345, 335, 294, 286, 278

Depths vent pipes placed: 470'

Vent pipe perforations: bottom 300'

Remarks: \_\_\_\_\_

RECEIVED

JAN 31 1994

OIL CON. DIV.

DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.