

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS

NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

30-034-20497

Operator: UNOCAL - Bloomfield, NM Location Unit _____ Sec. 01 Twp. 26N Rng. 7WName of Well/Wells or Pipeline Served: RINCON UNIT 192 DKElevation: 6466 GR Completion Date: 10/31/96 Total Depth: 320' Land Type* FCasing, Sizes, Types & Depths: NONEIf Casing is cemented, show amounts & types used: NONEIf Cement or Bentonite Plugs have been placed, show depths & amounts used NONE

Depths & thickness of water zones with description of water when possible: _____

WET SANDSTONE AT 190'Fresh, Clear, Salty, Sulfur, Etc.. CLEARDepths gas encountered: NONEType & amount of coke breeze used: 2500 LBS., SWB METALURGICAL PETROLEUM COKEDepths anodes placed: 190' 200' 210' 220' 230' 240' 250' 260' 270' 280' 290' 300'Depths vent pipes placed: 0' - 320', 1" PVCVent pipe perforations. 1/8" PERFORATIONS FROM 100' TO 300'Remarks: SECOND GROUND BED INSTALLED ON THIS LOCATION.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analysis & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal, I-Indian; S-State, P-Fee
If Federal or Indian, add Lease Number.

RECEIVED
NOV 27 1996OIL CON. DIV.
DIST. 3

COMPANY: Unocal DATE: 10-31-96
 WELL: Rincon 192
 LOCATION: 14 14 SEC. 1-26-6 PIPELINE:
 GROUND BED: DEPTH: 320' DIAMETER: 6 3/4" STATE: N.M. Rio Arriba
 BACKFILL: Wet Sandstone ANODES TYPE: Durachlor S1

DEPTH FT.	DRILLERS LOG	ANODE LOG			ANODE DEPTH	REMARKS
		I Logged	I Coded	R		
20	<u>Sand</u>					
30	<u>Sand Stone</u>					
40						
50						
60						
70						
80						
90						
100	<u>Sandy Shale</u>					
110						
120						
130						
140						
150						
160						
170	<u>Sand Stone</u>					
180						
190		<u>.4</u>	<u>.2</u>		<u>190'</u>	<u>Coke Breeze</u> <u>Wet Sand Stone</u>
200	<u>Sandy Shale</u>	<u>1.0</u>	<u>1.7</u>		<u>200'</u>	
210		<u>.9</u>	<u>1.5</u>		<u>210'</u>	
220		<u>.7</u>	<u>1.4</u>		<u>220'</u>	
230		<u>1.1</u>	<u>1.8</u>		<u>230'</u>	
240	<u>Shale</u>	<u>1.4</u>	<u>2.5</u>		<u>240'</u>	
250		<u>1.5</u>	<u>2.9</u>		<u>250'</u>	
260	<u>Sandy Shale</u>	<u>.8</u>	<u>1.8</u>		<u>260'</u>	
270		<u>.7</u>	<u>1.7</u>		<u>270'</u>	
280		<u>.7</u>	<u>2.0</u>		<u>280'</u>	
290		<u>1.0</u>	<u>2.1</u>		<u>290'</u>	
300		<u>1.1</u>	<u>2.1</u>		<u>300'</u>	
310						
320						
330						
340						
350						

NOTES:

POWER SOURCE: Battery VOLTS: 8.6INDICATE WATER ZONE DEPTHS 190'CASINO RUN: YES / ☒ NO TYPE: _____ DEPTH: _____ CEMENTED: YES / ☒ NOISOLATION PLUGS SET: YES / ☒ NO IF SO, WHERE: _____TOTAL: AMPS 7.0 RESISTANCE: 1.2