

1098

B#1A 30-045-26548
#100 30-045-26981

E

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL INC. Location: Unit B Sec. 28 Twp 32 Rng 6

Name of Well/Wells or Pipeline Serviced EPNG B #1A, #100
cps 1816w

Elevation 6460' Completion Date 8/6/87 Total Depth 400' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. 140' NO SAMPLE

Depths gas encountered: N/A

Type & amount of coke breeze used: N/A

Depths anodes placed: 360', 350', 340', 330', 315', 305', 295', 220', 195', 180'

Depths vent pipes placed: 395'

Vent pipe perforations: 340'

Remarks: gb #1

RECEIVED
MAY 31 1991
OIL CON.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

COMP
8-11-87

WELL CASING
CATHODIC PROTECTION CONSTRUCTION REPORT
DAILY LOG

Drilling Log (Attach Hereto) ☒

Completion Date 8-6-87

CPS #	Well Name: Line or Plant:	Work Order #	State:	Ins. Union Check
1816-w	EPNG "B" #1-A 100		600 N 84	☒ Good ☐ Bad
Location: B	Anode Size:	Anode Type:	Size Bit:	
NE28-32-6	2" x 60"	Duriron	6 3/4"	
Depth Drilled	Depth Logged	Drilling Rig Time	Total Lbs. Goke Used	Lost Circulation Mat'l Used
400'	393'			
Anode Depth				
#1 360'	#2 350'	#3 340'	#4 330'	#5 315'
#6 305'	#7 295'	#8 220'	#9 195'	#10 185'
Anode Output (Amps)				
#1 3.3	#2 2.8	#3 3.4	#4 3.8	#5 2.9
#6 3.6	#7 3.4	#8 3.9	#9 3.1	#10 3.4
Anode Depth				
#11	#12	#13	#14	#15
#16	#17	#18	#19	#20
Anode Output (Amps)				
#11	#12	#13	#14	#15
#16	#17	#18	#19	#20
Total Circuit Resistance	No. 8 C.P. Cable Used		No. 2 C.P. Cable Used	
Volts 12.1	Amps 13.6	Ohms .89	ELEVATION = 6436'	

Remarks: Drilled to 400'; LOGGED 393'; DRILLER SAID WATER AT 140' BUT NOT ENOUGH FOR SAMPLE. INSTALLED 395' of 1" PVC VENT PIPE; PERFORATED BOTTOM 340'

Rectifier Size: 40 V 16 A
 Addn'l Depth: _____
 Depth Credit: 107' ✓
 Extra Cable: 155' ✓
 Ditch & 1 Cable: 150' ✓
 Ditch & 2 Cable: 125' ✓
 25' Meter Pole: _____
 20' Meter Pole: _____
 10' Stub Pole: _____
 Junction Box: _____

4300 ✓
 -428 ✓
 38.75 ✓
 58.50 ✓
 65.00 ✓
 295.00 ✓
 40.00 ✓

4369.25
 218.46 ✓
 4587.71 ✓

All Construction Completed

Mick R. Will
 (Signature)

GROUND BED

6460

1816-w

N

aps 1816u

P.O. BOX 1359 - PHONE 334-6141
AZTEC, NEW MEXICO 87410

COMPANY Meridian Oil DAILY DRILLING REPORT 8/1, 1987

WELL NAME:

EPNG-B#1A

WELL NUMBER:

SECTION:

28

TOWNSHIP:

32

RANGE: 1-

6

WATER AT:

San Juan

FEET:

Wet 90

HOLE MADE:

DESCRIPTION OF FORMATION

[illegible]

REMARKS:

Driller

Here they

Tool Dresser

