District I 1625 N. French Dr., Hobbs, NM 88240 District Ii 1301 W Grand Avenue, Artesia, NM 88210 District III
1000 R10 Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr , Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

February 16, 2007

Pit or Below-Grade Tank Registration or Closure	
Is pit or below-grade tank covered by a "general plan"? Yes ☒ No ☐	

Type of action: Registration of a pit or below-grade tank ☐ Closure of a pit or below-grade tank ☒				
Operator: Elm Ridge Resources Telephone (50)	05) 632-3476 e-mail address: <u>amacke</u>	vil@elmridge.net		
Address: P.O. Box 156, Bloomfield, New Mexico, 87413	15) 052-5470 E-mail address amacke	y næemmage nei		
	03921426 U/L or Qtr/Qtr _ P	Sec. 4 T 23N P 3W		
County: Rio Arriba Latitude 36° 14.874' N				
Surface Owner: Federal State Private Indian	Longitude 107 09,044 W	NAD. 1921 🖸 1903 🗀		
	Below-grade tank			
Pit Type: Drilling Production Disposal	Volume. <u>45</u> bbl Type of fluid: <u>Produced Water</u>	and Incidental Oil		
Workover Emergency	Construction material: Steel	and incidental On		
Lined Unlined U		and the desired		
Liner type: Synthetic Thicknessmil Clay	Double-walled, with leak detection? Yes If not	, explain why not		
Pit Volumebbl	Tank installed prior to Rule 50			
Th volumeout	Less than 50 feet	(20 points)		
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)		
high water elevation of ground water.)	100 feet or more	(0 points) 0		
	Too leet of more	(o points)		
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)		
water source, or less than 1000 feet from all other water sources.)	No	(0 points) 0		
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)		
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)		
imigation canais, ditches, and perenniar and epitemeral watercourses.)	1000 feet or more	(0 points) I0		
	Ranking Score (Total Points)	10		
The state of the s	maletianskii 4 - 4km - 2 in 2 4 - 14 - 12 (2) Ye dan	to dismosphilipsetian (check the empire how if you		
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's		•		
are burying in place) onsite [] offsite [] If offsite, name of facility				
and end date. (4) Groundwater encountered: No 🖾 Yes 🗋 If yes, show de		n sample results.		
(5) Attach soil sample results and a diagram of sample locations and excavat	ions.			
Additional Comments:				
Soil sample passed 1000 ppin 1PH standard using USEPA Method 418 1 a	Soil sample passed 1000 ppm TPH standard using USEPA Method 418 1 and the 100 ppm OVM standard No excavation necessary			
		<u>RCUD MAY 21 '08</u> INI CINYS, DIV.		
		DIST. 3		
	/////////-	W.J. O		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank				
has been/will be constructed or closed according to NMOCD guidelines , a general permit , or an (attached) alternative OCD-approved plan .				
00005/15/08				
Date: 5 115 100 Reinted Name/Title Me Amy Modern Production Technicism Signature				
Printed Name/Title Ms. Amy Mackey, Production Technician Signature				
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or				
regulations.				
Approval. Divided Non-Attitude Silver 753				
Printed Name/Title Signature D				
· ·				

CLIENT:		Env	TROTEC	H INC.		LOC	A NOITA	· · · · · · · · · · · · · · · · · · ·
		5796 FARMIN	NTAL SCIENTIST U.S. HIGHWAY VGTON, NEW MI ONE: (505) 63:	S & ENGINEERS 7 64-3014 EXICO 67401 2-0615			C.O.C. N	10:
FIELD REPOR	PT:			ERIFIC	CATION	PAGE	No: _	of
LOCATION: NAME. JICAPILLA SORUT WELL #: KO # 1 PIT: SEP QUAD/UNIT: P SEC 4 TWP 23N RNG: 3W PM: NM CNTY: RA ST NM					STARTED. FINISHED:	418108 418108		
QTR/FOOTAGE: 990 F						ENVIRO SPECIA	ONMENTAL ALIST	enih
EXCAVATION APPROX DISPOSAL FACILITY: LAND USE:RALLGE							_	
FIELD NOTES & REMAR								
DEPTH TO GROUNDWATER >100								ì
NMOCD RANKING SCORE:			E STD: <u>lc</u>	XXO_ PPM		<u>CH</u> PIT	CK ON	
SOIL AND EXCAVATIO			•					INSTALLED
BGT MEKT TO AS	st No	T POLLER) Perione	o				
SAMPLE COLLECT FRO	m 202	T BEZOW	OUT SEC	de oftall	L NEAR	L SEP		
*	2008	500 /190	FIE	LD 418.1 CA	<u>LCULATIONS</u>		,	
	TIME	SAMPLE I.D.	LAB No	WEIGHT (g)	 	DILUTION 4		
SCALE		DIRECT BROW		٥	20	4	112	448
0 FT			OVM					
PIT PERIMI	ĽľĽR		RESULT		Pl'	r PR	OF,ITF	
	•	A SAMPL 1BELON 2 3	PID	HEADSPACE (ppm)	_			
(Nor) (Re-)		5						
	,				X	x x ,	×	
LAB SAMPLES								
8		SAMPLE ID	ANALYSIS	TIME				
,			,					
			<u> </u>					
TRAVEL NOTES. CALLOUT:	,		. -	NSITE.				



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

Elm Ridge Resources

Cool and Intact

Sample No.: Sample ID: Sample Matrix:

Soil

Preservative:

reservative:

Condition:

Cool

Bottom @ Directly below BGT

Project #:

03056-0106

Date Reported:

4/18/2008

Date Sampled:

4/8/2008

Date Analyzed:

4/8/2008

Analysis Needed:

TPH-418.1

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

448

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis

of Water and Waste, USEPA Storet No. 4551, 1978.

Comments:

Jic Joint Venture KD #1

Instrument calibrated to 200 ppm standard. Zeroed before each sample

Analyst

Nicole Hayworth

Greg Crabtree

Printed

Printed



CONTINUOUS CALIBRATION EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Cal	Date:
1 .71	Date

Printed

8-Apr-08

Parameter	Standard Concentration mg/L	Concentration Reading mg/L	
ТРН	100 200 500	190	
	1000		

The accepted percent relative deviation (%RSD) of the calibration factor is less than 20% over the working range.

Analyst Hayreat	<u>64 1/8 /08</u> Date
Nicole Hayworth	
Printed	
Muz Cult	4/10/00
Review	Date
Greg Crabtree	