submitted in lieu of Form 3160-5

JUL 0.1 2008

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Bureau of Land Management Farmington Field Office

	Sundry Notices and Reports of	n Wells		
		II WOIS	5.	_ Lease Number
1.	Type of Well GAS	JUL 0 3 2008	6.	NMNM-555078 If Indian, All. or Tribe Name Unit Agreement Name
			7.	
2.	Name of Operator BURLINGTON	FARMINGTON FIELD OFFICE BY		
	RESCURCES OIL & GA	AS COMPANY LP		
3.	Address & Phone No. of Operator		 8.	Well Name & Number
	PO Box 4289, Farmington, NM 874	199 (505) 326-9700	9.	Helm Federal 1G API Well No.
4.	Location of Well, Footage, Sec., T, R, M			30-045-34654
			10.	Field and Pool
Q)	Unit C (NENW), 1080' FNL & 177	0' FWL, Sec. 22, T30N, R10W, NMPM		Basin Dakota
τ			11.	County and State San Juan Co., NM
	X Subsequent Report	Abandonment Change of Plans Plugging Non-Routine Fracturing Casing Repair Water Shut off Altering Casing Conversion to Injection	X Other – Cas	RCVD JUL 3'08 OIL CONS. DIV.
13	. Describe Proposed or Completed C	Operations		DIST. 3
D/Pu Ce Ce Ce 6/2 ahd lar w//Ce	TO cement & then ahead to 3205' – 6/24 imped a preflush of 10 bbls gel H2O and blloflake, 5#/sx LCM-1, 0.4% FL-52 and blloflake, 5#/sx LCM-1, 0.4% FL-52 and blloflake and 0.2% FL-52. Dropped plut 26/08 PT casing to 1500 # @ 0630 hrs. ead to 7509' (TD). TD reached 6/27/0 inded casing @ 7509'. RU to cement. If 0.25#/sx Celloflake, 0.3% CD-32, 6.25#/sx LCM-	OK. 6/23/08 PT casing to 600#/30 min. OK. RI 4/08. Circ. hole. RIH w/80 jts 7", 20#, J-55 ST& d 2 bbls FW. Scavenger - 19 sx (57 cf - 10 bbls d 0.4% SMS. Lead pumped -428 sx (912 cf - 2 d 0.4% SMS. Tailed w/76 sx (1015 cf - 19 bbls ag and displaced and circ. 19 bbls cement to surface for 30 min. Good test. RIH w/6-1/4" bit & tag 8. Circ. hole. RIH w/163 jts of 4-1/2" J-55 LT& Pumped 10 bbls CW & 2 bbls FW ahead of Scave 6#/sx LCM-1, 1% FL-52. Tailed w/306 sx (605 1, 1% FL-52. Dropped plug and displaced w/120 menters. ND BOP, RD & released rig 6/29/08 d	C casing and s) Premium L (62 bbls) Prers) Type III ceace. Plug dover ged cement @ C casing (14 enger – 9 sx of – 108 bbls)	I set @ 3190'. RU to cement. ite w/3% CaC11, 0.25#/sx mium Lite w/3% CaC1 .25#/sx ment w/1% CaC11, 0.25#/sx vn @ 2230 hrs. 6/25/08. WOC @ 3146'. D/O cement and then 4 jts 10.5#, 19 jts 11.6#) & (27 cf – 5 bbls) Premium Lite Premium Lite HS w/0.25#/sx
		ng PT and get the TOC information and the result	lts will be sho	wn on the next report.
	1. I hereby certify that the foregoing gned Halby ells	is true and correct. Patsy Clugston Title Regulatory	Specialist	Date <u>07/01/08</u> .
AF	his space for Federal or State Office us PPROVED BY ONDITION OF APPROVAL, if any:	e)Title		Date

Title 18 U.S.C. Section 1001 makes it a crime for any person knowingly and willfully to make any department or agency of the United States any talse, factitious or traudulent statements or representations as to any matter within its jurisdiction