

Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT S. Lease Serial No. Rureau of Land Manage ISE 1079043

JUL 03 2008

FORM APPROVED

OMB No. 1004-0137 Expires: July 31, 2010

Prim IIII ema

SUNDRY NOTICES AND REPORTS ON WELLShington Field Off Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.				OIL CONS. DIV.	
SUBMIT IN TRIPLICATE - Other instructions on page 2. 1. Type of Well Onl Well Gas Well Other			7. If Unit of CA/Agreement, Name and/or No. Northeast Blanco Unit		
			8. Well Name and No. 421A		
2. Name of Operator Devon Energy Production Company		9. API Well No. 30-045-34610			
3a. Address 20 N. Boradway Oklahoma City, OK 73102		3b. Phone No. (include area co	ode)	10. Field and Pool or Exploratory Area Basin Fruitland Coal	
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Descripti SL 830° FSL & 2,105° FEL, Unit 0, SW SE, Sec. 33, 31N, 7W BHL: 760° FNL & 2,050° FEL, Unit B, NW NE, Sec. 4, 30N, 7W			11. Country or Parish, San Juan, NM		State
12. CHE(CK THE APPROPRIATE BO	DX(ES) TO INDICATE NATUR	RE OF NOTIC	CE, REPORT OR OTHE	R DATA
TYPE OF SUBMISSION		T	YPE OF ACT	ION	
Notice of Intent	Acidize Alter Casing Casing Repair	Deepen Fracture Treat New Construction	Recla	uction (Start/Resume) amation mplete	Water Shut-Off Well Integrity ✓ Other Casing & Cement
✓ Subsequent Report Final Abandonment Notice	Change Plans Convert to Injection	Plug and Abandon Plug Back	Temp	porarily Abandon or Disposal	
5#/sx Gilsonite, 1/4#/sx Flocele, 0,1	1% CFR 3, 0,4% Halad 34	.T&C, 23# casing at 3 <u>.454'</u> , C 4 and tail w/75 sx (16 bbls) S	Cemented lea	v/0.4% Halad 344. Cii	ACCEPTED FOR RECORD JUL 0 3 2008 FARRENGTON FIELD OFFICE
5#/sx Gilsonite, 1/4#/sx Flocele, 0.1 surface. Tested casing to 1,500 ps	1% CFR 3, 0.4% Halad 34	4 and tail w/75 sx (16 bbls) S	Cemented lea	v/0.4% Halad 344. Cii	ACCEPTED FOR RECORD JUL 0 3 2008
5#/sx Gilsonite, 1/4#/sx Flocele, 0.1 surface. Tested casing to 1,500 ps	1% CFR 3, 0.4% Halad 34	4 and tail w/75 sx (16 bbls) S	TD cement v	v/0.4% Halad 344. Cii	ACCEPTED FOR RECORD JUL 0 3 2008
5#/sx Gilsonite, 1/4#/sx Flocele, 0.1 surface. Tested casing to 1,500 ps	1% CFR 3, 0.4% Halad 34	4 and tail w/75 sx (16 bbls) S	TD cement v	v/0.4% Halad 344. Cii	ACCEPTED FOR RECORD JUL 0 3 2008
5#/sx Gilsonite, 1/4#/sx Flocele, 0.1 surface. Tested casing to 1,500 ps 14. I hereby certify that the foregoing is to the Melisa Castro	true and correct. Name (Printe	4 and tail w/75 sx (16 bbls) S ed/Typed) Title Senior	Staff Operat	ions Technician	ACCEPTED FOR RECORD JUL 0 3 2008
Drilled 8 3/4" hole to 3_460' on 6/20, 5#/sx Gilsonite, 1/4#/sx Flocele, 0.1 surface. Tested casing to 1,500 ps 14. I hereby certify that the foregoing is to Melisa Castro Signature Approved by	true and correct. Name (Printe	4 and tail w/75 sx (16 bbls) Since ded/Typed) Title Senior	Staff Operat	ions Technician 30 , 7068 FICE USE	ACCEPTED FOR RECORD JUL 0 3 2008

fictitious or fraudulent statements or representations as to any matter within its jurisdiction.