RECEIVED

Form 3160-5 (April 2004)

CR

UNITED STATES DEPARTMENT OF THE INTERIOR

JUN 09 2008

FORM APPROVED OM B No 1004-0137 Expires: March 31, 2007

	BUREAU OF LAND MANAGEMENT		Seineal Serial No	
SUNDRY NOTICES AND REPORTS ON WELLESgion Field C			ncesf 079060	
Do not use ti	his form for proposals to drill or ell. Use Form 3160-3 (APD) for s	to re-enter an	6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE- Other instructions on reverse side.			7. If Unit or CA/Agreement, Name and/or No.	
1. Type of Well Gas Well Other			8. Well Name and No.	
2. Name of Operator Devon Energy Production Company, L.P.			NEBU 19N 9. API Well No.	
3a. Address 20 N. Broadway, Oklahoma C		No. (include area code) -7917	30-039-30216 10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			Basin Dakota/La Jara Pictured Cliffs	
	SE SE, Unit P, Sec. 20, T30N- R7W , SW SE, Unit O, Sec. 20, T30N- R7W		11. County or Parish, State Rio Arriba, NM	
12. CHECK A	PPROPRIATE BOX(ES) TO INDICATE	NATURE OF NOTICE, R	EPORT, OR OTHER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION		
Notice of Intent ✓ Subsequent Report	Acidize □ Deepen Alter Casing □ Fracture □ ✓ Casing Repair □ New Con	Freat Reclamation	_ ~ ~ ~	
Final Abandonment Notice	Change Plans Plug and D	Abandon Temporarily Ab	pandon	
testing has been completed. Findetermined that the site is ready Estimated TOC for the 4 5,676'. Drilled out the DV Remedial work began with 9, 1% CFR-3, 1% HR-5 w/.4% Halad-9, 1% CFR-3, 1% & est TOC @ 5,400'. RIH squeeze holes @ 5,200' and	nal Abandonment Notices shall be filed only after to final inspection.) 1/2", J-55, LT&C, 11.6# casing is at 6,362'. Tool. h perforations at 6,330' & 5,720'. A 4 1/2" of was pumped. A cement plug was set outside3, .1% HR-5 was pumped. A second cement HR-5 was pumped. Pump 110 bbls 50/50 F & perf squeeze holes @ 5.600'. Set retreive	The casing was run with an A cement retainer was set @ 5,74 e 4 1/2" due to belief of water in the plug was spot outside 4 1/2" POZ w/.4% Halad-9, .1% CGF omatic packer @ 5,271 then pu Drill out to 5,720' lose returns	CP @ 5,678' and a Hydraulic DV tool @ 15' then 100 sx 50/50 POZ w/.4% Halad falling pas ACP, batch mix 5 bbls 50/50/ POZ	
Between TOC = 7" Casing shot Messaverle and lower Lewis. RCVD JUL 9'08				
			OIL CONS. DIV. DIST. 3	
14. I hereby certify that the fore	going is true and correct	I		
Name (Printed/Typed) Melisa Castro		Title Senior Staff Operation	s Technician	
Signature Signature	1	Date Date	4, 2008	
The second second	THIS SPACE FOR FEDERAL			
	ttached Approval of this notice does not warra		Date	
certify that the applicant holds legal which would entitle the applicant to	or equitable title to those rights in the subject le conduct operations thereon.	ase Office		
Title 18 U.S C. Section 1001 and Title States any false, fictitious or fraudul	43 U.S.C. Section 1212, make it a crime for any ent statements or representations as to any matter	person knowingly and willfully to r within its jurisdiction.	o make to	

NMOCD

JUN 1 6 2008

0

(Instructions on page 2)