In Lieu of Form 3160

RECEIVED UNITED STATES DEPARTMENT OF INTERIOR 17 2008

SEC 27,T31N,R5W

FORM APPROVED					
Budget Bureau No. 1004-0135					
Expires: March 31 1993					

(June 1	BUREAU OF LAND MANAGEMENTUL V 7 2000		Budget Bureau No. 1004-0135 Expires: March 31, 1993	
SUNDRY NOTICE AND REPORTS ON WELL of Land Manager File Control of the Control of		5.	Lease Designation and Serial No SF-078770	
	TO DRILL" for permit for such proposals	6.	If Indian, Allottee or Tribe Name	
	SUBMIT IN TRIPLICATE	7	If Unit or CA, Agreement Designation Rosa Unit	
1.	Type of Well Oil Well Gas Well X Other	8.	Well Name and No. Rosa Unit #378A	
2.	Name of Operator WILLIAMS PRODUCTION COMPANY	9.	API Well No. 30-039-30152	
3.	Address and Telephone No. PO Box 640 Aztec, NM 87410-0640	10.	Field and Pool, or Exploratory Area BASIN FRUITLAND COAL	
4.	Location of Well (Footage, Sec., T., R., M., or Survey Description) 510' FSL & 2225' FEL,	11.	County or Parish, State RIO ARRIBA	

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Change of Plans

Notice of Intent

Subsequent Report

Final Abandonment

990' FSL & 2225' FEL

Abandonment Recompletion Plugging Back Casing Repair Altering Casing X Other SURFACE CASING

New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection

Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/4/08

TD- 12 1/4" SURFACE HOLE @ 347, 2230 HRS 7/3/08 Ran 7 JTS, 9 5/8' 36 #, K-55, STC, CSG SET @ 336'. FC @ 286'. RCVD JUL 10'08

OIL CONS. DIV.

DIST. 3

7/5/08

CEMENT 9-5/8" CASING @ 335' - SHOE DEPTH / SINGLE SLURRY CEMENT JOB / 20 BBLS. FRESH WATER SPACER / 200 SXS TYPE 3 CEMENT + 2% CaCl-2 + .25#/SX CELLO FLAKE + 50.2 BBL. WATER = 92 BBL. (278 CuFt) SLURRY @ 14.5 PPG (YIELD = 1.41 / WGPS = 6.84) / DISPLACE WITH 22.3 BBL. WATER / PLUG DOWN ON 7/4/2008 @ 0745 AM 24 BBL .OF CEMENT RETURNS TO SURFACE.

INSTALL TEST PLUG & TEST BOP PIPE & BLIND RAMS, CHOKE MANIFOLD VALVES, MUD CROSS VALVES, FLOOR VALVE

ACCEPTED FOR PIECORD KELLY @ 250# 5-MIN EACH & 1500# 10-MIN EACH. TEST 9 5/8." CSG @ 1500# 30-MIN. TEST PUMP & TEST CHARTS USED ON ALL TEST. ALL TESTED GOOD.

JUL 0 9 2008

FARMINGTON FIELD OFFICE

			BY dy	
14.	I hereby certify that the foregoing is true and correct			
	Signed Larry Higgins Hygy	Title <u>Drilling C.O.M.</u>	Date 7/7/08	
	(This space for Federal or State office use)			
	Approved by	Title	Date	
	Conditions of approval, if any:			

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.