<u>Dist.€t I</u>

1625 N French Dr, Hobbs, NM 88240

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S St Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources**

Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

June 16, 2008 For temporary pits, closed-loop sytems, and below-grade

Form C-144

tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

	lity should operations result in pollution of surface water, ground water or the
Operator: Burlington Resources Oil & Gas Company, LP	OGRID#: 14538
Address: PO Box 4289, Farmington, NM 87499	RCVD JUL 15 VB
Facility or well name: San Juan 29-7 Unit #31A	UIL CONS. DIV.
API Number: 30-039-22065 OC	D Permit Number:
U/L or Qtr/Qtr: J(NWSE) Section: 32 Township: 29N	Range: 7W County: Rio Arriba
	ongitude: 107.590650' W NAD: 1927 X 1983 al Trust or Indian Allotment
Pit: Subsection F or G of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Seams: Welded Factory Other Volume: bbl Dimensions: L xW xD	X Closed-loop Systems: Subsection H of 19.15.17.11 NMAC Drying Pad X Tanks Haul-off Bins Other: Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other: Seams: Welded Factory Other: Volume: 500 bbl 104 yd3 Dimernsions: Length 45' x Width 10'
Below-grade tank: Volume:bbl Type of fluid: Tank Construction Material: Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other: Liner type: Thickness: mil HDPE PVC Other:	Fencing: Subsection D of 19 15.17.11 NMAC Chain link, six feet in height, two strangs of barbed wire at top Four foot height, four strands of barbed wire evenly spaced between one and four feet Netting: Subsection E of 19.15.17.11 Screen Netting Other Monthly inspections Signs: Subsection C of 19.15 17.11 NMAC 12"x 24", 2" lettering, provided Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19.15.3.103 NMAC
Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.		
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□Yes	No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	□Yes	□No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No
(Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	□NA	
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	□Yes	□No
(Applied to permanent pits)	□NA	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image		
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	□No
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.		
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	Yes	□No
- Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. LIS Fish and Wildlife Wetland Identification many Transportant areas Visual representation (certification) of the presentation.	Yes	□No
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site Within the area overlying a subsurface mine.	□ v	
- Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	∐Yes	□No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological	Yes	No
Society; Topographic map Within a 100-year floodplain	∏Yes	\square_{N_0}
- FEMA map		
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17. Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the definition of the following items must be attached to the application.		e attached.
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 I Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15 17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintence Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Previously Approved Design (attach copy of API Number:	NMAC	
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC		
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19	.15.17.9	re
Situng Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.10 N! X Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	MAC	
X Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC		
X Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC		
Previously Approved Design (attach copy of API Number:		

Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are	ıttached.
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC	
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Climatological Factors Assessment	
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC	
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC	
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC	
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC	!
Quality Control/Quality Assurance Construction and Installation Plan	
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
Nuisance or Hazardous Odors, including H2S, Prevention Plan	
Emergency Response Plan	
Oil Field Waste Stream Characterization	
Monitoring and Inspection Plan	
Erosion Control Plan	
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC	
Type: Drilling Workover Emergency Cavitation Permanent Pit Below-grade Tank X Closed-loop System Alt	ernative
Description of the LD 1	i
Proposed Closure X Waste Excavation and Removal On-site Closure Method (only for temporary pits and closed-loop	
☐ In-place ☐ On-site Trench ☐ Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau	for
Alternative Closure Method (Exceptions must be submitted to the Santa re Environmental Bureau	101
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC	
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommentations of acceptable source	
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate	
district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.	
Ground water is less than 50 feet below the bottom of the buried waste.	
- NM Office of the State Engineer - IWATERS database search; USGS; Data obtained from nearby wells	☐Yes ☐No
	☐Yes ☐No ☐NA
Ground water is between 50 and 100 feet below the bottom of the buried waste	
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells	□NA □
- NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste.	∏NA ∏Yes ∏No
- NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells	NA Yes No
- NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste.	NA Yes No NA Yes No NA Yes No
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). 	NA Yes No NA Yes No NA
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	NA Yes No NA Yes No NA Yes No NA Yes No
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial 	NA Yes No NA Yes No NA
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	NA Yes No NA Yes No NA Yes No Yes No
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic 	NA Yes No NA Yes No NA Yes No NA Yes No
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	NA Yes No NA Yes No NA Yes No Yes No
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time 	NA Yes No NA Yes No NA Yes No Yes No
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	NA Yes No NA Yes No NA Yes No NA Yes No Yes No Yes No
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. 	NA Yes No NA Yes No NA Yes No Yes No
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal 	NA Yes No NA Yes No NA Yes No NA Yes No Yes No Yes No
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended 	NA Yes No NA Yes No NA Yes No NA Yes No Yes No Yes No
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Written confirmation or verification from the municipality; Written approval obtained from the municipality 	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).	NA Yes No NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. 	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No
- NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	NA Yes No NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No Yes No
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).	NA Yes No NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division Within an unstable area. 	NA Yes No NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No Yes No
 NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. proposed site Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM 	NA Yes No NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No Yes No

Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicfate, by a check mark in the box, that the documents are attached.
X Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC
Confirantion Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC
X Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19 15.17.13 NMAC
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15 17 13 NMAC
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17 13 NMAC
Waste Removal Closure for Closed-loop Systems That Utilize Haul-off Bins Only: (19 15 17 13 D NMAC) Instructions: Please identify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings.
Disposal Facility Name. Envirotech, Basin Disposal Disposal Facility Permit Number. NM-01-0011 & NM-01-005
On-Site Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.
String Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17 10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC
Construction and Design of Burial Trench (if applicable) based upon the appropriate requirements of 19 15 17 11 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15 17.13 NMAC
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15.17 13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15.17.13 NMAC
- =
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be
Soil Cover Design - based upon the appropriate requirements of Subsection H of 19 15 17 13 NMAC
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15 17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC
Operator Application Certification:
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.
Name (Print): Crystal Tafoya Title. Regulatory Technician
Signature: Constal Talogo Date. 7/14/2008
e-mail address. <u>crystal.tafoya@conocophilips.com</u> Telephone. <u>505-326-9837</u>
OCD Assessed F Descrit Application (solutions also used to)
OCD Approval: Permit Application (including closure plan) Closure Plan (only)
OCD Representative Signature: Bl 63th Approval Date: 7-15-08
OCD Representative Signature: BlbBbb Approval Date: 7-15-08 Title: Ensire/Sec OCD Permit Number
OCD Representative Signature: BlbBbbbbbbbbbbbbbbbbbbbbbbbbbbbbbbbbbb
OCD Representative Signature: BlbBbb Approval Date: 7-15-08 Title: Ensire/Sec OCD Permit Number
OCD Representative Signature: Blbbll Approval Date: 7-15-08 Title: Enviro/Sec OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Completion Date:
OCD Representative Signature: Blbbbbb Approval Date: 7-15-08 Title: Enjiro/Sec OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Method: Waste Excavation and Removal On-Site Closure Alternative Closure
OCD Representative Signature: Blbbll Approval Date: 7-15-08 Title: Enviro/Sec OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Completion Date:
OCD Representative Signature: Blefall Approval Date: 7-15-08 Title: Ensire Spec OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Completion Date: Closure Method: Waste Excavation and Removal On-Site Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the
OCD Representative Signature: Blbbbb Approval Date: 7-15-08 Title: Enjiro Sec OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Completion Date: Closure Method: Waste Excavation and Removal On-Site Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.
OCD Representative Signature: Blefall Approval Date: 7-15-08 Title: Ensire Spec OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Completion Date: Closure Method: Waste Excavation and Removal On-Site Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the
OCD Representative Signature: Blbbbbb Approval Date: 7-15-08 Title: Enjiro Sec OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Method: Waste Excavation and Removal On-Site Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice
OCD Representative Signature: Block Approval Date: 7-15-08 Title: Ensiro/Sec OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Method: Waste Excavation and Removal On-Site Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable)
OCD Representative Signature: Block Sold Sold Sold Sold Sold Sold Sold Sold
Approval Date: 7-15-08 Title: Enrico/spec OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Method: Waste Excavation and Removal On-Site Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number
OCD Representative Signature: Block
OCD Representative Signature: Approval Date: 7-15-08 Title: Enjical Spec OCD Permit Number
Approval Date: 7-15-08 Title: Ensiro Sec. OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 1915 17 13 NMAC Closure Completion Date: Closure Method: Alternative Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation)
OCD Representative Signature: Approval Date: 7-15-08 Title: Enjical Spec OCD Permit Number
Approval Date: 7-15-08 Title: Ensiro Sec. OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 1915 17 13 NMAC Closure Completion Date: Closure Method: Alternative Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation)
Approval Date: 2-15-08 Title: Enjie QCD Permit Number OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Completion Date: Closure Method: Waste Excavation and Removal On-Site Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude. Longitude. NAD 1927 1983
Approval Date: 7-15-08 Title: Enrico Sec. OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 1915 17 13 NMAC Closure Completion Date: Closure Method: Waste Excavation and Removal On-Site Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Unstandard Sampling Analytical Results Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude. Longitude. NAD 1927 1983 Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and behef Labs certify that the
OCD Permut Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Method: Atternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Disposal Faculity Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude. Longitude. NAD 1927 1983 Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief 1 also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan

Form C-144 Oil Conservation Division

Page 4 of 4

NEW MEXICO OIL CONSERVATION COMMISSION WELL LOCATION AND ACREAGE DEDICATION PLAT

Torm C-102 Supersedes C-128 Effective 1-1-65

All distances must be from the outer houndaries of the Section Well Ho. (B-10037-47) EL PASO NATURAL GAS COMPANY SAN JUAN 29-7 UNIT Cont Letter 30 clion Township 29N RIO ARRIBA Actual Lott the Location of Well: South 1770 . feet from the feet from the line and line Growt Level Llev. Producing Formation Dudicated Acrenges Blanco Mesa Verde 320.00 6723 Mesa Verde Асты 1. Outline the acreage dedicated to the subject well by colored pencil or bechure marks on the plat below. 2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty). 3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc? Unitization If answer is "yes," type of consolidation ._ If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.). No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission. CERTIFICATION I hereby certify that the information contained herein is true and complete to the B-10037-47 B-10037-46 best of my knowledge and belief. Drilling Clerk El Paso Natural Gas Co. Company B-10037-46 B-10037-42 5-10-79 Sec I hereby certify that the well location B-10037-47 shown on this plat was plotted from field notes of actual surveys made by me or 17701 under my supervision, and that the same is true and correct to the best of my knowledge and belief. B-10037-51

Burlington Resources Oil & Gas Company, LP Closed-loop Plans

Closed-loop Design Plan

BR's closed loop system will not entail a drying pad, temporary pit, below grade tank or sump. It will include an above ground tank suitable for holding the cuttings and fluids for rig operations. The tank will be sufficient volume to maintain a safe free board between disposal of the liquids and solids from rig operations.

- 1. Fencing is not required for an above ground closed-loop system
- 2. It will be signed in compliance with 19.15.3.103 NMAC
- 3. A frac tank will be on location to store fresh water

Closed-loop Operating and Maintenance Plan

BR's closed-loop tank will be operated and maintained to contain liquids and solids in order to prevent contamination of fresh water sources, in order to protect public health and the environment. To ensure the operation is maintained the following steps will be followed:

- 1. The liquids will be vacuumed out and disposed of at the Basin Disposal facility (Permit # NM-01-005). Solids in the closed-loop tank will be vacuumed out and disposed of at Envirotech (Permit # NM-01-0011) on a periodic basis to prevent over topping.
- 2. No hazardous waste, miscellaneous solid waste or debris will be discharged into or stored in the tank. Only fluids or cutting used or generated by rig operations will be placed or stored in the tank.
- 3. The division district office will be notified within 48 hours of the discovery of compromised integrity of the closed-loop tank. Upon the discovery of the compromised tank, repairs will be enacted immediately
- 4. All of the above operations will be inspected and a log will be signed and dated. During rig operations the inspection will be daily.

Closed-loop Closure Plan

The closed-loop tank will be closed in accordance with 19.15.17.13. This will be done by transporting cuttings and all remaining sludges to Envirotech (Permit # NM-01-0011) immediately following rig operations. All remaining liquids will be transported and disposed of in the Basin Disposal facility (Permit # NM-01-005). The tanks will be removed from the location as part of the rig move. At time of well abandonment, the site will be reclaimed and re-vegetated to pre-existing conditions when possible.