Districa I

1625 N French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd , Aztec, NM 87410

District IV

1220 S St. Francis Dr , Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

> Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

June 16, 2008 For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

Form C-144

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Type of action: X Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method

Address: PO Box 4289, Farmington, NM 87499 RacUlty or well name: Hale #1 API Number: 30-045-10356 OCD Permit Number: DIJ CRMS. BRU API Number: DI	Instructions: Please submit one application (Form C-144) per individus Please be advised that approval of this request does not relieve the operator of habit environment. Nor does approval relieve the operator of its responsibility to comply with	ity should operations result in pollution of surface water, ground water or the
Facility or well name: Hale #1		OGRID#: 14538
API Number: 30-045-10356 OCD Permit Number: DIST, 3 U/L or Qtr/Qtr: A(NENE) Section: 27 Township: 31N Range: 8W County: San Juan Center of Proposed Design: Latitude: 36.873933 'N Longitude: 107.657533' W NAD: X 1927	Address: PO Box 4289, Farmington, NM 87499	
Content of Proposed Design: Latitude: 36.873933' N	Facility or well name: Hale #1	<u> </u>
Center of Proposed Design: Latitude: 36.873933' N Longitude: 107.657533' W NAD: X 1927 1983 Surface Owner: X Federal State Private Tribal Trust or Indian Allotment Pit: Subsection F or G of 19.15.17.11 NMAC Tribal Trust or Indian Allotment Pit: Subsection F or G of 19.15.17.11 NMAC Temporary: Drilling Workover Permanent Emergency Cavitation Lined Unlined Unlined Unlined Line type: Thickness mil LLDPE HDPE PVC Other: String-Reinforced String-Reinforced String-Reinforced Seams: Welded Factory Other Soon bbl 104 yd3 Dimensions: L xW xD Dimensions: Length 45" x Width 10" Below-grade tank: Subsection 1 of 19.15.17.11 NMAC Chain link, six feet in height, two strangs of barbed wire at top Four foot height, four strands of barbed wire evenly spaced between one and four feet String-Reinforced Signs: Subsection E of 19.15.17.11 NMAC String-Reinforced Signs: Subsection E of 19.15.17.11 NMAC Chain link, six feet in height, two strangs of barbed wire at top Four foot height, four strands of barbed wire evenly spaced between one and four feet Signs: Subsection E of 19.15.17.11 NMAC Screen Netting: Subsection E of 19.15.17.11 NMAC Screen Netting: Subsection E of 19.15.17.11 NMAC Signs: Subsection E of	API Number: 30-045-10356 OC	D Permit Number: DIST, 3
Surface Owner:	U/L or Qtr/Qtr: A(NENE) Section: 27 Township: 31N	Range: 8W County: San Juan
Pit: Subsection F or G of 19.15.17.11 NMAC	Center of Proposed Design: Latitude: 36.873933' N L	ongitude:107.657533' W NAD: X 1927 1983
Temporary: Drilling Workover Permanent Emergency Cavitation Lined Unlined Lined Unlined Linet type: Thickness mil LLDPE HDPE PVC Other String-Reinforced Seams: Welded Factory Other Volume: 500 bbl 104 yd3 Volume: bbl Dimensions: xw xD Dimensions: Length 45' x Width 10' Below-grade tank: Subsection I of 19.15.17.11 NMAC Chain link, six feet in height, four strands of barbed wire at top Four foot height, four strands of barbed wire evenly spaced between one and four feet Netting: Subsection E of 19.15.17.11 NMAC Signs: Subsection E of 19.15.17.11 NMAC Other: Monthly inspections Signs: Subsection C of 19.15.17.11 NMAC Signs: Subsection C of 19.15.17.11 NMAC Signs: Subsection E of 19.15.17.11 NMAC Signs: Signs: Subsection E of 19.15.17.11 NMAC Signs: Subsection E of 19.15.17.11 NMAC Signs: Signs: Subse	Surface Owner: X Federal State Private Triba	al Trust or Indian Allotment
Permanent Emergency Cavitation Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Unter type: Thickness mil HDPE PV	Pit: Subsection F or G of 19.15.17.11 NMAC	X Closed-loop Systems: Subsection H of 19.15.17.11 NMAC
Liner type: Thickness	Temporary: Drilling Workover	Drying Pad X Tanks Haul-off Bins Other:
Liner type: Thickness	Permanent Emergency Cavitation	Lined Unlined
Other	Lined Unlined	Liner type: Thickness mil LLDPE HDPE PVC
Scams: Welded Factory Other Volume: 500 bbl 104 yd3 Dimensions: L xW xD Dimensions: Length 45' x Width 10' Below-grade tank; Subsection I of 19.15.17.11 NMAC Chain link, six feet in height, two strangs of barbed wire at top Four foot height, four strands of barbed wire evenly spaced between one and four feet Netting: Subsection E of 19.15.17.11 Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Screen Netting: Subsection E of 19.15.17.11 Visible sidewalls and liner Monthly inspections Signs: Subsection C of 19.15.17.11 NMAC Other: 12"x 24", 2" lettering, provided Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19.15.3.103 NMAC Alternative Method: Submitted to the Santa Fe Environmental Bureau office for consideration of approval Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of paproval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe	Liner type: Thickness mil LLDPE HDPE PVC	Other:
Scams: Welded Factory Other Volume: 500 bbl 104 yd3 Dimensions: L xW xD Dimensions: Length 45' x Width 10' Below-grade tank: Subsection I of 19.15.17.11 NMAC Chain link, six feet in height, two strangs of barbed wire at top Four foot height, four strands of barbed wire evenly spaced between one and four feet Netting: Subsection E of 19.15.17.11 Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Screen Netting: Subsection E of 19.15.17.11 Visible sidewalls and liner Monthly inspections Signs: Subsection C of 19.15.17.11 NMAC Other: 12"x 24", 2" lettering, provided Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19.15.3.103 NMAC Alternative Method: Submitted to the Santa Fe Environmental Bureau office for consideration of approval Administrative approval(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of performance of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of performance in Design Plan) Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe	Other String-Reinforced	Seams: Welded Factory Other:
Dimensions: L xW xD Dimensions: Length 45' x Width 10'		Volume: 500 bbl 104 yd3
Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume:	Volume; bbl Dimensions; L xW xD	Dimernsions: Length 45' x Width 10'
Volume:bbl		
Type of fluid:	Below-grade tank: Subsection I of 19.15.17.11 NMAC	Fencing: Subsection D of 19.15.17.11 NMAC
Tank Construction Material: Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Signs: Subsection C of 19.15.17.11 NMAC Other: Liner type: Thickness: Other: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe	Volume:bbl	Chain link, six feet in height, two strangs of barbed wire at top
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls and liner Visible sidewalls and liner Visible sidewalls only Signs: Subsection C of 19.15.17.11 NMAC Other:		Four foot height, four strands of barbed wire evenly spaced between
Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls and liner Visible sidewalls and liner Visible sidewalls and liner Visible sidewalls only Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, provided Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19.15.3.103 NMAC Administrative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe	Tank Construction Material:	one and four feet
Visible sidewalls and liner	Secondary containment with leak detection	Netting: Subsection E of 19.15.17.11
Visible sidewalls only Signs: Subsection C of 19.15.17.11 NMAC Other:	Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off	Screen Netting Other
Dther:	Visible sidewalls and liner	Monthly inspections
Liner type: Thickness: mil	Visible sidewalls only	Signs: Subsection C of 19.15.17.11 NMAC
Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe	Other:	12"x 24", 2" lettering, provided Operator's name, site location, and
Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe	Liner type: Thickness:mil HDPE PVC	emergency telephone numbers
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval Dustifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe	Other:	X Signed in compliance with 19.15.3.103 NMAC
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval Dustifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe	Alternative Method:	Administrative Approvals and Exceptions:
of approval Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe	Submittal of an exception request is required. Exceptions must be	Justifications and/or demonstrations of equivalency are required. Please
leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe		1
Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe	or approvat	
office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe		Administrative approval(s): Requests must be submitted to the
Exception(s): Requests must be submitted to the Santa Fe		
Environmental Bureau office for consideration of approval.		Environmental Bureau office for consideration of approval.


Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.				
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes	□No		
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	□Yes	□No		
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No		
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)	\prod NA			
Visual inspection (certification) of the proposed site; Aerial photo; Satellite image				
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	No		
 (Applied to permanent pits) Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	∐NA			
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	□No		
- NM Office of the State Engineer - 1WATERS database search; Visual inspection (certification) of the proposed site.				
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	Yes	□No		
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	П.,	—		
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	∐Yes	∐No		
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	□No		
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes	No		
Within a 100-year floodplain - FEMA map	Yes	No		
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.	9 NMAC			
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the definition of the following items must be attached to the application.	ocuments ar	e attached.		
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintence Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC				
Previously Approved Design (attach copy of API Number: or Permit				
Closed-loop Systems Permit Application Attachment Checklist: Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19 Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.11 NMAC Toperating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	0.15.17.9	re		
Previously Approved Design (attach copy of API Number:				

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC						
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.						
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC						
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC						
Climatological Factors Assessment						
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC						
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC						
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC						
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC						
Quality Control/Quality Assurance Construction and Installation Plan						
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC						
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC						
Nuisance or Hazardous Odors, including H2S, Prevention Plan						
Emergency Response Plan						
Oil Field Waste Stream Characterization						
Monitoring and Inspection Plan						
Erosion Control Plan						
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC						
Proposed Closure: 19.15.17.13 NMAC						
Type: Drilling Workover Emergency Cavitation Permanent Pit Below-grade Tank X Closed-loop System Alter	native					
Proposed Closure X Waste Excavation and Removal						
On-site Closure Method (only for temporary pits and closed-loop						
In-place On-site Trench						
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau f	for					
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC	1					
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommentations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of						
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of						
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate						
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.	□Ver □No					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste.	∐Yes ∏No ∏NA					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□NA □					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste	ı ≓ '' ı					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells	□NA □Yes□No □NA					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste.	□NA □Yes□No □NA					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells	NA Yes No NA Yes No					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal	NA Yes No NA Yes No NO					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	NA Yes No NA Yes No NO					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial	NA Yes No NA Yes No NO					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	NA Yes No NA Yes No NA Yes No Yes No Yes No					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic	NA Yes No NA Yes No NA Yes No NA Yes No					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time	NA Yes No NA Yes No NA Yes No Yes No Yes No					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA Yes No NA Yes No NA Yes No Yes No Yes No					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	NA Yes No NA Yes No NA Yes No Yes No Yes No					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	NA Yes No NA Yes No NA Yes No Yes No Yes No					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	NA Yes No NA Yes No NA Yes No Yes No Yes No					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the	NA Yes No NA Yes No NA Yes No Yes No Yes No					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval. In may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Within 500 feet of a wetland.	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or my be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Within 500 feet of a wetland. Within 500 feet of a wetland.	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste. NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - 1WATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Within 500 feet of a wetland. Within the area overlying a subsurface mine. Within the area overlyin	NA Yes No NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No Yes No					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste. NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - 1WATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Within 500 feet of a wetland. Proposed site Within the area overlying a subsurface mine. Within an	NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No					
material are provided below. Requests regarding changes to certain siting criteria may require diministrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Within 500 feet of a wetland. Proposed site Within 40 as a subsurface mine. Within 600 feet of a we	NA Yes No NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No Yes No					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo, Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Within 500 feet of a wetland. Within 500 feet of a wetland. Proposed site Within the area overlyin	NA Yes No NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No Yes No Yes No					
material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance. Ground water is less than 50 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is between 50 and 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended Within 500 feet of a wetland. Proposed site Within an unstable area. Engineering measures incorpora	NA Yes No NA Yes No NA Yes No NA Yes No Yes No Yes No Yes No Yes No Yes No					

Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate by a check mark in the box, that the documents are attached				
to the closure plan. Please indicfate, by a check mark in the box, that the documents are attached. X Protocols and Procedures - based upon the appropriate requirements of 19 15.17.13 NMAC				
Confirantion Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)				
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC				
X Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15 17 13 NMAC				
X Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC				
Waste Removal Closure for Closed-loop Systems That Utilize Haul-off Bins Only: (19 15 17 13 D NMAC) Instructions: Please identify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings.				
Disposal Facility Name: Envirotech, Basin Disposal Disposal Disposal Facility Permit Number: NM-01-0011 & NM-01-005				
On-Site Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the following items must bee attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.				
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
Construction and Design of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC				
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.11 NMAC				
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17 13 NMAC				
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be				
Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15 17 13 NMAC				
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC				
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19 15.17.13 NMAC				
Operator Application Certification:				
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.				
Name (Print): Crystal Tafoya Title. Regulatory Technician				
Signature: Date: 7/14/2008				
e-mail address: <u>cfystal tafoya@conocoptfflips.com</u> Telephone. <u>505-326-9837</u>				
OCD Assessed And Society (reduction design and and a second and a seco				
OCD Approval; / Permit Application (including closure plan) Closure Plan (only)				
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Representative Signature: 7-15-08				
OCD Representative Signature: 33 6 30 Approval Date: 7-15-08 Title: En Ji 10 Spec OCD Permit Number				
OCD Representative Signature: 33/6-00 Approval Date: 7-/5-08				
OCD Representative Signature: 336536 Approval Date: 7-/5-08 Title: En Ji 10 Spec OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Completion Date:				
OCD Representative Signature: 33 6 30 Approval Date: 7-/5-08 Title: En Ji 10 Spec OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Completion Date: Closure Method:				
OCD Representative Signature: 33 6 36 COD Permit Number: 7-75-08 Title: En Jito Spec OCD Permit Number: Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Method: Alternative Closure Alternative Closure				
Approval Date: 7-/5-08 Title: En Ji / O Spec OCD Permit Number				
OCD Representative Signature: B 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6				
Approval Date: 7-/5-08 Title: En Ji / O Spec OCD Permit Number				
Approval Date: 7-/5-08 Title: Enviro Spec OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Method: Waste Excavation and Removal On-Site Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable)				
Approval Date: 7-/5-08 Title:				
Approval Date: 7-15-08 Title: Enviro Spec OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Method: Closure Completion Date: Closure Method: Alternative Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results				
Approval Date: 7-15-08 Title: En Jilo Spec OCD Permit Number: Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Method: Waste Excavation and Removal On-Site Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results				
Approval Date: 7-15-08 Title: Enviro Spec OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Completion Date: Closure Method: Waste Excavation and Removal On-Site Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number				
Approval Date: 7-15-08 Title: En Jilo Spec OCD Permit Number: Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Method: Waste Excavation and Removal On-Site Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results				
Approval Date: 7-/5-08 Title: EnvirolSpec OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Completion Date: Closure Method: Waste Excavation and Removal On-Site Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation				
Approval Date: 7-/5-08 Title: Enviro Spec OCD Permit Number Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Method: Closure Completion Date: Closure Method: Alternative Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique				
Approval Date: 7-/5-08 Title: En 1/0 Spec OCD Permit Number: Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Method: Closure Completion Date: Closure Completion Date: Closure Method: Closure Excavation and Removal On-Site Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) Con-site Closure Longitude NAD: 1927 1983				
Approval Date: 7-/5-08 Title: Enviro Spec OCD Permit Number: Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Completion Date: Closure Method: Waste Excavation and Removal On-Site Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude: Longitude NAD: 1927 1983 Operator Closure Certification: Thereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief I also certify that the				
Approval Date: 7-/5-08 Title: Envivo/Spec OCD Permit Number: OCD Perm				
Approval Date: 7-/5-08 Title: Enviro Spec OCD Permit Number: Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Closure Completion Date: Closure Method: Waste Excavation and Removal On-Site Closure Alternative Closure If different from approved plan, please explain Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude: Longitude NAD: 1927 1983 Operator Closure Certification: Thereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief I also certify that the				
Approval Date: 7-/5-08 Title: Envivo/Spec OCD Permit Number: OCD Perm				

Page 4 of 4

Form C-144 Oil Conservation Division



U.S. CIC IN OTE SHIVEY FARMINGTON, N. M.

Company	, Sou	ther	unic	n Gas	Com	oany	·····	
Lease			hio			Well No	<u>. 1</u>	OFF THE
Sec	27	T	31 N.	, R	8 W.	N • 1	M.P.M.	
Location	9901	from	the East	North line	line	and	1190	MAY 9 1952 OIL CO
San J	uan C	ounty	7		Nev	Mex.	ico	Dic
			4 6 8			400		
	;					8 ₹	1190-	
					<u> </u>	· · · · · · · · · · · · · · · · · · ·		
			2	7				
		<u> </u>			•	<u> </u>	:	
								N
	,							
				L				
Scale—4		_		7.4		• # A		
This is to of actual same are	surveys	made b	y me or ı	ınder my	y supervi	sion and	that the	
Same are	uue ai	iu corre				Z '	nd bener.	•
		A	Ma	ules		nk	Les Ch	arles J. Finklea
Seal:			E	register ngineer	red Prof and Lar	essional id Surve		Mex. "eg. No. 1302
Surveyed		Nove	mber	10			, 19 <u>51</u>	

Burlington Resources Oil & Gas Company, LP Closed-loop Plans

Closed-loop Design Plan

BR's closed loop system will not entail a drying pad, temporary pit, below grade tank or sump. It will include an above ground tank suitable for holding the cuttings and fluids for rig operations. The tank will be sufficient volume to maintain a safe free board between disposal of the liquids and solids from rig operations.

- 1. Fencing is not required for an above ground closed-loop system
- 2. It will be signed in compliance with 19.15.3.103 NMAC
- 3. A frac tank will be on location to store fresh water

Closed-loop Operating and Maintenance Plan

BR's closed-loop tank will be operated and maintained to contain liquids and solids in order to prevent contamination of fresh water sources, in order to protect public health and the environment. To ensure the operation is maintained the following steps will be followed:

- 1. The liquids will be vacuumed out and disposed of at the Basin Disposal facility (Permit # NM-01-005). Solids in the closed-loop tank will be vacuumed out and disposed of at Envirotech (Permit # NM-01-0011) on a periodic basis to prevent over topping.
- 2. No hazardous waste, miscellaneous solid waste or debris will be discharged into or stored in the tank. Only fluids or cutting used or generated by rig operations will be placed or stored in the tank.
- 3. The division district office will be notified within 48 hours of the discovery of compromised integrity of the closed-loop tank. Upon the discovery of the compromised tank, repairs will be enacted immediately
- 4. All of the above operations will be inspected and a log will be signed and dated. During rig operations the inspection will be daily.

Closed-loop Closure Plan

The closed-loop tank will be closed in accordance with 19.15.17.13. This will be done by transporting cuttings and all remaining sludges to Envirotech (Permit # NM-01-0011) immediately following rig operations. All remaining liquids will be transported and disposed of in the Basin Disposal facility (Permit # NM-01-005). The tanks will be removed from the location as part of the rig move. At time of well abandonment, the site will be reclaimed and re-vegetated to pre-existing conditions when possible.