## ( District )

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St Francis Dr, Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-144 June 16, 2008

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

## Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Type of action:	X Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method
	Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of hability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. OGRID#: 217817 Operator: ConocoPhillips Company Address: PO Box 4289, Farmington, NM 87499 PANAL IN AND Facility or well name: San Juan 31-6 Unit #223 OIL CONS. DIV. DIST. 3 OCD Permit Number: API Number: U/L or Qtr/Qtr: L(NWSW) Section: 32 Township: 31N Range: 6W County: Rio Arriba Center of Proposed Design: Latitude: 36.854120' N Longitude: **107.490780' W** NAD: **X** 1927 1983 Private Tribal Trust or Indian Allotment Surface Owner: Federal  $\mathbf{X}$ State Pit: Subsection F or G of 19.15.17.11 NMAC X Closed-loop Systems: Subsection H of 19.15.17.11 NMAC Drilling Workover Drying Pad X Tanks Haul-off Bins Other: Temporary: Permanent Emergency Cavitation Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Unlined Lined Liner type: Thickness mil LLDPE HDPE PVC Other: String-Reinforced Seams: Welded Factory Other: Seams: Welded Factory Other Volume: bbl yd3 Dimernsions: Length 45' x Width \_\_bbl Dimensions: L \_\_\_xW \_\_xD Below-grade tank: Subsection I of 19.15.17 11 NMAC Fencing: Subsection D of 19.15.17.11 NMAC Volume: bbl Chain link, six feet in height, two strangs of barbed wire at top Four foot height, four strands of barbed wire evenly spaced between Type of fluid: Tank Construction Material: one and four feet Secondary containment with leak detection Netting: Subsection E of 19.15.17.11 Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Screen Netting Visible sidewalls and liner Monthly inspections Visible sidewalls only Signs: Subsection C of 19 15 17.11 NMAC Other: 12"x 24", 2" lettering, provided Operator's name, site location, and Liner type: Thickness: mil HDPE PVC emergency telephone numbers Other: X Signed in compliance with 19.15.3.103 NMAC Alternative Method: **Administrative Approvals and Exceptions:** Submittal of an exception request is required. Exceptions must be Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. submitted to the Santa Fe Environmental Bureau office for consideration of approval. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. (Fencing in Design Plan) Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC  Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.							
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□Yes	□No					
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	□Yes	□No					
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No					
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	□NA						
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No					
(Applied to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	∐NA						
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	□No					
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.							
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended							
<ul> <li>Written confirmation or verification from the municipality; Written approval obtained from the municipality</li> <li>Within 500 feet of a wetland.</li> <li>US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site</li> </ul>	□Yes	□No					
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division							
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological							
Society; Topographic map  Within a 100-year floodplain  - FEMA map							
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC							
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the de	ocuments ar	e attached.					
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Operating and Maintence Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC							
Previously Approved Design (attach copy of API Number: or Permit							
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.							
Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9  Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC							
X Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC  Previously Approved Design (attach copy of API Number:							
Trivinoer,							

Hydrogeslogic Report - based upon the requirements of Pangasph (1) of Subsection B of 19.15.17.9 NMAC		Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC						
Sting Criteria Compliance Demonstratures - based upon the appropriate requirements of 19.15.17.11 NMAC	Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.							
Cintratological Factors Assessment   Cintratol								
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC								
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC   Liner Specifications and Compatibility Assurance Posture - based upon the appropriate requirements of 19.15.17.11 NMAC   Quality ControlQuality Assurance Construction and Installation Plan   Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Quality ControlQuality Assurance Construction and Installation Plan   Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Nuissence or Hazardous Odors, including H2S, Prevention Plan   Emergency Response Plan   Emergency Response Plan   Emergency Response Plan   Erosion Control Plan   Course Plan - hased upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC   Proposed Closure   Newtower   mergency   Covation   Permanent Fit   Below-goad: Task   Closed-loop System   Alternative Proposed Closure   Mechanic Individual Proposed Closure   Mechanic Individual Proposed Closure   Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for   String Criteria (regarding on-site Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for   String Criteria (regarding on-site Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for   String Criteria (regarding on-site Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for   String Criteria (regarding on-site Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for   String Criteria (regarding on-site Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for   String Criteria (regarding on-site Closure Method on-site February Plan Method (Exceptions must for the Santa Fe Environmental Environmental Plan Method (Excep	L Climatological Factors Assessment							
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC   Lear Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC   Quality Control Plan   Benziero Control Plan   Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC   Proposed Closure   Quality Control Plan   Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC   Proposed Closure   Quality Control Plan   Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC   Proposed Closure   Quality Control Plan   Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC   Proposed Closure   Quality Control Plan   Quality Cont	Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC							
Closure Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Quality Control/Quality Assurance Construction and Installation Plan   Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC   Prechand and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Nutrance or Hazardous Odolon, including 12S, Prevention Plan   General Plan	Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC							
Quality Control/Quality Assurance Construction and Installation Plan   Quality Control Quality Assurance of National Control Plan   Section 19.15.17.12 NMAC   Quality Control Plan	Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC							
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC							
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC   Nuisance or Hzaradous Odors, including H2S, Prevention Plan   Emergency Reponse Plan   Emergency Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	Quality Control/Quality Assurance Construction and Installation Plan							
Nussance or Hazardous Odors, including H2S, Prevention Plan	Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC							
Nussance or Hazardous Odors, including H2S, Prevention Plan	Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC							
Emergency Response Plan   Oil Field Waste Stream Characterization   Monitoring and Inspection Plan   Erosion Control Plan   Closure Plan - based upon the appropriate requirements of Subsection C of 19:15.17.9 NMAC and 19:15.17.13 NMAC								
Golden   Field Waste Stream Characterization   Golden								
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC								
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	Monitoring and Inspection Plan							
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC   Proposed Closure:   19.15.17.13 NMAC   Premanent Pit   Delow-grade Tank   Closed-loop System   Alternative   Proposed Closure:   19.15.17.13 NMAC   Proposed Closure   Mark   Closed-loop System   Alternative   Proposed Closure   Mark   Closed-loop   Consideration   Premanent Pit   Delow-grade Tank   Closed-loop   Alternative   Proposed Closure   Mark   Closed-loop   Consideration   Considerati								
Proposed Closure: 19.15.17.13 NMAC Type:   Ontling   Workow   Emergency   Cavitation   Permanent Pit   Below-grade Tank   X Closed-loop System   Alternative   Proposed Closure   Waste Excavation and Removal   On-site Closure Method (only for temporary pits and closed-loop   Imperior	Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC							
Type:   Dnfling   Workover   Energency   Cavitation   Permanent Pit   Below-grade Tank   X Closed-loop System   Alternative Proposed Closure   Cavitation   On-site Closure Method (only for temporary pits and closed-loop     In-place   On-site Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for   Sliting Criteria (regarding on-site closure methods only):   9.15.17.10 NMAC   Instructions: Each stitus criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requires tegrading, changes to certain sting criteria may require administrative approval from the appropriate district affece or may be considered on acceptain which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.  Ground water is less than 50 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells   NA   Yes   No   NA   No   No   No   No   No   No								
Proposed Closure    Name   Closure Method (only for temporary pits and closed-loop	Proposed Closure: 19.15.17.13 NMAC							
Proposed Closure   Maste Excavation and Removal	Type: Drilling Workover Emergency Cavitation Permanent Pit Below-grade Tank X Closed-loop System Alternation	native						
On-site Closure Method (only for temporary pits and closed-loop								
Siting Criteria (regarding on-site closure methods only):  Siting Criteria (regarding on-site closure methods only):  Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommentations of acceptable source material are provided below. Request regarding changes to certain stiling criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.  Ground water is less than 50 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 500 horizontal feet of a private, domestic fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within 100 feet of a wetland.  Pres No  Within 100 feet of a wetland.  Pres No  Pres No  Pres No  Engineering measures incorporated into the								
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC  Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommentations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which musts be submitted to the Smala of E- Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.  Ground water is less than 50 feet below the bottom of the burned waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 300 feet for a private, domestic fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978,								
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC  Instructions: Each sting criteria requires a demonstration of compliance in the closure plan. Recommentations of acceptable source material are provided below. Requests regarding changes to certain stiling criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.  Ground water is less than 50 feet below the bottom of the burned waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the burned waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, smkhole, or playa lal (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well or spring, in existence at the time of initial application.  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 100 feet of a wetland.  Pyes No  Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  Engineering measu								
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommentations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.  Ground water is less than 50 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site Within 300 foet for a permanent residence, school, hospital, institution, or church in existence at the time of initial Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizontal feet of a private, domestic fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  Within 500 feet of a wetland.  Within 500 feet of a wetland.  Within 500 feet of a metland.  Engineering measures incorporated into the design; NM Bureau of Geology & Muneral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain	Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau r	or						
material are provided below. Requests regarding changes to certain sting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submited to the Stanta Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.  Ground water is less than 50 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  Within 100 feet of a wetland.  Pes No  Pes	Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC							
material are provided below. Requests regarding changes to certain sting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submited to the Stanta Fe Environmental Bureau office for consideration of approval. Justification and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.  Ground water is less than 50 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  Within 100 feet of a wetland.  Pes No  Pes								
Ground water is less than 50 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  Pyes No  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM  Geological Society; Topographic map	material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate							
Ground water is less than 50 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM  Geological Society; Topographic map  Within a 100-year floodp								
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site, Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain	approvat. Justification unator demonstrations of equivalency are required. I teuse refer to 17.13.17.10 (VMAC for guidance.							
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is between 50 and 100 feet below the bottom of the buried waste  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site, Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain	Ground water is less than 50 feet below the bottom of the buried waste	□Ves□No						
Ground water is between 50 and 100 feet below the bottom of the buried waste  NM Office of the State Engineer - iWATERS database serach; USGS; Data obtained from nearby wells  Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  Within 500 feet of a wetland, proposed site  Within the area overlying a subsurface mine.  Within the area overlying a subsurface mine.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain								
Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  Within 500 feet of a wetland.  Within 500 feet of a wetland.  Pyes No  Yes No  Yes No  Yes No  Yes No  Topographic map  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain	Ground water is between 50 and 100 feet below the bottom of the buried waste							
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal  (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain								
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  Visual inspection (certification) of the proposed site  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  Within 500 feet of a wetland.  Within 500 feet of a wetland.  Within the area overlying a subsurface mine.  Within the area overlying a subsurface mine.  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain	1111 Office of the otate Engineer 11111 ERO database screen, OBOD, Data obtained from ficarby wells							
(measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  Within 500 feet of a wetland.  Proposed site  Within the area overlying a subsurface mine.  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain  Within a 100-year floodplain		□NA □						
- Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain	Ground water is more than 100 feet below the bottom of the buried waste.	□NA □Yes □No						
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  Within 500 feet of a wetland.  Within 500 feet of a wetland.  Pyes No  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain  Within a 100-year floodplain	Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□NA □Yes□No □NA						
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM  Geological Society; Topographic map  Within a 100-year floodplain    Yes   No	Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal	□NA □Yes□No □NA						
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM  Geological Society; Topographic map  Within a 100-year floodplain    Yes   No	Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).	□NA □Yes□No □NA						
or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  Within 500 feet of a wetland.  Proposed site  Within the area overlying a subsurface mine.  Within the area overlying a subsurface mine.  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM  Geological Society; Topographic map  Within a 100-year floodplain	Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal  (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial	NA  Yes No  NA  Yes No						
of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  Within 500 feet of a wetland.  Proposed site  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain	Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal  (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	NA  Yes No  NA  Yes No						
- NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM  Geological Society; Topographic map  Within a 100-year floodplain	Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal  (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic	NA  Yes No  NA  Yes No						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM  Geological Society; Topographic map  Within a 100-year floodplain    Yes   No	Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal  (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time	NA  Yes No  NA  Yes No						
ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM  Geological Society; Topographic map  Within a 100-year floodplain	Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	NA  Yes No  NA  Yes No						
- Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland. proposed site  Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM  Geological Society; Topographic map  Within a 100-year floodplain    Yes   No	Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	NA Yes No NA Yes No Yes No						
proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM  Geological Society; Topographic map  Within a 100-year floodplain	Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal	NA Yes No NA Yes No Yes No						
proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM  Geological Society; Topographic map  Within a 100-year floodplain	Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	NA Yes No NA Yes No Yes No						
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain	Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	NA  Yes No  NA  Yes No  Yes No  Yes No						
- Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map  Within a 100-year floodplain	Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.	NA  Yes No  NA  Yes No  Yes No  Yes No						
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM  Geological Society; Topographic map  Within a 100-year floodplain	Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site	NA Yes No NA Yes No Yes No Yes No Yes No						
- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map Within a 100-year floodplain	Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.	NA Yes No NA Yes No Yes No Yes No Yes No						
Geological Society; Topographic map Within a 100-year floodplain	Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	NA  Yes No  NA  Yes No  Yes No  Yes No  Yes No  Yes No  Yes No						
Within a 100-year floodplain	Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  proposed site  Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.	NA  Yes No  NA  Yes No  Yes No  Yes No  Yes No  Yes No  Yes No						
	Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes,or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  Proposed site  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM	NA  Yes No  NA  Yes No  Yes No  Yes No  Yes No  Yes No  Yes No						
- FEMA map	Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lal (measured from the ordinary high-water mark).  Topographic map; Visual inspection (certification) of the proposed site  Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial  Visual inspection (certification) of the proposed site; Aerial photo; Satellite image  Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended  Witten confirmation or verification from the municipality; Written approval obtained from the municipality  Within 500 feet of a wetland.  Proposed site  Within the area overlying a subsurface mine.  Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division  Within an unstable area.  Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	NA Yes No NA Yes No						

Waste Excavation and Removal Closure Plan Checklist: (19 15 17.13 NMAC) Instructions: Each of the following items must be attached									
to the closure plan. Please indicfate, by a check mark in the box, that the documents are attached.  [V] Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC									
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC   Confiramtion Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC									
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)									
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19 15.17.13 NMAC									
X Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC									
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC									
Waste Removal Closure for Closed-loop Systems That Utilize Haul-off Bins Only: (19 15 17 13 D NMAC) Instructions: Please identify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings.									
Disposal Facility Name. Envirotech, Basin Disposal Disposal Facility Permit Number: NM-01-0011 & NM-01-005									
On-Site Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a									
check mark in the box, that the documents are attached.									
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC									
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC									
Construction and Design of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17 11 NMAC									
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC									
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15.17.13 NMAC									
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC									
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be									
Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC									
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC									
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15 17.13 NMAC									
Operator Application Certification:									
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.									
Name (Print). Crystal Tafoya Title. Regulatory Technician									
Signature Crystal Tologo Date 7/15/2008									
e-mail address: crystal.tafoya@conoccamillips.com Telephone: 505-326-9837									
OCD Assessment A Description (varieties (var									
OCD Approval: Permit Application (including closure plan) Closure Plan (only)									
OCD Proprogramative Signatures 7 1/ OC									
OCD Representative Signature: Search 6-M Approval Date: 7-16-08									
OCD Representative Signature: Stand 6M Approval Date: 7-16-08  Title: ENDO/Spec OCD Permit Number.									
Tide: Enviro/gec OCD Permit Number.									
Title: Enviro / spec OCD Permit Number.  Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Completion Date:									
Title: Enviro/spec OCD Permit Number.  Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Completion Date:  Closure Method:									
Title: Enviro/spec OCD Permit Number.  Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Completion Date:  Closure Method:									
Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain									
Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Completion Date:  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure									
Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice									
Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)									
Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)  Plot Plan									
Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice  Proof of Deed Notice (if applicable)									
Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results									
Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Soil Backfilling and Cover Installation									
Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique									
Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation)									
Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique									
Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation)									
Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude: Longitude: NAD 1927 1983									
Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the bost, that the documents are attached.  Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Waste Material Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude: Longitude: NAD 1927 1983  Operator Closure Certification:  I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief Lalso certify that the									
Closure Report (required within 60 days of closure completion): Subsection K of 19.15 17.13 NMAC  Closure Method:  Waste Excavation and Removal On-Site Closure Alternative Closure  If different from approved plan, please explain  Closure Report Attactment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.  Proof of Closure Notice Proof of Closure Notice Proof of Deed Notice (if applicable) Plot Plan Confirmation Sampling Analytical Results Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Latitude: Longitude: NAD 1927 1983  Operator Closure Certification:  I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan									

Form C-144 Oil Conservation Division Page 4 of 4

Submit to Appropriate District Office State Lease - 4 copies Fee Lease - 3 copies

# State of New Mexico Energy, Minerals and Natural Resources Department

Form C-102 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240 OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD, Ariesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aziec, NM 87410

WELL LOCATION AND ACREAGE DEDICATION PLAT

All Distances must be from the outer boundaries of the section									
Operator		Lease	· · · · · · · · · · · · · · · · · · ·		Well No.				
PHILLIPS F	PETROLEUM	SAN	JUAN 31-	·6	223				
Unit Letter Section	T.31 N.	Range		County					
L 32	T.31 N.	R.6	W. NMP	₄ RIO AF	RRIBA COUNTY				
Actual Footage Location of Well: 1956 feet from the	SOUTH line and	1162		n the WEST	line				
Ground level Elev. Prod	tucing Formation	Pool		11 42	Dedicated Acreage:				
6312 Fru	itland	Basin Fruit	land Coal Ga	s	320 Acres				
<ol> <li>Outline the acreage dedi</li> </ol>	cated to the subject well by colored p	ocil or hachure marks on	the pist below.						
2. If more than one lease is	dedicated to the well, outline each ar	d identify the ownership t	nereof (both as to work	ting interest and s	royaity).				
3. If more than one lease of	f different ownership is dedicated to the	ne well, have the interest o	f all owners been cons	olidated by comn	nunitization,				
unitization, force-pooling	<u>द्र बद</u> ्	,		•	·				
	No If answer is "yes" to where and tract descriptions which have		Unitization						
this form if necessary.									
No allowable will be assign or until a non-standard unit	ned to the well until all interests have eliminating such interest, has been a	per consolidated (by comproved by the Division.	munitization, unitizatio	on, forced-pooling	g, or otherwise)				
	<del>/-/-/-/</del>		<del></del>	OPERAT	OR CERTIFICATION				
	1	ļ	11		certify that the information				
7	act 11	!	11		in true and complete to the				
•	289~3	1	1 1	best of my browl	edge and belief.				
1 160	Acres (	Brab.							
j {		DECEN		Signature	$\mathcal{O}$ $\mathcal{O}$				
<i>y</i> 1	<i>X</i> 1		3132 1 1	19:71/~	SanGers				
11	4 L	<i>uu</i> ,,,,,		Printed Name					
トナーーーーー	+	MAR 97 109	0	L. M. Sai	nders				
1 ' i				Position					
	1 .	OIL CON. I	DIV   [	Supv. Reg	gulatory Affairs				
X	L,	DI\$T. 3		Company					
	X		`   [	Phillips	Petroleum Co.				
<i>}</i>		ļ		Date					
1	<b>,</b>		1 1	March 6	1990				
<u> </u>	1	ļ	1.	SURVEY	OR CERTIFICATION				
T	12.				that the well location shown				
	ct 12a	ĺ			us plotted from field notes of				
1102	46-25	1			made by me or under my I that the same is true and				
	Acres	Ì	3 1	•	best of my knowledge and				
5280	<i>V</i>	i	1 1	belief.	out of my name of the				
i i	1	i							
1 · 1;	1	;	11	Date Surveyed					
	ーーセーーオーーー			FEBRUA	ALCHO VAC				
60		1		Signature & Sta Professions So	AND CO.				
956'	1	l l	1 1		A ME Y/C				
<del> </del>	l,	ļ	11	R. HOWA	DATUE 10				
1	1	ļ	11	D NI	Loop Dollar				
. , ,	ì	1	1 1	71. 704					
z	V	Ĭ	·	[2]					
WEST	5280' 1	i		Certificate No. o	SET BOOMAL				
330 660 990 1320 165	0 1980 2310 2640 200	00 1500 1000	500 0	Regi	etered Professional				
	<del></del>				-Lend Surveyor				

## ConocoPhillips Company Closed-loop Plans

#### Closed-loop Design Plan

COPC's closed loop system will not entail a drying pad, temporary pit, below grade tank or sump. It will include an above ground tank suitable for holding the cuttings and fluids for rig operations. The tank will be sufficient volume to maintain a safe free board between disposal of the liquids and solids from rig operations.

- 1. Fencing is not required for an above ground closed-loop system
- 2. It will be signed in compliance with 19.15.3.103 NMAC
- 3. A frac tank will be on location to store fresh water

#### **Closed-loop Operating and Maintenance Plan**

COPC's closed-loop tank will be operated and maintained to contain liquids and solids in order to prevent contamination of fresh water sources, in order to protect public health and the environment. To ensure the operation is maintained the following steps will be followed:

- 1. The liquids will be vacuumed out and disposed of at the Basin Disposal facility (Permit # NM-01-005). Solids in the closed-loop tank will be vacuumed out and disposed of at Envirotech (Permit # NM-01-0011) on a periodic basis to prevent over topping.
- 2. No hazardous waste, miscellaneous solid waste or debris will be discharged into or stored in the tank. Only fluids or cutting used or generated by rig operations will be placed or stored in the tank.
- 3. The division district office will be notified within 48 hours of the discovery of compromised integrity of the closed-loop tank. Upon the discovery of the compromised tank, repairs will be enacted immediately
- 4. All of the above operations will be inspected and a log will be signed and dated. During rig operations the inspection will be daily.

#### **Closed-loop Closure Plan**

The closed-loop tank will be closed in accordance with 19.15.17.13. This will be done by transporting cuttings and all remaining sludges to Envirotech (Permit # NM-01-0011) immediately following rig operations. All remaining liquids will be transported and disposed of in the Basin Disposal facility (Permit # NM-01-005). The tanks will be removed from the location as part of the rig move. At time of well abandonment, the site will be reclaimed and re-vegetated to pre-existing conditions when possible.