This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator ConocoPhillips					Lease Name SAN JUAN 28				28-7 UNIT			Well No74A
Location of Well: U		_etter _	<u> </u>	ec	11	Twp _	028N	Rg	je	007W	API	# 30-039-22237
	Name of Reservoir or Pool			Î	Type of Prod				Method of Prod			Prod Medium
Upper Completion	PC				Gas			Flow				Tubing
Lower Completion	MV				Gas			Artificial Lift				Tubing
				Pre	-Flow S	Shut-In	Pressu	re Data				
Upper Completion	Hour, Date, Shut-In				Length of Time Shut-In			SI Press. PSIG				Stabilized?(Yes or No)
	8/8/2008				128 hours				211			Yes
Lower Completion	Hour, Date, Shut-In				Length of Time Shut-In				SI Press. PSIG			Stabilized?(Yes or No)
	8/8/2008				105 hours				145			Yes
Commenced a	at: 8/12		00:00 AM ed Time			w Test Z SSURE		oducing		or Lowe	er): Lov	wer
(date/time)		Since*		Uppe	per zone Lower zone		Temperature			Remarks		
8/13/2008 8:57:33 AM 23		2	213 128		10	100		R	RCVD AUG 20 '08			
Production rate	e during t	est									C	DIL CONS. DIV. DIST. 3
Oil:BPOD Based on:		Bbls	Bbls. In H			Grav.			GOR			
			PD; Test th	,								·
				Mic	l-Test S	Shut-In	Pressu	re Data				
Upper Completion	Hour, Date, Shut-In				Length of Time Shut-In			SI Press. PSIG			Stabilized?(Yes or No)	
Lower Completion	Hour, Date, Shut-In				Length of Time Shut-In			SI Press. PSIG			Stabilized?(Yes or No)	

(Continue on reverse side)

Flow Test No. 2

Commenced at:				Zone Producing (Upper or Lower)								
Time Lapsed Time			PRES	SURE	Prod Zone							
(date/tim	e)	Since*	Upper zone	Lower zone	Temperature		Remarks					
			·									
Production rat	e during test											
Oil:	BPOD Based on:		Bbls. In	Hrs.		Grav.	GOR					
Gas		_MCFPD; Test th	nru (Orifice or M	leter)								
Remarks:												
,	sing on uppe	r zone increased	from 211 to 21	3, pressure on	lower zone w	ent from 145 to 1	28.					
		• •										
	1											
I hereby certify	y that the info	ormation herein c	ontained is true	and complete	to the best of	f my knowledge.						
A	AH	3 2 5 2008	20	0-0-0	taw. Canasa	Dhilling						
Approved:			20	<u> </u>	tor: Conoco							
New Mexic	co Oil Conser U G. 😓	vation Division		By:	David Boun	ds						
By:	•			Title:	Multi-Skilled	Operator						
Title:	Deputy Oil & Gas Inspector, District #3					e: Tuesday, August 19, 2008						

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note, if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows. 3 hours tests, immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desued, or may be requested on wells which have previously shown questionable test data

24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone

The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)

Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3