In Lie	u of
Form	3160
(June	1990

UNITED STATES

Ri	,	-	<i>_</i>	
R.7!		1	•	

RITO	,	-	~
1/7!		1	•

FÓRM APPROVED
Budget Bureau No. 1004-013
Expires March 31 1993

Form 31 (June 19	990) BUREAU OF LAND MANAGEMENT	SEP		2008	FÖRM APPROVED Budget Bureau No. 1004-0135 Expires March 31, 1993
Do not	SUNDRY NOTICE AND REPORTS ON WELLS use this form for proposals to drill or to deepen or reentry to a different reservoir. Us	Bureze o na Familingio se "APPLICAT	in Flo	5 C Winka	' 'Lease Designation and Serial No NMSF-078768
	TO DRILL" for permit for such proposals				If Indian, Allottee or Tribe Name
	SUBMIT IN TRIPLICATE			7.	If Unit or CA, Agreement Designation Rosa Unit
1	Type of Well Oil Well Gas Well X Other			8	Well Name and No. Rosa Unit #377A CONF
2	Name of Operator WILLIAMS PRODUCTION COMPANY		,	9.	API Well No. 30-039-29925
3.	Address and Telephone No PO Box 640 Aztec, NM 87410-0640			10	Field and Pool, or Exploratory Area Basin Fruitland Coal
4.	Location of Well (Footage, Sec., T, R, M, or Survey Description) 1895' FNL & 1915' FWL 1190' FNL & 1190' FWL SEC 26, 31N, 5W			11	County or Parish, State Rio Arriba, New Mexico
	CHECK APPROPRIATE BOX(s) TO INDICATE NATUR	RE OF NOTICE	E, REPO	ORT, OR O	THER DATA

TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction X Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Altering Casing Conversion to Injection X SURFACE CASING Dispose Water (Note Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13 Describe Proposed or Completed Operations (Clearly state all pertunent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD- 12 1/4" SURF HOLE @ 347', 2100 HRS

RCVD SEP 9 '08 OIL CONS. DIV.

DIST. 3

RAN 7 JTS, 9 5/8', 36#, K-55, 8rD - ST&C, CSG SET @ 337', FC @ 288'

CEMENT 9-5/8" CASING @ 337' - SHOE DEPTH / SINGLE SLURRY CEMENT JOB / 20 BBLS. FRESH WATER SPACER / 150 SXS TYPE 3 CEMENT + 2% CaCl-2 + .25#/SX CELLO FLAKE + 24.42 BBL, WATER = 80.22 BBL, (212 CuFt) SLURRY @ 14.5 PPG (YIELD = 1.41 / WGPS = 6.84) / DISPLACE WITH 22 BBL. WATER / 800 PSI,PLUG DOWN ON 8/30/08,@ 0600 AM 200 PSI SHUT IN,10 BBL .OF CEMENT RETURNS TO SURFACE .

INSTALL TEST PLUG & TEST BOP PIPE & BLIND RAMS, CHOKE MANIFOLD VALVES, MUD CROSS VALVES, FLOOR VALVE

KELLY @ 250# 5-MIN EACH & 1500# 10-MIN EACH. TEST 9 5/8" CSG @ 1500# 30-MIN. TEST PUMP & TEST CHARTS-USEDRRECORD ON ALL TEST. ALL TESTED GOOD. J

FARMINGTON FIELD OFFICE

			BY TL Salvers
14.	I hereby certify that the foregoing is true and correct Signed Larry Higgins	Title <u>Drilling C.O.M.</u>	Date September 2, 2008
	(This space for Federal or State office use)		
	Approved by	Title	Date
	Conditions of approval, if any:		

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

