District I 1625 N French Dr., Hobbs, NM 88240 District II
1301 W. Grand Avenue, Artesia, NM 88210 District III
1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and

provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System, Below-Grade Tank, or	
Proposed Alternative Method Permit or Closure Plan Applica	tion

lype of action: Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method Modification to an existing permit Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.
ı. Operator:McElvain Oil & Gas Properties, Inc OGRID #:22044
Address:1050 17 th Street , Suite 1800, Denver, CO_80265
Facility or well name: _CASSIDY IR
API Number:30-045-34273 OCD Permit Number:
U/L or Qtr/Qtr _H_ Section19 Township29N Range11W County:San Juan
Center of Proposed Design: Latitude 36 42.773N Longitude 108 01.564W
Surface Owner: Federal State Private Tribal Trust or Indian Allotment
and compression of co
Center of Proposed Design: Latitude36 42.773N Longitude108 01.564W 1927 1983 Surface Owner: Federal State Private Tribal Trust or Indian Allotment 2.
Temporary: Drilling Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other
☐ String-Reinforced
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D
3.
Closed-loop System: Subsection H of 19.15.17.11 NMAC
Type of Operation: P&A Drilling a new well Workover or Drilling (Applies to activities which require prior approval of a permit or notice of
intent) Drying Pad Above Ground Steel Tanks Haul-off Bins Other
Lined Lined Lines type: Thickness mil LIDDE BYC Other
Liner Seams: Welded Factory Other Other
Below-grade tank: Subsection I of 19.15.17.11 NMAC
Volume: 95 bbl Type of fluid: Water Volume: 95 bbl Type of fluid: Water
☑ Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: _95
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
Volume:95bbl Type of fluid:Water
Liner type: Thicknessmil
5.
Alternative Method:
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
☐ Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
7.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other_Expanded Metal	
Monthly inspections (If netting or screening is not physically feasible)	
8. Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
☑ Signed in compliance with 19.15.3.103 NMAC	
9.	
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau of the Santa Fe En	office for
consideration of approval.	office for
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the approoffice or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of a Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drylabove-grade tanks associated with a closed-loop system.	priate district pproval.
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.	☐ Yes ⊠ No
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☒ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No ☑ NA
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No
(Applies to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	⊠ NA
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock	☐ Yes ☑ No
watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☑ No
Within 500 feet of a wetland.	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☒ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☑ No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes 🛛 No
Within a 100-year floodplain.	☐ Yes ☑ No

Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: (Applies only to closed-loop system that use
above ground steel tanks or haul-off bins and propose to implement waste removal for closure)
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan Gil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
14. Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Instructions: Please indentify the facility or facilities for the disposal of liquids,					
facilities are required.	urining fluius and arm cultings. Ose allachment if h	nore inan iwo			
Disposal Facility Name:	Disposal Facility Permit Number:				
Disposal Facility Name:	Disposal Facility Permit Number:				
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will not be used for future service and operations. Yes (If yes, please provide the information below) No					
Required for impacted areas which will not be used for future service and operatio Soil Backfill and Cover Design Specifications based upon the appropriate Re-vegetation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection	requirements of Subsection H of 19.15.17.13 NMAC I of 19.15.17.13 NMAC	C			
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the provided below. Requests regarding changes to certain siting criteria may require considered an exception which must be submitted to the Santa Fe Environmental demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC j	e administrative approval from the appropriate disti Bureau office for consideration of approval. Justi	rict office or may be			
Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Database search;	a obtained from nearby wells	☐ Yes ☐ No ☐ NA			
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data	a obtained from nearby wells	☐ Yes ☐ No ☐ NA			
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Database search;	a obtained from nearby wells	☐ Yes ☐ No ☐ NA			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other sig lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	nificant watercourse or lakebed, sinkhole, or playa	☐ Yes ☐ No			
Within 300 feet from a permanent residence, school, hospital, institution, or church - Visual inspection (certification) of the proposed site; Aerial photo; Satellite		☐ Yes ☐ No			
Within 500 horizontal feet of a private, domestic fresh water well or spring that les watering purposes, or within 1000 horizontal feet of any other fresh water well or s - NM Office of the State Engineer - iWATERS database; Visual inspection (pring, in existence at the time of initial application.	☐ Yes ☐ No			
Within incorporated municipal boundaries or within a defined municipal fresh water adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approve	•	☐ Yes ☐ No			
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visua	al inspection (certification) of the proposed site	☐ Yes ☐ No			
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining	and Mineral Division	☐ Yes ☐ No			
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geolog Society; Topographic map 	y & Mineral Resources; USGS; NM Geological	☐ Yes ☐ No			
Within a 100-year floodplain FEMA map		☐ Yes ☐ No			
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Construction/Design Plan of Temporary Pit (for in-place burial of a drying protocols and Procedures - based upon the appropriate requirements of 19.13 Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Disposal Facility Name and Permit Number (for liquids, drilling fluids and Confirmation Plan - based upon the appropriate requirements of Subsection Re-vegetation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection	uirements of 19.15.17.10 NMAC Subsection F of 19.15.17.13 NMAC oppropriate requirements of 19.15.17.11 NMAC ad) - based upon the appropriate requirements of 19. 5.17.13 NMAC uirements of Subsection F of 19.15.17.13 NMAC Subsection F of 19.15.17.13 NMAC lrill cuttings or in case on-site closure standards cann H of 19.15.17.13 NMAC I of 19.15.17.13 NMAC	15.17.11 NMAC			

19.		
Operator Application Certification: I hereby certify that the information submitted with this application	n is true, accurate and complete to	the best of my knowledge and belief.
Name (Print): Deborah K Powell	Title: _Engineerin	g Tech Supervisor
Signature: Dell K Poull	Date:	9-4-08
e-mail address:DebbyP@McElvain.com	Telephone	e:303-893-0933
20. OCD Approval: Permit Application (including closure plan)	Closure Plan (only) OC	D Conditions (see attachment)
OCD Representative Signature: DENIED		Approval Date:
Title:	OCD Permit Nu	mber:
21. Closure Report (required within 60 days of closure completion) Instructions: Operators are required to obtain an approved closu The closure report is required to be submitted to the division with section of the form until an approved closure plan has been obtain	re plan prior to implementing an in 60 days of the completion of th	y closure activities and submitting the closure report. ne closure activities. Please do not complete this
	☐ Closure Con	mpletion Date:
22. Closure Method: Waste Excavation and Removal On-Site Closure Method If different from approved plan, please explain.	☐ Alternative Closure Metho	od Waste Removal (Closed-loop systems only)
23. Closure Report Regarding Waste Removal Closure For Closed-Instructions: Please indentify the facility or facilities for where the two facilities were utilized.	-loop Systems That Utilize Abov he liquids, drilling fluids and drill	e Ground Steel Tanks or Haul-off Bins Only: I cuttings were disposed. Use attachment if more than
Disposal Facility Name:	Disposal Facility	Permit Number:
Disposal Facility Name:	Disposal Facility	Permit Number:
Were the closed-loop system operations and associated activities per Yes (If yes, please demonstrate compliance to the items belo		ot be used for future service and operations?
Required for impacted areas which will not be used for future servi Site Reclamation (Photo Documentation) Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique	ce and operations:	
24. Closure Report Attachment Checklist: Instructions: Each of the mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique		ed to the closure report. Please indicate, by a check
Site Reclamation (Photo Documentation) On-site Closure Location: Latitude	Longitude	NAD: □1927 □ 1983
25.		
Operator Closure Certification: I hereby certify that the information and attachments submitted with belief. I also certify that the closure complies with all applicable closure.	1 this closure report is true, accura osure requirements and conditions	te and complete to the best of my knowledge and specified in the approved closure plan.
Name (Print):	Title:	
Signature:	Date:	,
e-mail address:	Telephone: _	

DIL CONS. DIV.

DISTRICT | 1625 N. French Dr., Hobbs, N.M. 68240

State of New Mexico
Energy, Minerals & Natural Resources Department

DIST. 3 Form C-102 Revised October 12, 2005

DISTRICT II 1301 W. Grand Avenue, Artesia, N.M. 88210

DISTRICT III 1000 Rio Brazos Rd., Aztec, N.M. 87410

OIL CONSERVATION DIVISION 1220 South St. Francis Dr.

Submit to Appropriate District Office State Lease - 4 Copies Fee Lease - 3 Copies

Santa Fe, NM 87505


☐ AMENDED REPORT

DISTRICT_IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 WELL LOCATION AND ACREAGE DEDICATION PLAT

	HOLE DOCATION AND ACIO	DROD DUDIORITOR I LAL	
API Number	* Pool Code	³ Pool Name	
30-045-34273	77200	FULCHER KUTZ/PICTURED CL	IIFS
⁴ Property Code	Property Na	me .	* Weil Number
36455	CASSIDY	1R	
OGRID No.	*Operator Na	me	⁸ Elevation
22044	MCELVAIN OIL AND GAS	PROPERTIES, INC.	5488'

10 Surface Location UL or lot no. Section North/South line East/West line Lot Idn Feet from the Feet from the Township Range County 2080' NORTH 660' EAST SAN JUAN Н 19 29N 11W 11 Bottom Hole Location If Different From Surface Township UL or lot no. Section Lot Idn Feet from the North/South line | Feet from the East/West line Range County ¹² Dedicated Acres "Consolidation Code 15 Order No. is Joint or Infill SE/NE, NE/SE & S/SE NWU -39 159.07 ACRES

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



New Mexico Office of the State Engineer POD Reports and Downloads

Township: 29N Range: 11W Sections: 17,18,19,20,29,30 NAD27 X: Y: Zone: Search Radius: Basin: SJ(San Juan) County: . 1 Number: Suffix: O Non-Domestic O Domestic O All Owner Name: (First) (Last) POD / Surface Data Report Avg Depthsto Wäter Report Water Column Report Clear Form iWATERS Menu Help

WATER COLUMN REPORT 08/25/2008

(quarters are 1=NW 2=NE 3=SW 4=SE) Depth Depth Water (in (quarters are biggest to smallest) POD Number Rng Sec q q q Zone X Y Well Water Column Tws 80 295 SJ 02926 29N 11W 17 2 4 3 375 100 SJ 03399 29N 11W 17 4 2 60 54 SJ 00487 29N 11W 17 4 4 6 29N 50 SJ 02868 11W 17 4 4 4 120 55 65 29N 11W 19 2 2 3 SJ 01641 29N 440000 2077700 27 6 21 SJ 02026 11W 19 3 1 29N 100 18 82 19 3 2 SJ 02970 11W 4 60 20 40 29N SJ 01250 11W 19 4 4 50 SJ 02869 29N 11W 20 2 2 120 SJ 00583 29N 20 3 3 150 30 11W SJ 01355 36 3 33 29N 11W 20 4 4 SJ 03475 29N 11W 29 1 1 3 40 20 20 SJ 00292 29N 11W 29 2 1 4 24 9 15 35 18 17 SJ 01554 29N 11W 29 2 2 14 4 10 29N 11W 29 SJ 02038 4 1 70 6 64 29N 11W 29 SJ 03298 4 1 1 24 7 17 4 2 SJ 02023 29N 11W 29 27 11 16 SJ 02182 29N 11W 29 4 2 15 19 29N 11W 29 4 3 34 SJ 00822 50 28 22 SJ 03421 29N 11W 29 4 4 3 25 15 40 SJ 01391 29N 11W 30 60 SJ 03348 29N 11W 30 2 1 3 15 13 SJ 01328 29N 11W 30 2 2 28 29N 11W 30 2 2 42 16 26 SJ 01260 27 12 15 29N 11W 30 2 2 SJ 01264 29N 11W 30 70 6 64 2 4 SJ 01821 11W 30 37 20 17 29N 4 1 SJ 00875

Record Count: 27

New Mexico Office of the State Engineer POD Reports and Downloads

Township: 29N Range: 12W Sections: 13,24,25 Search Radius: Y: Zone: NAD27 X: Basin: SJ(San Juan) County: Number: Suffix: Non-Domestic Domestic All Owner Name: (First) (Last) POD / Surface Data Report Avg Depth to Water Report Water Column Report Clear Form iWATERS Menu Help


WATER COLUMN REPORT 08/25/2008

• •							3=SW 4 small				Dep	t-h	Depth	Water	(in
POD Number	Tws		Sec				Zone	esc, X	ζ	3	_		Water	Column	\
SJ 01597	29N	12W	24	3	2	-					4	0	15	25	
SJ 02555	29N	12W	24	3	3						2	:1	6	15	
SJ 00400	29N	12W	24	3	4						8	3	35	48	
SJ 03735 POD1	29N	12W	24	3	4	1					10	0	15	85	
SJ 03507	29N	12W	24	3	4	1					6	0			
SJ 03786 POD1	29N	12W	24	3	4	1		265819	9	2077065	. 3	5	11	24	
SJ 02082	29N	12W	25	1	1						3	0	3	27	
SJ 00938	29N	12W	25	1	2						8	30	40	40	
SJ 00706	29N	12W	25	1	4						4	.9	20	29	
SJ 00652	29N	12W	25	1	4						4	2	20	22	
SJ 01322	29N	12W	25	1	4						4	12	20	22	
SJ 00617	29N	12W	25	1	4	3					4	<u>1</u> 7	20	27	
SJ 01466	29N	12W	25	2	4						2	27	14	13	
SJ 00570	29N	12W	25	3	1						3	86	18	18	
SJ 03340	29N	12W	25	3	3	3						15	12	33	
SJ 03173	29N	12W	25	3	4	2						50	10	50	
SJ 03580	29N	12W	25	3	4	4						20	4	16	
SJ 00763	29N	12W		4	3							50	20	40	
SJ 02132	29N	12W	25	4	3	1					4	10	12	28	

Record Count: 19


San Juan Mines, Mills And Quarries Web Map


Mines, Mil	ls & Quarries Commodity Groups
Δ	Aggregate & Stone Mines
•	Coal Mines
*	Industrial Minerals Mines
♥	Industrial Minerals Mills
Ø	Metal Mines and Mill Concentrate
	Potash Mines & Refineries
	Smelters & Refinery Ops.
*	Hranium Minas












1:24,000 950 1,900 3,800 5,700




Legend

McElvain Well & 200' Radius

McElvain Well & 300' Radius

McElvain Well & 500' Radius

Source: USGS 1:24,000 Scale Topographic Map Series San Juan Basin New Mexico Township 29N 11W Section 19



Legend

McElvain Well & 300' Radius

McElvain Well & 1000' Radius

Aerial Source: NM Resource Geographic Information System Program made available by the University of New Mexico and the State of New Mexico 2005-2006 vintage Digital Orthophoto Quarter-Quadrangles were derived from the New Mexico Statewide Orthophotography Project. Source imagery flown at 35,000' above average ground.

San Juan Basin New Mexico Township 29N 11W Section 19

Siting Criteria Compliance Demonstrations

Cassidy #1R well is not located in an unstable area. The location is not over a mine and is not on the side of a hill. The location of the excavated pit material is located within 300' of a continuously flowing watercourse and located within the proximity of a permanent residence.

McElvain Oil & Gas Properties, Inc. San Juan Basin Below Grade Tank Design and Construction

In accordance with Rule 19.15.17 NMAC the following describes the as-built construction of the Below Grade Tank on the McElvain Oil & Gas Properties, Inc (MOG) Cassidy #1R well located in the SENE of Sec 19, T29N, 11W.

As-built Installation:

- 1. The existing tank pit consists of an approximate 12 foot by 5 foot earth walled hole into which a 8 foot by 8 foot steel, single wall 45 bbl tank.
- 2. The tank walls are closed.
- 3. There is an expanded metal covering on the top of the below grade tank.
- 4. The tank pit is surrounded by a 30ft X 30ft X 2ft berm that is contained within a 50 ft X 140 ft berm that encloses the tank battery to prevent overflow or surface water run-on.
- 5. A general location sign is displayed on site.
- 6. The pit tank is fenced with 6 foot chain link fence.

McElvain Oil & Gas Properties, Inc. San Juan Basin Below Grade Tank Maintenance and Operating Plan

In accordance with Rule 19.15.17 NMAC the following describes the below grade tank operation and maintenance plan for the McElvain Oil & Gas Properties, Inc (MOG) on the Cassidy #1R well located in the SENE of Sec 19, T29N, 11W.

General Plan:

- 1. MOG shall operate and maintain the below grade tank to contain liquids and solids and prevent contamination of fresh water to protect the public health and environment.
- 2. MOG shall not allow a below grade tank to overflow or allow surface water run-on to enter the below grade tank.
- 3. MOG shall continuously remove any visible or measurable layer of oil from the fluid surface of a below grade tank in an effort to prevent significant accumulation of oil over time.
- 4. MOG shall inspect the below grade tank monthly and maintain a written record of each inspection for five years.
- 5. MOG shall maintain adequate freeboard to prevent overtopping of the below grade tank.

McElvain Oil & Gas Properties, Inc. San Juan Basin Closure Plan


In accordance with Rule 19.15.17.1 NMAC the following procedure describes the closure plan for the McElvain Oil & Gas Properties, Inc (MOG) below grade tank on the Cassidy #1R well located in the SENE of Sec 19, T29N, 11W.

Closure Requirements:

- 1. MOG shall close the below grade tank within the time periods provided in 19.15.17.13 NMAC or by an earlier date that the division requires because of imminent danger to fresh water, public health, or the environment.
- 2. MOG shall close an existing below grade tank that does not meet the requirements of Paragraph (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008 if not retrofitted to comply with Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC.
- 3. MOG shall close a permitted below grade tank within 60 days of cessation of the below ground tank's operation or as required by the transitional provisions of Subsection B of 19.15.17.17 NMAC in accordance with a closure plan that the appropriate division district office approves. The closure report will be filed on C-144.
- 4. All liquids will be removed from the temporary permit prior to closure and the liquids disposed of in a division approved facility.
- 5. MOG shall remove the below grade tank and dispose of it in a division approved facility or recycle, reuse, or reclaim it in a manner that the appropriate division district office approves.
- 6. MOG will remove any on-site equipment associated with the below grade tank unless the equipment is required for some other purpose.
- 7. MOG shall test the soils beneath the below grade tank to determine whether a release has occurred. MOG shall collect a five point composite sample and individual grab samples from any area that is wet, discolored, or showing other evidence of a release. The samples will be analyzed for BTEX, TPH, and chlorides to demonstrate that the benzene concentration as determined by EPA SW-846 methods 8021B or 8260B or other EPA method that the division approves, does not exceed 50 mg/kg; the TPH concentration as determined by EPA method 418.1 or other EPA method that the division approves does not exceed 100 mg/kg; and the chloride concentration as determined by EPA

- method 300.1 or other EPA method that the division approves does not exceed 250 mg/kg or the background concentration, whichever is greater. MOG shall notify the division of its results on form C-141.
- 8. If MOG or the division determines that a release has occurred, then MOG shall comply with 19.15.3.116 NMAC and 19.15.1.19 NMAC as appropriate.
- 9. If contamination is confirmed by field sampling. MOG will follow the Guidelines For Remediation Of Leaks, Spills, and Releases NMOCD August 1993 when remediating identified contaminants.
- 10. If the sampling program demonstrates that a release has not occurred or that any release does not exceed the concentrations specified in Paragraph (4) of Subsection E of 19.15.17.13 NMAC, then MOG shall backfill the excavation with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover; re-contour, and re-vegetate the site.
- 11. Notice of closure will be given to the Aztec Division office between 72 hours and one week of closure via email or verbally. The notification of closure will include the following:
 - · Operator's name
 - · Location by Unit Letter, Section Township, and Range.
 - · Well name and API number
- 12. All closure activities will include proper documentation and be available for review upon request and will be submitted to OCD within 60 days of closure of the blow grade tank. The closure report will be filed on C-144 and incorporate the following:
 - · Details on capping and covering where applicable
 - · Inspection reports
 - · Sampling results
- 13. The site will be re-contoured to match the surrounding area. Natural drainages will be unimpeded and erosion control will be utilized where necessary.
- 14. MOG shall seed the disturbed areas the first growing season with a division approved seed mixture after pit closure. Seeding will be accomplished by drilling on the contour whenever possible or by other division approved methods. Repeat seeding or planting will be continued until successful vegetative growth occurs.
- 15. A minimum of four feet of cover shall be achieved and the cover shall include one foot of suitable material to establish vegetation at the site, or the thickness of the topsoil native to the area, whichever is greater.

16. The surface owner shall be notified of MOG's closing of the below grade tank as per the approved closure plan using certified mail with return receipt requested.



Cassiny # IR

McElvain Oil & Gas Properties, Inc.