

Submit 3 Copies To Appropriate District Office
District I
1625 N French Dr, Hobbs, NM 88240
District II
1301 W Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd, Aztec, NM 87410
District IV
1220 S. St Francis Dr, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-039-30504
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-505-6
7. Lease Name or Unit Agreement Name Northeast Blanco Unit
8. Well Number 22M
9. OGRID Number 6137
10. Pool name or Wildcat Blanco Mesaverde/S Los Pinos F/S PC
11. Elevation (Show whether DR, RKB, RT, GR, etc.) GR 6,476'

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
Devon Energy Production Company, L.P.

3. Address of Operator
20 N. Broadway, Oklahoma City, OK 73102

4. Well Location
Unit Letter O : 660 feet from the South line and 1,805 feet from the East line
Section 36 Township 31N Range 7W NMPM Rio Arriba County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Spud Notice ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

The above referenced well was spud on 9/2/08 at 11:00.

Drilled 12 1/4" hole to 291' on 9/2/08, set 14 jts of 9 5/8", H-40, ST&C, 32.3# casing at 285'. Cemented w/165 sx (35 bbls) Type 5 cement w/2% CaCl and 1/4 ppsx Celloflake. Circulated 19 bbls of cement to surface. Tested casing to 750 psi, held ok.

RCVD SEP 8 '08

OIL CONS. DIV.

DIST. 3

Spud Date: 9/2/08

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Melisa Castro TITLE Senior Staff Operations Technician DATE 9-4-08

Type or print name Melisa Castro E-mail address: melisa.castro@dmn.com PHONE: 405-552-7917
For State Use Only Deputy Oil & Gas Inspector,
District #3

APPROVED BY: [Signature] TITLE DATE SEP 23 2008
Conditions of Approval (if any):