

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Sundry Notices and Reports on Wells

RECEIVED

SEP 24 2008

Bureau of Land Management
Farmington Field Office

1. **Type of Well**
Oil

2. **Name of Operator**
Arwood Stowe, c/o NMOCD

3. **Address & Phone No. of Operator**
1000 Rio Brazos Rd., Aztec, NM 87410

4. **Location of Well, Footage, Sec., T, R, M**
372' FSL and 1106' FEL, Section 28, T-18-N, R-3-W,

5. **Lease Number**
NM-0556820 A

6. **If Indian, All. or Tribe Name**

7. **Unit Agreement Name**

8. **Well Name & Number**
Timmy #3

9. **API Well No.**
30-043-60012

10. **Field and Pool**
South San Luis

11. **County & State**
Sandoval, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other -

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

RCVD SEP 29 '08

OIL CONS. DIV.

DIST. 3

13. Describe Proposed or Completed Operations

8/22/08 Road equipment to location. RU rig. NU 4.5" tubing head and flange. NU BOP. RIH with 2.375" workstring and tag fill at 8'. Attempt to circulate casing; pumped 4 bbls water with no blow or circulation out casing. Work tubing through bridge. Start RIH with tubing. Tag again at 240' and attempt to circulate. Found 2" casing valve cemented up. Replaced valve. Circulate tubing down to 780'. Wait on orders. **Plug #1** with 73 sxs Class B cement (87 cf) inside the 4.5" casing from 780' to surface, circulate good cement out casing. PUH to 110' and circulate the well clean. TOH with tubing. Shut in well. SDFD.

8/25/08 Pressure test 4.5" casing to 400 PSI, held OK. RIH with wireline and tag TOC at 125'. Perforate 3 holes at 102'. Establish circulation out the 4.5" x 8.625" annulus. **Plug #2** with 53 sxs Class B cement (63 cf) pumped down the 4.5" casing from 102' to surface, circulate good cement out casing and bradenhead valve. ND BOP. RD rig. Issue Hot Work Permit. Cut off casing. Found cement at surface in both casing and annulus. RD and MOL.

Kelly Roberts, NMOCD representative, was on location. Virgil Lucero, BLM representative, was on location.

14. I hereby certify that the foregoing is true and correct.

Signed

William F. Clark
William F. Clark

Title

Contractor, A-Plus Well Service, Inc.

Date

9/18/08

(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

FARMINGTON FIELD OFFICE