Form 3160-5 (August 1999)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

Vease Serial No. NMSF079329

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an income of the sum of t

abandoned wel	I. Use form 3160-3 (APD)	for such propósals.	6. Il Indian, Allou	ee or Tribe Name
SUBMIT IN TRIF	PLICATE - Other instruction	ons on reverse side.		Agreement, Name and/or No.
1. Type of Well ☐ Oil Well ☐ Gas Well ☐ Oth	er		8. Well Name and SAN JUAN 32	
Name of Operator     CONOCOPHILLIPS COMPAN	ATSY CLUGSTON Mail: piclugs@ppco.com	9. API Well No. 30-045-3184	I9-00-X1	
3a. Address 5525 HIGHWAY 64 FARMINGTON, NM 87401	3b. Phone No. (include area cod Ph: 505.599.3454 Fx: 505-599-3442		10. Field and Pool, or Exploratory BASIN FRUITLAND COAL	
4. Location of Well (Footage, Sec., T	11. County or Par	11. County or Parish, and State		
Sec 13 T32N R9W NWSE 13	SAN JUAN (	SAN JUAN COUNTY, NM		
12. CHECK APPR	ROPRIATE BOX(ES) TO I	NDICATE NATURE OF	NOTICE, REPORT, OR OT	HER DATA
TYPE OF SUBMISSION	TYPE OF ACTION			
☐ Notice of Intent	☐ Acidize	□ Deepen	☐ Production (Start/Resume	Water Shut-Off
_	Alter Casing	☐ Fracture Treat	☐ Reclamation	■ Well Integrity
Subsequent Report	☐ Casing Repair	☐ New Construction	☐ Recomplete	Other
☐ Final Abandonment Notice	Change Plans	Plug and Abandon	☐ Temporarily Abandon	Drilling Operations
	Convert to Injection	□ Plug Back	■ Water Disposal	
Description of cement job to fro Ojo Alamo formations as per I Date - 10/16/03 - Time started Hole - 7.875"; Casing size - 5-Turbo Centralizers - 2166', 22 3351', 3396', 3440', 3484', 352 Preflush - 30 bbls water w/dye Stage 1: Lead - 505 sx (1318 Cello-flake. Tail - 245 sx (311 Bentonite, 0.2% Antifoam, 2.5 Volume Circulated - 68 bbls g Average pressure - 838 psi; A	NTL-FRA-90-1. I - 0000 hrs; Time complete -1/2", 17#, J-55 (new); Set 10', 2254'; Spring Type Cer 26', 3571', 3615', 3658', 370 e in last 10 bbls. cf) Class G, 3% Extender, ( cf) Class G 50/50 POZ, 0.3 #/sx Pheno-seal, 2% CaCla ood cement; Displaced w/8	ed - 0145 hrs @ 3835'. ntralizers - 213', 3219', 326 01', 3745', 3764', 3788', 38 0.2% Antifoam, 5#/sx Phei 253/sx Cello-flake, 5#/sx 6 2. 8 bbls 2% KCI.	63', 3307', 114', no-seal. 0.25#/sx	
14. I hereby certify that the foregoing is  Comr Name (Printed/Typed) PATSY C	Electronic Submission #24 For CONOCOPHIL nitted to AFMSS for process	· · I	ell Information System le Farmington on 10/29/2003 (04AXG1675SE) ORIZED REPRESENTATIVE	
Signature (Electronic S	Submission)	Date 10/20/	2003	
	THIS SPACE FOR	R FEDERAL OR STATE	OFFICE USE	
Approved By ACCEPT	ED		NE GARCIA EUM ENGINEER	Date 10/29/2003
Conditions of approval, if any, are attache certify that the applicant holds legal or equal which would entitle the applicant to condu-	uitable title to those rights in the s uct operations thereon.	ubject lease Office Farmin		
Fitle 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a crestatements or representations as to	rime for any person knowingly a o any matter within its jurisdiction	nd willfully to make to any department.	ent or agency of the United