Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

5.	Lease Serial No.	
	NMSF079381	

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use thi abandoned wel	s form for proposals to dril I. Use form 3160-3 (APD) fo	or to re-enter an or such proposals.	36. If Indian, Allottee	or Tribe Name		
SUBMIT IN TRII	PLICATE - Other instruction	ns on reverse side.	グラff Unit or CA/Agr のNMNM78424B	eement, Name and/or No.		
1. Type of Well		Very state of	8:Well Name and No			
Oil Well 🛛 Gas Well 🔲 Oth			② 「 SAN JUAN 32-8	ONIT 204A		
Name of Operator CONOCOPHILLIPS COMPAN	IY E-M	rsy clugston, ail: plclugs@ppco.com/	9. API Well No. 30-045-31869			
3a. Address 5525 HIGHWAY 64 FARMINGTON, NM 87401	Pt	. Phone No. (include area code) n: 505.599.3454 n: 505-599-3442		10. Field and Pool, or Exploratory BASIN FRUITLAND COAL		
4. Location of Well (Footage, Sec., 7	., R., M., or Survey Description)		11. County or Parish	n, and State		
Sec 34 T32N R8W NWNW 67	70FNL 1070FWL		SAN JUAN CO	DUNTY, NM		
12. CHECK APPI	ROPRIATE BOX(ES) TO IN	DICATE NATURE OF N	NOTICE, REPORT, OR OTH	ER DATA		
TYPE OF SUBMISSION TYPE OF ACTION						
☐ Notice of Intent	☐ Acidize	Deepen	☐ Production (Start/Resume)	□ Water Shut-Off		
	☐ Alter Casing	☐ Fracture Treat	☐ Reclamation	☐ Well Integrity		
Subsequent Report	Casing Repair	New Construction	Recomplete	Other Drilling Operations		
Final Abandonment Notice	Change Plans	Plug and Abandon	Temporarily Abandon	Drilling Operations		
_	Convert to Injection	Plug Back	☐ Water Disposal			
following completion of the involved testing has been completed. Final Al determined that the site is ready for form of the control of the complete of the com	pandonment Notices shall be filed or inal inspection.) agged cement @ 187'. Drilled 5 casing and set @ 3299'. R in last 10 bbls. Pumped 440 ophane, 0.2% Antifoam. Tail nite, 2% CaCl2, 0.25#/sx Cell s FW. Circ. 20 bbls good cer	I cement and then formati U Schlumberger to ceme sx (204.5 bbls 1147.9 cf) - 100 sx (22.5 bbls - 127 lophane, 0.2% antifoam. nent to surface. RD Schlumber	on to 3350'. nt. Pumped a Class G cement cf) 50/50 Class Released wiper plug umberger. ND BOP,	d, and the operator has		
14. Thereby certify that the foregoing is	Electronic Submission #245	IPS COMPAÑY, sent to the	Farmington			
	LUGSTON		RIZED REPRESENTATIVE			
Signature (Electronic	Submission)	Date 10/27/2				
	THIS SPACE FOR	FEDERAL OR STATE	OFFICE USE			
Approved By ACCEPT	ED	TitlePETROLE	E GARCIA UM ENGINEER	Date 10/29/2003		
Conditions of approval, if any, are attached certify that the applicant holds legal or eq which would entitle the applicant to conditions.	uitable title to those rights in the sul		yton			

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.