		<b>1</b>	
FORM 3160-5	UNITED	STATES RECEIVE	FORM APPROVED
(June 1990)	DEPARTMENT OF	F THE INTERIOR	Budget Bureau No. 1004-0135
,	BUREAU OF LAN	D MANAGEMENT 2003 001 10 M 1	. O Expires: March 31, 1993
		7.002 かり <b>132 269 1</b>	5. Lease Designation and Serial No.
	SUNDRY NOTICES AND REPORT	S ON WELLS	SF-078214
Do not use this form for proposals to drill or to deepen or reenter a different reservoir.			6 If Indian, Allottee or Tribe Name
	Use "APPLICATION FOR PER	MIT -" for such proposals	
			7. If Unit or CA, Agreement Designation
	SUBMIT IN TR	PLICATE	
1. Type of Wel			8. Well Name and No.
Oil	Gas	A notified	N .
Well )	X Well Other	fig - 12003	Tiger #14
			9: API Well No.
2. Name of Ope		the second of the second	30-045-29951
Calpine Natural Gas L.P.			10. Field and Pool, or Exploratory Area
3. Address and Telephone No.			Basin Fruitland Coal
			11. County or Parish, State
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  1165' FNL & 1020' FWL Sec. 33-30N-13W			San Juan County, New Mexico
12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, I			
	/PE OF SUBMISSION	TYPE C	OF ACTION
Į.	X Notice of Intent	Abandonment	Change of Plans
$\Omega_{c}$	<del>-</del>	x Recompletion	New Construction
<i>[</i>	Subsequent Report	Plugging Back	Non-Routine Fracturing
{ <i>a</i> -	<b></b>	Casing Repair	Water Shut-Off
, [	Final Abandonment Notice	Altering Casing	Conversion to Injection
	<b></b>	Other	Dispose Water
		(Note: Report results of multiple co	ompletion on Well
		Completion or Recompletion Repo	
work. If we	ell is directionally drilled, give subsur	face locations and measured and true vertical	tinent dates, including estimated date of starting any proposed depths for all markers and zones pertinent to this work.)*  asin Fruitland Coal Gas formation.
•		ure to recomplete the Basin Fruitla	
,	4		CONDITIONS OF APPROVAL Adhere to previously issued stipulations.
14. I hereby see	ertify that the foregoing is true and co	Title OPERATIONS MANAG	GER Date 10/06/03
(This enges	for Federal or State office use)	<b>5</b>	
Approved by		Title	Date 0CT 2.0 3003
	of approval, if any:		001 20 1200
	· · · · · · · · · · · · · · · · · · ·		
			,
Title 18 U.S.	.C. Section 1001, makes it a crime f	or any person knowingly and willfully to make	to any department or agency of the United States andy fals
		tions as to any mater within its jurisdiction.	

MMOCD

\*See Instructions on Reverse Side

## Recompletion Procedure for

## Calpine Natural Gas Company Tiger #14

Location: SWSW Sec 33 T30N R13W Date: October 6, 2003

San Juan County, NM

Field: Basin Fruitland Coal Elev: GL 5535'

KB 5540'

Surface: BLM PBTD 4-1/2" @ 1554'

Minerals: BLM SF-078214 Existing Perfs 1343-1354, 1378-1382'

Set and fill 2 frac tanks with city water and heat to 80 degrees.
 Check for anchors. MOL and RU completion rig. Hold safety meeting.

- 2. NU 2-3/8" relief line. Blow well down and kill with water if necessary.
- 3. ND tubing head and pull tubing slips. NU BOP. POOH with rods and pump.
- 4. POOH with tubing. RIH with tubing and set drillable bridge plug at 1300'. POOH with tubing.
- 5. Perforate 4 spf (0.38" holes) from 1256' to 1263'. Total of 28 holes. Depths refer to the open-hole logs.
- 6. Rig up frac equipment and pressure test surface lines. Fracture with 30,000# of 20/40 Brady sand in a 25#/1000 gal cross-linked gel fluid.
- 7. Close BOPs. RD frac company and install flowline with 1/4" ceramic choke. Flow well back to pit overnight.
- 8. When well dies, TIH with bit on 2-3/8" EUE tubing and clean out and drill out bridge plug at 1300. Drill out bridge plug and clean out to 1554'. TOH with tubing and lay down bit.
- 9. TIH with 1 tail joint, 1-4' perforated sub, Seating Nipple and 45 joints of 2 3/8" tubing. Land tubing at 1385' KB. NU wellhead. RIH with rods and pump. Put well on production. RD and release rig.

Well Name: Tiger #14

Date:

10/6/2003

Operator:

Calpine Natural Gas

Field:

**Basin Fruitland Coal** 

Location:

NWNW Sec. 33-30N-13W

Footages:

1165' FNL & 1020' FWL

County: State:

San Juan

API No.:

New Mexico 30-045-29951

Elevation :

5535 GL, 5540 KB

Surface Hole: 8 3/4"

Production Hole: 6 1/4"

**Tubing:** 45 jts. 2 3/8

Set at: 1450'

## Pump and Rods:

2 x 1-1/2 x 10' top hold pump:


56 - 3/4" rods

1 3/4" x 6' pony rod

1-1/4" x 22' polish rod

**PBTD:** 1554'

**TD**: 1610'



**Spud Date:** 8/20/1999 **First Prod:** 9/29/1999

Surface Casing: 7" 23 #/ft.

Set at: 125'

Cement:

65 sx Class B w/ 4% CaCl

Production Casing: 4 1/2" 10.5 #/ft.

Set at: 1644'

Cement: 90 sx Class B w/ 2%

Econolite

Plus 80 sx Class B

4 SPF

Perfs: 1343-1354

1378-1382

Stimulation: 33600 gal 70 quality foam

80000# 20/40 sand

Max. Pres. : 2100# Min. Pres. : 1600# Ave. Pres. : 1800# ISIP : 1400#

Ave. Rate: 20 BPM