## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RE(		VE	
-----	--	----	--

Conden Notices and Decrease William		DET 0 9 2008
Sundry Notices and Reports on Wells	Bure	au or lar o more janet.
1. Type of Well GAS		SF -080673 If Indian, All. or Tribe Name
2. Name of Operator	7.	Unit Agreement Name
BURLINGTON RESOURCES OIL & GAS COMPANY LP		San Juan 27-4 Unit
3. Address & Phone No. of Operator	8.	Well Name & Number
PO Box 4289, Farmington, NM 87499 (505) 326-9700		San Juan 27-4 Unit 38P API Well No.
A Location of Wall Footon See T D M		30-039-30202
4. Location of Well, Footage, Sec., T, R, M  Unit E (SENIN), 1650; ENL 8, 2250; ENL Sec. 6, T25N, DANY	10.	Field and Pool Basin DK/Blanco MV
Unit F (SENW), 1658' FNL & 2250' FWL, Sec. 6, T27N, R4W, N	11.	County and State Rio ArribaCo., NM
12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF N	OTICE, REPORT, OTHER	DATA
Type of Submission Type of Action  Notice of Intent Abandonment Change of Plan  X Subsequent Report Plugging Non-Routine		sing Report
Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to	f	RCVD OCT 22 '08
13. Describe Proposed or Completed Operations		TIL CONS. DIV.
Report was missed should have been turned in June of 2008.		DIST. 3
06/02/08 MIRU HP 283, PT csg @ 600#/30min, OK. MU 8.75" bit, tagg hole. RIH w/ 104 jnts of 7" 20# J-55csg set @ 4279' w/ ST set @ 3657'. clean, 5 bbl FW. Pumped Lead 6sx(11cf-2bbl) Prem Lite w/ .4% sodium, .25pps Cello Flake. Tail 93sx(129cf-23bbl) Type 3 w/ 1% CaCl, .2% FL 142 bbl mud opend ST & circ 4 bbl cmt to surface. 2nd Stage: Preflushed 479sx(1024cf-182 bbl) Prem Lite w/ .4% sodium, 3% CaCl, 5pps LCM-1Dropped Plug & Displaced w/ 148 bbl FW closed ST, Circ 60 bbl cmt to 06/06/08 PT csg 1500#/30min. MU 6.25" bit, D/O cmt and drilled ahead 205 jnts of 4.5" 11.6# J-55 csg set @ 8517'. RU CMT 06/09/08. Preflush 17sx(39cf-7bbl) Prem Lite w/ . Lead 307sx(608cf-108) Prem Lite w/ 1% and displaced w/ 135 bbl water. ND BOP. RD, released 06/10/08.	RU CMT 06/05/08. 1st Stage, 3% CaCl, 5pps LCM-1, 8% In-52, & .25pps Cello Flake. Dr l w/ 10 bbl Mud clean & 5 bbl l, 8% Bentonite, .4% FL-52, & surface.  to 8523' TD. TD reached on (ned w/ 10 bbl MD Clean, 2 bbl	: Preflushed w/ 10 bbl MD Bentonite, .4% FL-52, & opped plug & displaced w/ FW. Pumped Lead & .25pps Cello Flake.  06/08/08, circ hole. RIH w/ FW. Pumped Scavenger
PT will be conducted by completion rig; results & TOC will appear on ne	ext report. 🗸	
14. I hereby certify that the foregoing is true and correct.  Signed Kelly Je	effery Title Regulatory Tech	<u>nician</u> Date <u>10/07/08.</u>
(This space for Federal or State Office use)  APPROVED BY		Date OCT 1 5 2008  FARMINGTON FIELD OFFICE BY T. SALVESS