District I

1625 N French Dr , Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd, Aztec, NM 87410

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Department Oil Conservation Division 1220 South St. Francis Dr.

Santa Fe. NM 87505

Form C-144 July 21, 2008

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

19	4	4
----	---	---

Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Type of action:	X Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method
	Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method
	Modification to an existing permit
	Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system,
	below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the

environment Nor does approval relieve the operator of its responsibility to comply with any other applic	able governmental authority's rules, regulations or ordinances
Operator: Burlington Resources Oil & Gas Company, LP	OGRID#: <u>14538</u>
Address: PO Box 4289, Farmington, NM 87499	
Facility or well name: Negro Canyon 4M	
API Number: 30-045- 34643 OCD Permit Nu	umber:
U/L or Qtr/Qtr: M(SWSW) Section: 36 Township: 32N Range:	8W County: San Juan
Center of Proposed Design: Latitude: 36.935073' N Longitude:	107.632706' W NAD: ☐ 1927 X 1983
Surface Owner: Federal X State Private Tribal Trust or Ir	ndian Allotment
String-Reinforced Liner Seams: Welded Factory Other Volume:	HDPE
3 X Closed-loop System: Subsection H of 19.15.17.11 NMAC Type of Operation: P&A X Drilling a new well Workover or Drilling (Applie notice of intent)	es to activities which require prior approval of a permit or
X Drying Pad X Above Ground Steel Tanks Haul-off Bins Other X Lined Unlined Liner type: Thickness 20 mil X LLDPE Liner Seams: X Welded X Factory Other	HDPE PVD Other A 121314157677
4	(9 Inct 2003)
Below-grade tank: Subsection I of 19.15.17.11 NMAC	OIL CONS. DIV. DIST. 3
Volume: bbl Type of fluid: Tank Construction material:	OIL CONS. DIV. DIST. 3
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and Visible sidewalls and liner Visible sidewalls only Other Liner Type: Thickness mil HDPE PVC Other	\ \ \\\.
5 Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe En	vironmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15 17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks)			
CHICAGO GUASCERON D ST 17/17 17/11 11/21/2 (Applies to permanent part samporar) print and vector grade tarmen			
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, insti-	tution or chure	ch)	
Four foot height, four strands of barbed wire evenly spaced between one and four feet			
Alternate. Please specify			
7			
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent puts and permanent open top tanks)			
Screen Netting Other			
Monthly inspections (If netting or screening is not physically feasible)			
8	-		
Signs: Subsection C of 19 15 17 11 NMAC			
12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers			
X Signed in compliance with 19 15.3 103 NMAC			
9			
Administrative Approvals and Exceptions:			
Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank:			
Trease theth a box if one of more of the following is requested, if not leave blank.			
Administrative approval(s) Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for const	deration of ap	proval.	
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval			
Siting Criteria (regarding permitting): 19.15.17.10 NMAC			
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable			
source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the			
appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria			
does not apply to drying pads or above grade-tanks associated with a closed-loop system.			
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.	Yes	\square_{No}	
- NM Office of the State Engineer - 1WATERS database search; USGS; Data obtained from nearby wells		L	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa	Yes	□No	
lake (measured from the ordinary high-water mark).			
- Topographic map; Visual inspection (certification) of the proposed site			
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial	Yes	No	
application.			
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)	□NA		
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image			
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	∐No	
(Applied to permanent pits)	∐NA		
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image			
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	∐Yes	∐No	
purposes, or writing 2000 not izonian teet of any other fresh water were or spring, in existence at the time or mittan appreciation			
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.			
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	Yes	No	
adopted pursuant to NMSA 1978, Section 3-27-3, as amended Westton confirmation or varification from the municipality. Written approval obtained from the municipality.			
 Written confirmation or verification from the municipality; Written approval obtained from the municipality Within 500 feet of a wetland. 	Yes	□No	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site		ш	
Within the area overlying a subsurface mine.		No	
- Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division			
Within an unstable area.	Yes	No	
- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map			
Within a 100-year floodplain	☐ Yes	□No	
- FEMA map	🗀 🚟	<u></u>	

Form C-144 Oil Conservation Division Page 2 of 5

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17 9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15 17.10 NMAC
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API or Permit
12
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17 9 NMAC Instructions. Each of the following items must be attached to the application Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC
X Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
X Operating and Maintenance Plan - based upon the appropriate requirements of 19.15 17.12 NMAC
X Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9
NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API
Previously Approved Operating and Maintenance Plan API
13
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
Climatological Factors Assessment Contified Factors Plans - based upon the appropriate requirements of 10.15.17.11.NMAC
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design based upon the appropriate requirements of 19.15.17.11 NMAC
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19 15.17 11 NMAC
Quality Control/Quality Assurance Construction and Installation Plan
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17 12 NMAC
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
Nuisance or Hazardous Odors, including H2S, Prevention Plan
Emergency Response Plan
Oil Field Waste Stream Characterization
Monitoring and Inspection Plan
Erosion Control Plan
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Proposed Closure: 19.15.17.13 NMAC
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.
Type. Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank X Closed-loop System
Alternative Dispussed Clayura Matheda
Proposed Closure Method: Waste Excavation and Removal X Waste Removal (Closed-loop systems only)
On-site Closure Method (only for temporary pits and closed-loop systems)
In-place Burial On-site Trench
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
Waste Excavation and Removal Closure Plan Checklist: (19 15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan.
Please indicate, by a check mark in the box, that the documents are attached.
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19 15 17 13 NMAC

Form C-144 Oil Conservation Division Page 3 of 5

16 Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel	Tanks or Houl-off Rins Only	(10 15 17 12 D NMAC)	
Instructions: Please identify the facility or facilities for the disposal of liquids, drilling f			cilities
are required	Diamond Facility Down 4 #	NIM 01 0011	
Disposal Facility Name: Envirotech	Disposal Facility Permit #:		
Disposal Facility Name: Basin Disposal Facility	Disposal Facility Permit #		<u> </u>
Will any of the proposed closed-loop system operations and associated activities Yes (If yes, please provide the information No	occur on or in areas that wi	ll not be used for future se	rvice and operations?
Required for impacted areas which will not be used for future service and operations Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC			
17			
Siting Criteria (Regarding on-site closure methods only: 19 15.17 10 NMAC Instructions Each siting criteria requires a demonstration of compliance in the closure plan Receitain siting criteria may require administrative approval from the appropriate district office of the control of the con	ecommendations of acceptable soi r may be considered an exception	which must be submitted to the !	
for consideration of approval. Justifications and/or demonstrations of equivalency are required	. Please refer to 1915 17 10 NM/ 	AC for guidance	
Ground water is less than 50 feet below the bottom of the buried waste	nad from noorby walls		Yes No
- NM Office of the State Engineer - iWATERS database search; USGS: Data obtain	ned from nearby wens		∐N/A
Ground water is between 50 and 100 feet below the bottom of the buried waste	and from nonthy wells		Yes No
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtain	led from hearby wells		∐N/A
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtain	ned from nearby wells	•	Yes No
-	·		
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other signification (measured from the ordinary high-water mark).	ant watercourse or lakebed, sin	khole, or playa lake	∐Yes ∐No
- Topographic map; Visual inspection (certification) of the proposed site			
 Within 300 feet from a permanent residence, school, hospital, institution, or church in e Visual inspection (certification) of the proposed site; Aerial photo, satellite image 	xistence at the time of initial ap	pplication	∐Yes ∐No
, , , , , , , , , , , , , , , , , , , ,			Yes No
Within 500 horizontal feet of a private, domestic fresh water well or spring that less that purposes, or within 1000 horizontal fee of any other fresh water well or spring, in existe - NM Office of the State Engineer - iWATERS database; Visual inspection (certific	ence at the time of the initial ap		
Within incorporated municipal boundaries or within a defined municipal fresh water we pursuant to NMSA 1978, Section 3-27-3, as amended.		pal ordinance adopted	Yes No
 Written confirmation or verification from the municipality; Written approval obta Within 500 feet of a wetland 	med from the municipanty		□Yes □No
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspe	ection (certification) of the prop	osed site	
Within the area overlying a subsurface mine.			Yes No
- Written confiramtion or verification or map from the NM EMNRD-Mining and M	ineral Division		
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mi	neral Resources: USGS: NM G	eological Society:	∐Yes ∐No
Topographic map		cological decicity,	
Within a 100-year floodplam FEMA map			Yes No
18			
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of by a check mark in the box, that the documents are attached.	of the following items must	bee attached to the closur	e plan. Please indicate,
Stting Criteria Compliance Demonstrations - based upon the appropriate	requirements of 19.15.17.10) NMAC	
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC			
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC			
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC			
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC			
Disposal Faculity Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)			
Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC			
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC			

Form C-144 Oil Conservation Division

19 Operator Application Certification:		
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.		
Name (Print): Crystal Tafoya Title: Regulatory Technician		
Signature: Date: Date:		
e-mail address: <u>crystal.tafoya@conocophilips.com</u> Telephone 505-326-9837		
20 OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 1/-3-08		
Title: En Siro /sper OCD Permit Number:		
Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Instructions Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:		
22		
Closure Method: Waste Excavation and Removal On-site Closure Method Alternative Closure Method Waste Removal (Closed-loop systems only) If different from approved plan, please explain.		
23 Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: Instructions: Please identify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized.		
Disposal Facility Name: Disposal Facility Permit Number:		
Disposal Facility Permit Number: Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations?		
Yes (If yes, please demonstrate compliane to the items below) No		
Required for impacted areas which will not be used for future service and operations: Site Reclamation (Photo Documentation) Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique		
24 <u>Closure Report Attachment Checklist:</u> Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.		
Proof of Closure Notice (surface owner and division)		
Proof of Deed Notice (required for on-site closure) Plot Plan (for on-site closures and temporary pits)		
Confirmation Sampling Analytical Results (if applicable)		
Waste Material Sampling Analytical Results (if applicable)		
Disposal Facility Name and Permit Number		
Soil Backfilling and Cover Installation		
Re-vegetation Application Rates and Seeding Technique		
Site Reclamation (Photo Documentation)		
On-site Closure Location Latitude: Longitude NAD 1927 1983		
Operator Closure Certification:		
I hereby certify that the information and attachments submitted with this closure report is ture, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.		
Name (Print): Title		
Signature: Date:		
e-mail addressTelephone:		

Form C-144 Oil Conservation Division

Burlington Resources Oil & Gas Company, LP

Closed Loop Design:

The closed loop design will not incorporate a temporary pit or below grade tank. The plan will utilize an above grade tank suitable for holding the cuttings and fluids generated during drilling operations. The volume of the tank shall be of a sufficient volume to maintain an adequate free board for periodic removal and disposal of cuttings and fluids.

Burlington Resources Oil & Gas Company, LP may incorporate the use of a 20 mil, string reinforced, LLDPE liner with factory welded seams to line the drying pad in order to minimize the volume of fluids to be disposed of. The drying pad will be designed to prevent contamination of fresh water, protect public health and the environment, and have sumps to facilitate the collection of liquids derived from drilling cuttings, as specified per subsection H of 19.15.17.11. The cuttings pad will be constructed above grade and containment will be through the use of earthen berms of sufficient height to contain the cuttings and prevent run-off of surface water or fluids. The drying pad area will replace the area of the drill site previously designated for the reserve pit. It will be signed in compliance with 19.15.3.103.NMAC. Frac tanks will be utilized on site for fresh water storage.

Closed Loop Operations and Maintenance:

The closed loop system will be operated and maintained for solids and liquid containment to prevent ground water contamination as follows:

- Any free liquids will be recovered and reused or disposed of at the Basin Disposal Facility (Permit # NM-01-005). Reuse may include the relocating of liquids to be used in other permitted drilling operations.
- 2. Drill solids will be recovered from location and hauled to a Envirotech (Permit #NM-01-0011) periodically as required to maintain a safe free board in the cuttings tank. No onsite trench burial of cuttings will occur.
- 3. In the event a drying pad is utilized, the cuttings will be picked up and transported to Basin Disposal Facility (Permit #NM-01-005). The liner will be disposed of at the San Juan County Landfill located on CR 3100. The drying pad will be closed within 6 months from the date that the drilling rig is released. Berms constructed from native materials will be bladed on site to the location's contour.
- 4. Any drilling materials or trash will be stored and disposed of appropriately.
- 5. The NMOCD will be notified within 48 hours of the discovery of compromised integrity of the closed loop containment. Any required repairs will commence immediately.

Closed Loop Closure Plan:

- Upon completion of the drilling operations, all solids and liquids will be removed and disposed of to Envirotech (Permit #NM-01-0011) and Basin Disposal Facility (Permit # NM-01-005). Equipment shall also be removed from location. In the event a drying pad is utilized, the solids contained on the pad shall remain on site to allow sufficient drying and will then be transported to Envirotech (Permit # NM-01-0011) within 6 months from the date that the drilling rig is released.
- 2. After the drying pad is removed the surface below will be visually inspected for any contamination. If contamination is discovered a five point composite sample will be taken of the drying pad area using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

- 3. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 4. Notification will be sent to OCD when the reclaimed area is seeded.
- 5. BR shall seed the disturbed areas the first growing season after the operator closes the drying pad. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rimrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgrass	Hy-crest	3.0
Bottlebrush Squirreltail	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows:

Source No. One (poor quality)
Purity
50 percent
Germination
Percent PLS
20 percent

Source No. two (better quality)
Purity
80 percent
Germination
63 percent
Percent PLS
50 percent

5 lb. bulk seed required to make 2 lb. bulk seed required to make

1 lb. PLS . 1 lb. PLS