

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505
AS DRILLED

Form C-102
Revised October 12, 2005
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies
NOV 21 '08
AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

OIL CONS. DIV.

¹ API Number 30-039-30531	² Pool Code 80690	³ Pool Name So. Los Pinos Frt/Sand Pictured Cliffs
⁴ Property Code 19641	⁵ Property Name Northeast Blanco Unit	⁶ Well Number 258 H
⁷ OGRID No. 06137	⁸ Operator Name Devon Energy Production Company, L.P.	⁹ Elevation 6322' GL

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
K	2	30-N	7-W		2685'	NORTH	2415'	WEST	Rio Arriba

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
D	24	30-N	7-W		695'	NORTH	678'	WEST	Rio Arriba

¹² Dedicated Acres NW/4-158.62	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
--	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

5280' ® 695' 678' 1901' 2685' BOTTOM HOLE 7\"/> 1718' 2415' SURFACE 2					¹⁷ OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. Signature <u>Mike Pippin</u> Date <u>11/19/08</u> Printed Name <u>Mike Pippin</u>
					¹⁸ SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. 4/7/08 Date of Survey Signature and Seal of Professional Surveyor Gary D Mann 7016 Certificate Number

5284' (R)



Job Number: 08236
 Company: Devon Energy
 Lease/Well: NEBU 258 H
 Location: Rio Arriba County
 Rig Name:
 RKB:
 G.L. or M.S.L.:

State/Country: New Mexico
 Declination:
 Grid:
 File name: J:\CUST08~1\SURVEYS\DEVON\08236.SVY
 Date/Time: 29-Oct-08 / 07:15
 Curve Name: As Drilled

API# 30-039-30531

#258H
 7" SHOE @ 3860'
 K SURF 2685' FN 2415' FW
 F 784 697
 7" 1901' FN 1718' FW

Inwell, Inc

WINSERVE SURVEY CALCULATIONS
 Minimum Curvature Method
 Vertical Section Plane 319.00
 Vertical Section Referenced to Wellhead
 Rectangular Coordinates Referenced to Wellhead

#258H TD-5472
 K SURF 2685' FN 2415' FW
 D BH 1990 1737
 695' FN 678' FW

RCVD NOV 21 '08
 OIL GISS. DIV.

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	CLOSURE		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
.00	.00	.00	.00	.00	.00	.00	.00	.00	.00
2291.00	.00	.00	2291.00	.00	.00	.00	.00	.00	.00
2341.00	1.00	296.40	2341.00	.19	-.39	.40	.44	296.40	2.00
2373.00	1.10	296.40	2372.99	.45	-.92	.94	1.02	296.40	.31
2404.00	2.70	314.55	2403.97	1.10	-1.70	1.95	2.03	302.84	5.45
2436.00	5.00	325.80	2435.90	2.78	-3.02	4.08	4.11	312.61	7.53
2466.00	7.70	329.60	2465.71	5.60	-4.78	7.36	7.36	319.52	9.10
2497.00	10.60	330.90	2496.32	9.88	-7.21	12.19	12.23	323.86	9.38
2529.00	13.40	327.80	2527.61	15.59	-10.62	18.74	18.87	325.73	8.98
2560.00	16.20	325.30	2557.58	22.19	-15.00	26.59	26.78	325.94	9.26

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
2591.00	18.60	322.70	2587.16	29.68	-20.46	35.82	36.04	325.42	8.14
2622.00	21.30	321.90	2616.30	38.04	-26.93	46.38	46.61	324.71	8.75
2654.00	23.30	322.00	2645.90	47.60	-34.41	58.50	58.74	324.14	6.25
2685.00	25.10	322.10	2674.18	57.62	-42.23	71.19	71.44	323.77	5.81
2717.00	27.00	321.75	2702.93	68.68	-50.89	85.23	85.49	323.46	5.96
2748.00	28.90	320.35	2730.31	79.98	-60.03	99.75	100.00	323.11	6.48
2779.00	30.80	320.90	2757.20	91.91	-69.82	115.17	115.42	322.78	6.19
2810.00	32.80	320.80	2783.54	104.57	-80.13	131.49	131.75	322.54	6.45
2841.00	34.50	320.75	2809.35	117.88	-90.99	148.66	148.92	322.34	5.48
2871.00	35.90	319.45	2833.86	131.14	-102.09	165.95	166.19	322.10	5.29
2901.00	37.30	318.25	2857.94	144.61	-113.86	183.84	184.05	321.78	5.24
2933.00	39.10	317.90	2883.09	159.33	-127.08	203.62	203.81	321.42	5.67
2963.00	40.80	317.90	2906.09	173.62	-140.00	222.88	223.03	321.12	5.67
2995.00	42.80	317.80	2929.94	189.44	-154.31	244.21	244.33	320.83	6.25
3026.00	45.00	317.80	2952.28	205.36	-168.75	265.69	265.80	320.59	7.10
3057.00	47.00	317.30	2973.81	221.81	-183.80	287.99	288.07	320.35	6.56
3087.00	49.40	316.90	2993.81	238.19	-199.02	310.34	310.40	320.12	8.06
3118.00	51.80	317.10	3013.48	255.71	-215.36	334.27	334.32	319.90	7.76
3149.00	54.70	317.25	3032.03	273.93	-232.24	359.10	359.13	319.71	9.36
3179.00	57.70	317.05	3048.71	292.20	-249.19	384.01	384.03	319.54	10.02
3210.00	61.70	316.25	3064.35	311.66	-267.56	410.75	410.76	319.35	13.09
3242.00	66.00	316.10	3078.45	332.38	-287.45	439.43	439.43	319.15	13.44
3273.00	69.40	316.16	3090.21	353.05	-307.32	468.07	468.07	318.96	10.97
3304.00	72.00	316.75	3100.46	374.26	-327.48	497.30	497.30	318.81	8.58
3336.00	72.20	317.25	3110.29	396.53	-348.25	527.73	527.74	318.71	1.61
3367.00	71.70	316.85	3119.90	418.10	-368.33	557.19	557.20	318.62	2.03
3398.00	72.20	316.90	3129.50	439.61	-388.48	586.64	586.66	318.53	1.62
3429.00	73.40	317.30	3138.67	461.31	-408.63	616.24	616.27	318.46	4.06
3459.00	76.60	318.35	3146.43	482.78	-428.09	645.21	645.24	318.44	11.19

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
3491.00	77.80	319.20	3153.52	506.25	-448.65	676.41	676.44	318.45	4.56
3522.00	78.10	318.50	3160.00	529.08	-468.60	706.73	706.76	318.47	2.41
3554.00	78.40	319.45	3166.51	552.71	-489.16	738.06	738.09	318.49	3.05
3585.00	78.60	318.80	3172.69	575.68	-509.04	768.43	768.46	318.52	2.15
3616.00	78.90	318.90	3178.74	598.58	-529.05	798.84	798.87	318.53	1.02
3707.00	76.30	317.90	3198.28	665.03	-588.05	887.70	887.73	318.52	3.05
3804.00	73.70	317.30	3223.38	734.22	-651.22	981.36	981.41	318.43	2.75
X 3874.00	73.30	317.60	3243.27	783.66	-696.61	1048.45	1048.52	318.37	.70
3904.00	73.70	317.30	3251.79	804.85	-716.06	1077.21	1077.28	318.34	1.64
3936.00	76.10	317.80	3260.12	827.65	-736.91	1108.09	1108.17	318.32	7.65
3965.00	79.50	319.10	3266.25	848.86	-755.70	1136.43	1136.51	318.32	12.52
3996.00	83.30	320.80	3270.88	872.32	-775.42	1167.07	1167.14	318.37	13.40
4027.00	87.00	322.10	3273.50	896.47	-794.67	1197.92	1197.98	318.45	12.65
4058.00	89.90	323.40	3274.34	921.14	-813.42	1228.84	1228.88	318.55	10.25
4089.00	90.90	324.20	3274.13	946.15	-831.73	1259.73	1259.75	318.68	4.13
4121.00	91.50	323.80	3273.46	972.03	-850.53	1291.60	1291.61	318.81	2.25
4214.00	90.20	322.80	3272.08	1046.59	-906.10	1384.33	1384.33	319.11	1.76
4308.00	91.70	322.10	3270.52	1121.10	-963.38	1478.14	1478.17	319.33	1.76
4402.00	91.30	321.40	3268.06	1194.89	-1021.56	1572.00	1572.05	319.47	.86
4493.00	89.00	321.85	3267.82	1266.23	-1078.05	1662.90	1662.99	319.59	2.58
4586.00	90.40	320.30	3268.31	1338.58	-1136.47	1755.83	1755.95	319.67	2.25
4679.00	88.70	319.70	3269.04	1409.81	-1196.25	1848.81	1848.94	319.68	1.94
4772.00	90.00	318.45	3270.09	1480.07	-1257.16	1941.80	1941.93	319.66	1.94
4867.00	91.20	317.20	3269.10	1550.47	-1320.94	2036.77	2036.87	319.57	1.82
4961.00	89.70	316.60	3268.36	1619.10	-1385.17	2130.70	2130.77	319.45	1.72
5055.00	89.00	315.45	3269.43	1686.74	-1450.43	2224.57	2224.60	319.31	1.43
5149.00	90.70	314.90	3269.67	1753.41	-1516.69	2318.35	2318.36	319.14	1.90
5242.00	90.80	316.80	3268.45	1820.13	-1581.46	2411.20	2411.20	319.01	2.05
5336.00	90.80	317.90	3267.14	1889.26	-1645.14	2505.15	2505.15	318.95	1.17

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
5415.00	91.10	317.60	3265.83	1947.73	-1698.25	2584.12	2584.12	318.91	.54
Projected to Bit									
5472.00	91.10	317.60	3264.74	1989.81	-1736.68	2641.09	2641.10	318.89	.00