

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

RECEIVED

NOV 10 PM 2 08

070 Farmington, NM

1. Type of Well
GAS

2. Name of Operator

BURLINGTON
RESOURCES

OIL & GAS COMPANY LP

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

870' FNL, 1820' FWL, Sec. 11, T-27-N, R-4-W, NMPM

5. Lease Number

NMSF-080671A

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 27-4 Unit

8. Well Name & Number

San Juan 27-4 U #28A

9. API Well No.

30-039-23716

10. Field and Pool

Blanco Mesaverde

11. County and State

Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment

Type of Action

☐ Abandonment ☐ Change of Plans
☐ Recompletion ☐ New Construction
☐ Plugging Back ☐ Non-Routine Fracturing
☐ Casing Repair ☐ Water Shut off
☐ Altering Casing ☐ Conversion to Injection
☒ Other - Tubing repair and squeeze

13. Describe Proposed or Completed Operations

10-24-03 MIRU. SDON.
10-25-03 ND WH. NU BOP. TIH, tag up @ PBTD @ 6614'. TOOH w/205 jts 2 3/8" tbg. TIH w/7" RBP, set @ 2000'. Load hole w/wtr. TOOH. ND BOP. ND WH to check secondary seal. NU csg head & BOP. SDON.
10-26-03 Load hole w/12 bbl wtr. Fluid level falling. ND BOP & csg head. TIH w/7" pkr, set @ 30'. Load csg w/wtr. Found holes in csg @ 340-370'. Stub up csg, install new 7" csg head. PT csg head. NU BOP. TIH, PT RBP & csg, OK. TOOH w/pkr. SDON.
10-27-03 (Verbal approval to squeeze from Steve Mason, BLM and Charlie Perrin, OCD). TIH w/retrieving tool. Establish circ. Circ sd off RBP. Reset RBP @ 3000'. Load hole w/wtr. TOOH. TIH w/pkr, set @ 500'. PT RBP & csg to 500 psi/15 min, OK. TOOH w/pkr. Ran CBL @ 0-3110', TOC @ 2338' w/stringers. SDON.
10-28-03 Establish injection into holes in csg @ 340-370' w/20 bbl wtr. Establish circ down csg & out bradenhead. Pump 50 sx Class "B" neat cmt down csg. Displace w/1 bbl wtr. Close bradenhead valve. Displace cmt to 300' w/4 bbl wtr. Left 40-70' cmt in csg. TOOH. WOC. SDON.
10-29-03 PT csg & cmt to 500 psi, OK. TOOH. TIH w/mill to TOC @ 300'. Establish circ. Mill cmt @ 300-360'. TOOH w/mill. TIH w/retrieving tool. PT csg to 500 psi, OK. Circ sd off RBP. Latch RBP, TOOH. TIH w/211 jts 2 3/8" 4.7# J-55 EUE tbg, landed @ 6538'. (SN @ 6528'). ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed Nancy Altman Title Senior Staff Specialist Date 11/7/03

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

Date NOV 17 2003

CONDITION OF APPROVAL, if any:

NMOC

NOV 17 2003
Jm