In L	ieu	of
Fori	n 3	160
(Jur	e I	990

3

4

Type of Well

Oil Well Gas Well X

## UNITED STATES DEPARTMENT OF INTERIOR BUREAU OF LAND MANAGEMENT

RECE	FORM APPROVED  Budget Bureau No 1004-0135  Expires March 31, 1993
------	-------------------------------------------------------------------

SUNDRY NOT	TICE AND	REPORTS	ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use

TO DRILL" for permit for such proposals

DEC 0 1 32008 Lease Designation and Serial No
Jicarilla Apache Contract #93

APPLICATION Jicarilla Apache Contract #93

Bureau of Lanc Management

Farmington Field Office Indian, Allottee or Tribe Name

Jicarilla Apache Nation

7 If Unit or CA, Agreement Designation

SUBMIT IN TRIPLICATE

8 Well Name and No.

Other Jicarilla 93 #12B

2.Name of Operator9API Well NoWILLIAMS PRODUCTION COMPANY30-039-29805

Address and Telephone No.

PO BOX 640 Aztec, NM 87410-0640

10 Field and Pool, or Exploratory Area
Blanco MV

Location of Well (Footage, Sec., T., R., M., or Survey Description)

1190' FNL & 660' FWL, Sec. 34, T27N, R3W

County or Parish, State
Rio Arriba, NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

	TYPE OF SUBMISSION	TYPE OF ACTION	
	Notice of Intent	Abandonment	Change of Plans
$\sim$		Recompletion	New Construction
P	X Subsequent Report	Plugging Back	Non-Routine Fracturing
•		Casing Repair	Water Shut-Off
	Final Abandonment	Altering Casing	Conversion to Injection
		Ξ Other – Surface Casing	Dispose Water
		(Note Report results of multiple completion on	
			Well Completion or Recompletion Report and
			Log form )

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-26-08 – TD 14-3/4" SURFACE HOLE @ 325', 1330 HRS RUN 7 JTS 10-3/4', 40.5# K-55, LT&C CASING, SET @ 317'

CMT W/ BJ SVC AS FOLLOWS; 10 BBL FRESH WATER PRE FLUSH FOLLOWED BY 200sx (281 cuft ) TYPE III CMT + 1/4# cello-flake/sk (YEILD=1.41 cuft, WT=14.5#/GAL) CIRC. 15 BBL'S GOOD CMT TO PIT. PLUG DOWN @ 6:36 PM 11/26/08

11-27-08 - TEST BOPE-PIPE RAMS, BLIND RAMS, INNER & OUTER MUD CROSS VALVES, CHOKE MANIFOLD VALVES, KILL LINE VALVES, UPPER KELLY VALVE, FLOOR VALVE, 250# LOW F/5 - MIN EACH, 1500# HIGH F 10 MIN EACH. TEST 10-3/4" CSG @ 1500# F/ 30 MIN. ALL TESTS GOOD. [ TEST PLUG, TEST PUMP, & CHART RECORDER USED ] TEST WITNESSED BY ROD VELARDE [ JICARILLA OIL & GAS ]

RCVD DEC 18'08 OIL CONS. DIV. DIST. 3

14.	I hereby certify that the foregoing is to de and correct  Signed Larry Higgins	Title <u>Drilling COM</u>	Date 12-1-2008 ACCEPTED FOR ECOCAD
	(This space for Federal or State office use)	- marketing ten	DEC 1 8 2338
	Approved by	Title	Date
	Conditions of approval, if any.		FARMINGTON FIELD OFFICE BY

Title 18 U S C Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

