FORM APPROVED OMB No. 1004-0136 Expires November 30, 2000 Form 3160-3 (August 19*9*9) UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT 5. Lease Serial No. NM-16057 APPLICATION FOR PERMIT TO DRILL OR REENTER 6. If Indian, Allottee or Tribe Name la. Type of Work: Ø DRILL CREENTER 7. If Unit or CA Agreement, Name and No Farmington, NM 8. Lease Name and Well No. Oil Well Poles Paradise #90 lb. Type of Well: Gas Well Other Single Zone ☐ Multiple Zone Name of Operator
 DUGAN PRODUCTION CORP. Contact: KURT FAGRELIUS 9. API Well No. E-Mail: kfagrelius@duganproduction.com 300453195 3a. Address 709 EAST MURRAY DRIVE 10. Field and Pool, or Exploratory 3b. Phone No. (include area code) Ph: 505.325.1821 Basin Fruitland Coal FARMINGTON, NM 87401 Fx: 505.327.4613 4. Location of Well (Report location clearly and in accordance with any State requirements.\*) 11. Sec., T., R., M., or Blk. and Survey or Area At surface SWSW 993' FSL 986' FWL 36.4927 N Lat, 108.1910 W Lon Sec. 9, T30N, R14W At proposed prod. zone Same As Above 14. Distance in miles and direction from nearest town or post office\*
Approx. 7-Miles North of Kirtland, New Mexico 12. County or Parish SAN JUAN 13. State NM Distance from proposed location to nearest property or lease line, ft. (Also to nearest drig, unit line, if any) 16. No. of Acres in Lease 17. Spacing Unit dedicated to this well 986' 320-W/2 800.00 18. Distance from proposed location to nearest well, drilling, 19. Proposed Depth 20. BLM/BIA Bond No. on rile completed, applied for, on this lease, ft. 1250' Approx. 1,250' 21. Elevations (Show whether DF, KB, RT, GL, etc. 5594 22. Approximate date work will start ASAP 23. Estimated duration 5-DAYS 24. Attachments The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form: 1. Well plat certified by a registered surveyor. 4. Bond to cover the operations unless covered by an existing bond on file (see 2. A Drilling Plan. Item 20 above). 3. A Surface Use Plan (if the location is on National Forest System Lands, the Operator certification SUPO shall be filed with the appropriate Forest Service Office). Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature Kurt Tzgrelu	Name (Printed/Typed) KURT FAGRELIUS	Date 10/6/03
Title GEOLOGIST		att 646. and a
A Pay David J. Mankiewicz	Name (Printed/Typed)	NOV 1 2 2003
Title	Office	NVC.

Application approval does not warrant or certify the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

A water based gel-mud will be used to drill surface and production casing hole. Standard 2,000 psi BOP will be used to drill production hole. The Fruitland Coal will be completed from approximately 950' - 1115'. The interval will be fractured.

DRILLING OPERATIONS AUTHORIZED ARE SUBJECT TO COMPLIANCE WITH ATTACHED "GENERAL REQUIREMENTS".

This action is subject to technical and procedural review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4

District 1

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Avenue, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico

Energy, Minerals & Natural Resources Department OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-102

Revised June 10, 2003

Submit to Appropriate District Office

State Lease - 4 Copies

Fee Lease - 3 Copies

☐ AMENDED REPORT

# WELL LOCATION AND ACREAGE DEDICATION PLAT

30-045-3	7957 71629	BASIN FRUITLAND	COAL
Property Code		PARADISE	'Wall Number
<sup>7</sup> OGRID №. 006515		Operator Name ICTION CORP.	, Elevation 5594

<sup>10</sup> Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
M	9	30 N	14 W		993	SOUTH	986	WEST	SAN JUAN

11 Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Ida	Feet from the	North/South line	Fect from the	East/West line	County
12 Dedicated Acres	Joint o	r Infill	Consolidation	Code 15 Or	der No.				
320 W/2	:								

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

16/////////////////////////////////////		<sup>17</sup> OPERATOR CERTIFICATION
DUGAN		I hereby certify that the information contained herein is true
NM-16057		and complete to the best of my knowledge and belief.
<b>Y</b> ////////////////////////////////////	·	•
\$/////////////////////////////////////		Signature
	15 (5 15 17 pg	Kurtjaguelan
\$/////////////////////////////////////		Printed Name
	A MOVED S	Kurt Fagrelius
		Title and E-mail Address
		Geologist
		Date
		Oct. 6, 2003
	Selected in the selection of the selecti	<sup>18</sup> SURVEYOR CERTIFICATION
<b>\</b>		I hereby certify that the well location shown on this plat was
		plotted from field notes of actual surveys made by me or under
		my supervision, and that the same is true and correct to the
		best of my belief.
C ON CANOLINA		185578030
		Date of Survey N ME Signature and Scal of Professional Surveyors
986' 000		Signalists and Scal of Professional Surveyor
	.	155129
1.56		15519 (A)
<b>Ö</b>		305ER03 100
V/////X/X/////////////////////////////	0075.55	Certificate Number STONAL
<u> </u>	2635.55	75516

# EXHIBIT B OPERATIONS PLAN

Poles Paradise #90

# APPROXIMATE FORMATION TOPS:

Kirtland	Surface'	Pictured Cliffs	1120′
Fruitland	680′	Total Depth	1250'

Catch samples every 10 feet from 900 feet to total depth.

#### LOGGING PROGRAM:

Run cased-hole GR-CCL-CNL from total depth to surface.

### CASING PROGRAM:

Hole	Casing		Setting	Grade and
Size	Size	Wt./ft.	Depth	Condition
<del>9-7/</del> 8"	7"	20#	120′	J-55
6-1/4"	4-1/2"	10.5#	1250′	J-55

Plan to drill a 9-7/8" hole and set 250' of 7" OD, 20#, J-55 surface casing. Then plan to drill a 6-1/4" hole to total depth with gel-water mud program to test the Fruitland Coal. 4-1/2", 10.5#, J-55 production casing will be run and cemented. Cased hole GR-CCL-CNL log will be run. Productive zone will be perforated and fractured. After frac, the well will be cleaned out and production equipment will be installed.

#### CEMENTING PROGRAM:

Surface: Cement to surface with 70 cf Class B + 2% CaCl<sub>2</sub>. Circulate to surface.

Production Stage-Cement with 130 cf 2%Lodense with

%# celloflake/sx followed by 70 cf Class "B" with

%# celloflake/sx.

Total cement slurry for production stage is 200 cf.

Circulate cement to surface.

An adequate spacer will be pumped ahead of the cement slurry to help prevent mud contamination of the cement. An adequate number of casing centralizers will be run through usable water zones to ensure that casing is centralized through these zones. The adequate number of centralizers will be determined based on API standards. Centralizers to impart a swirling action around the casing will be used just below and into the base of the

lowest usable water zone. These devices will assist mud displacement, increase cement bonding potential and create an effective hydraulic seal. A chronological log will be kept which records the pump rate, pump pressure, slurry density, and slurry volume for the cement job. The log will be sent to the BLM after completion of the job.

## WELLHEAD EQUIPMENT:

Huber 7"x4-1/2" casing head, 1000# WP, tested to 2000#. Huber 4-1/2"x2-7/8" tubing head, 1000# WP, tested to 2000#.

BOP and Related Equipment will include for a 2000 psi system: (Exhibit D)

Annular preventer, double ram, or 2 rams with one being blind and one being a pipe ram.

Kill line (2" minimum)

1 kill line valve (2" minimum)

1 choke line valve

2 chokes

Upper kelly cock valve with handle available Safety valve and subs to fit all drill string connections in use.

Pressure gauge on choke manifold.

2" minimum choke line.

Fill-up line.

#### Contacts:

Dugan Prod.Corp. Office & Radio Dispatch: 325-1821

Mark Brown	327-3632 320-8247	
Kurt Fagrelius	325-4327 320-8248	
John Alexander	325-6927 320-1935	