

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED

Sundry Notices and Reports on Wells

2003 NOV 21 AM 9:06

1. Type of Well

GAS

2. Name of Operator

**BURLINGTON**

RESOURCES OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 328-9780

4. Location of Well, Footage, Sec., T, R, M

2050' FSL, 990' FWL, Sec. 24, T-31-N, R-17-W, NM PM

5. Lease Number

14-20-603-2037

6. If Indian, All. or

Tribe Name

Navajo

7. Unit Agreement Name

Horseshoe Gallup Unit

8. Well Name & Number

Horseshoe Gallup U#97

9. API Well No.

30-045-10547

10. Field and Pool

Horseshoe Gallup

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☒ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☐ Other -

13. Describe Proposed or Completed Operations

10/08/03 MIRU. Open up well, no pressures. Layout relief line to pit. Remove WH cap. PU & release tbg slips, release packer. Install flange & NU BOP, test. SDON.

10/09/03 TOOH and tally 40 joints 2-3/8" tbg and LD packer. TIH, set 5-1/2" DHS cmt retainer @ 1200'. PT tbg to 1300#. Sting out of retainer & load csg w/15 bbls water. PT csg to 500 psi/15 mins, held OK. Plug #1 with retainer @ 1200', spot 47 sxs cmt inside csg above CR up to 800' to isolate the Gallup perfs. TOH and LD tbg. RU wireline & perf 2 sqz holes at 217'. Establish circ out BH w/12 bbls of water. Circ BH annulus with 10 bbls of water. Plug #2 with 127 sxs cmt pumped down the 5-1/2" csg from 217' to surface, to circ good cmt out the BH valve. WOC. SDON.

10/12/03 TIH with tbg & tag cmt at 50' down inside the 5-1/2" csg. LD tbg. Remove BH valve, unable to determine top of cmt in BH annulus. Wait on orders from W. Freeman with Navajo EPA. Connect pump line to BH valve & pump 15 bbls of wtr. Created a hole in 8-5/8" surface csg @ 2' below GL @ 100# pressure. Wait on orders from J. Lovato with BLM. J. Walker with Navajo EPA required the annulus to be cemented with 1" pipe from the surface. Arrange for 1" pipe. Shut in well. SDON.

10/13/03 ND BOP and flange. Dig out and cut off wellhead. RU tools for 1" pipe. TIH & tag cmt in BH annulus at 40'. Plug #2a with 35 sxs cement: 1<sup>st</sup> inside the BH annulus from 40 to surface; and 2<sup>nd</sup> inside the 5-1/2" casing from 50' to surface. TOH & LD 1" pipe. Install P&A marker. RD. Rig released.

R. Maurer, Burlington Resources, representative was on location.

W. Ashley, Navajo Nation representative was on location.

Well was plugged and abandoned 10/13/03.

14. I hereby certify that the foregoing is true and correct.

Signed Tammy W. Ashely Title Regulatory Specialist Date 11/20/03

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FOR RECORD

NOV 24 2003

ALBUQUERQUE FIELD OFFICE

NMOCDD