

RECEIVED

In Lieu of
Form 3160
(June 1990)

UNITED STATES
DEPARTMENT OF INTERIOR
BUREAU OF LAND MANAGEMENT

FEB 06 2009

FORM APPROVED
Budget Bureau No 1004-0135
Expires March 31, 1993

SUNDRY NOTICE AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir Use "APPLICATION TO DRILL" for permit for such proposals

Bureau of Land Management
Farmington Field Office

5. Lease Designation and Serial No.
Jicarilla Apache Contract #92

6. If Indian, Allottee or Tribe Name
Jicarilla Apache Nation

7. If Unit or CA, Agreement Designation

SUBMIT IN TRIPLICATE

1. Type of Well
Oil Well Gas Well X Other

8. Well Name and No
Jicarilla 92 #18A

2. Name of Operator
WILLIAMS PRODUCTION COMPANY

9. API Well No.
30-039-29943

3. Address and Telephone No
PO BOX 640 Aztec, NM 87410-0640

10. Field and Pool, or Exploratory Area
Blanco MV

4. Location of Well (Footage, Sec , T , R , M , or Survey Description)
1850' FNL & 2000' FEL SEC 29, T27N, R3W

11. County or Parish, State
Rio Arriba, NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input checked="" type="checkbox"/> Notice of Intent	Abandonment
<input type="checkbox"/> X Subsequent Report	Recompletion
<input type="checkbox"/> Final Abandonment	Plugging Back
	Casing Repair
	Altering Casing
	X Other <u>SURFACE CASING</u>
	Change of Plans
	New Construction
	Non-Routine Fracturing
	Water Shut-Off
	Conversion to Injection
	Dispose Water
	(Note Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)*

2/3/09- TD 12 1/4" SURF HOLE @ 350', 1900 HRS

RAN 7 JTS, 9.5/8", 36# K-55, FLOAT INSERT 294', CSG SET @ 341'

CEMENT 9-5/8" CASING @ 340' - SHOE DEPTH / SINGLE SLURRY CEMENT JOB / 20 BBLs. FRESH WATER SPACER / 200 sxs premium - class G, 2% cacl .0.125 lbm poly-e-flake.cmt slurry 46bbl (240 CuFt) slurry @ 15.6 ppg (yield = 1.2 / wgps 5.24) displace w/ 22.8 bbls, bump plug w/ 150psi @ 2300 on 2/3/2009. 15 bbls of cement returns to surface ✓

2/4/09-INSTALL TEST PLUG & TEST BOP PIPE & BLIND RAMS, CHOKE MANIFOLD VALVES, MUD CROSS VALVES, FLOOR VALVE 250# 5-MIN EACH & 1500# 10-MIN EACH. TEST CHARTS WAS USED ✓

TEST BOP PIPE & BLIND RAMS, CHOKE MANIFOLD VALVES, MUD CROSS VALVES, FLOOR VALVE @ 250# 5-MIN EACH & 1500# 10-MIN EACH. TEST 9 5/8" CSG @ 1500# 30-MIN. CSG HIGH TEST DROP 10# ON TEST CHARTS. BRYCE HAMMOND SAID TO PU. 8.3/4" BIT & TIH W/ DC'S & TAG UP @ 264

TEST CASING TO 600 PSI W/ TEST CHARTS, TEST 9.5/8" CASING ON TOP OF PLUG W/ 600 PSI . TEST F/ 10MIN & PSI DROP 10# ON THE TEST CHARTS . SO BRYCE W/ BLM SAID T/ GO ON W/ OPERATIONS. ✓

PU. KELLY & TEST 250# LOW 5 -MIN & 1500# HIGH 10 MIN. TEST CHARTS WAS USED ✓

RCVD FEB 13 '09
OIL CONS. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed Larry Higgins
Larry Higgins

Title Drilling COM

Date 2/6/09


(This space for Federal or State office use)

Approved by _____

Title _____

Date FEB 11 2009

Conditions of approval, if any



Title 18 U S C Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

NMOCD