This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## **Oil Conservation Division**

## **Northwest New Mexico Packer-Leakage Test**

Page 1 Revised June 10, 2003

Operator ConocoPhillips					Lease Name AXI APACHE O					Well No2	
ocation of We	ell: Unit	Letter _	D S	Sec 0	3	Twp 025N	Rge	i —	004W API	# 30-039-20677	
	Name of Reservoir or Pool			ol	Type of Prod			Method of Prod		Prod Medium	
Upper Completion	PC				Gas			Flow		Tubing	
Lower Completion	MV				Gas			Flow		Tubing	
				Pre-f	Flow S	hut-In Pressu	re Data	t •			
Upper	Hour, Date, Shut-In				Length of Time Shut-In			SI Press. PSIG		Stabilized?(Yes or No)	
Completion	8/25/2008				110 hours			: 151		Yes	
Lower	Hour, Da	Hour, Date, Shut-In			Length of Time Shut-In			SI Press. PSIG		Stabilized?(Yes or No)	
Completion	8/25/2008				0 hours				189	Yes	
					Flov	w Test No. 1		3			
Commenced	at:	8	3/25/2008			Zone Pro	oducing (L	Jpper	or Lower): Lo	wer	
Time (date/time)		Lapsed Time Since* Upp			PRESSURE		Prod Zone Temperature			Danada	
				Upper zone		Lower zone			Remarks		
8/26/2008 2:33:25 PM			38	168		220			Day 1	· <u></u>	
8/27/2008 2:34:24 PM			62	17	7	262	Day 2		Day 2		
8/28/2008 2:35:13 PM			86	18	37	281			Day 3 Opened Lower Zone		
8/29/2008 2:36:30 PM			110	19	1	136		,	Test Completed		
roduction rate	e during t	test						k k			
l:BPOD Based on:		Bbls.	In	Hrs.		Grav		GOR			
ias		MCF	PD; Test th	nru (Orific	e or M	eter)			•		
				Mid-	Test SI	hut-In Pressu	re Data	i			
Upper Completion	Hour, Date, Shut-In				Length of Time Shut-In			SI Press. PSIG		Stabilized?(Yes or No)	
	Hour, Date, Shut-In				Length of Time Shut-In			SI Press. PSIG		Stabilized?(Yes or No)	



## Flow Test No. 2

Commer	nced at:			Zone Pro	Zone Producing (Upper or Lower)					
Time		Lapsed Time		SURE	_Prod Zone					
(dat	e/time)	Since*	Upper zone	Lower zone	Temperature	9	Remarks			
							·			
	<u>.</u>									
Productio	n rate during	test								
Oil:	BPOD	Based on:	Bbls. In	Hrs.		Grav.	GOR			
Gas		MCFPD; Test th	ru (Orifice or M	leter)						
Remarks	* *** **** ** ***** ******						<u> </u>			
I hereby o	certify that the	information herein co	ontained is true	and complete	to the best o	f my knowledge.				
Approved	. MA	IR 0 4 2009	20	Onera	tor: Conoco	nPhillins				
• •		nservation Division		Ву:	Augustine G					
23	AGG. R			-						
Ву:		0.0		Title:	Multi-Skilled	d Operator				
Title:	itle: Deputy Oil & Gas Inspector, District #3				Date: Tuesday, September 09, 2008					

## NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified 1. 6.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days

-> \

- 4 For Flow Test No 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours
- Following completion of Flow Test No 1, the well-shall again be shut-in, in accordance with Paragraph 3 above

- Flow Test No 2 shall be conducted even though no leak was indicated during Flow Test No 1. Procedure for Flow Test No 2 is to be the same as for Flow Test No 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests, immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data
- 24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone
- The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)