This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator Cond	ocoPhilli	ips		₋ease Name	SAN	JUAN 32-7 UN	NT	Well No83
Location of We	ell: Unit	Letter M	Sec28	Twp _	032N	Rge	007W API	# 30-045-26376
	Name of Reservoir or Pool			Type of Prod			Method of Prod	Prod Medium
Upper Completion	FRS	FRS		Gas		Flow		Casing
Lower Completion	MV			Gas				Tubing
			Pre-FI	ow Shut-In	Pressu	re Data		
Upper Completion	Hour, Date, Shut-In 8/20/2008			Length of Time Shut-In 153 hours			ss. PSIG 547	Stabilized?(Yes or No) Yes
Lower Completion	Hour, Date, Shut-In 8/20/2008			Length of Time Shut-In 203 hours			ss. PSIG 140	Stabilized?(Yes or No) Yes
				Flow Test	: No. 1			
Commenced	at: 8/2	6/2008 9:36:00 AM	Λ	. Z	one Pro	oducing (Uppe	er or Lower): Up	pper
Time Lapsed Time (date/time) Since*		Upper z	PRESSURE cone Lowe	r zone	Prod Zone Temperature	Remarks		
8/26/2008 9:36:48 AM 0		551	4	44	Turned upper		zone on.	
8/27/2008 12:05	:20 PM	27	153	4	44			
8/28/2008 11:46	:11 AM	50	163	4	44			
Production rate	e during	test					\$	
Dil:BPOD Based on:Bbl			Bbls. Ir	bls. InHrs			Grav.	GOR
Gas		MCFPD; Tes	t thru (Orifice	or Meter) _			,	•
			Mid T	oot Chut-In	Process	iro Data		
	Hour, Date, Shut-In			d-Test Shut-In Pressure Dat Length of Time Shut-In			ss. PSIG	Stabilized?(Yes or No)
Upper Completion	riour, D							



Flow Test No. 2

Commenced at:			Zone Pro	Zone Producing (Upper or Lower)					
Time	Lapsed Time		SURE	Prod Zone					
(date/time)	Since*	Upper zone	Lower zone	Temperature		Remarks			
					,				
					·				
					:				
Production rate during	test								
Dil:BPOD Based on:		Bbls. In	Hrs.		Grav.	GOR			
Gas	MCFPD; Test th	ru (Orifice or M	leter)						
Remarks:					,				
				THE R PERSONAL PROPERTY.					
					4				
					<u>. </u>				
I hereby certify that the		ontained is true	and complete	to the best of	my knowledge.				
Approved:	R O 4 2009	20	Opera	tor: Conocol	Phillips				
New Mexico Oil Cor			Ву:	By: Travis Munkres					
By: Kerry G. Roll			Title:	Multi-Skilled	Operator				
Title: Deputy C	oil & Gas Inspect District #3	tor,	_ Date:	Date: Monday, September 08, 2008					

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- 7 Jul 222 19
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones, shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days
- while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note, it, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours
- For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1 Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. It a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone
- 8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)

Following completion of Flow Test No 1, the well shall again be shut-in, in accordance with Paragraph 3