

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

**RECEIVED**

FEB 25 2009

## Sundry Notices and Reports on Wells

1. **Type of Well**  
GAS

2. **Name of Operator**  
**BURLINGTON**  
RESOURCES OIL & GAS COMPANY LP

3. **Address & Phone No. of Operator**  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. **Location of Well, Footage, Sec., T, R, M**  
Surf: Unit J (NWSE), 1965' FSL & 1965' FEL, Sec. 31, T29N, R7W, NMPM

Bureau of Land Management  
Farmington Field Office

5. **Farmington Number**

SF-078503

6. **If Indian, All. or Tribe Name**7. **Unit Agreement Name**

San Juan 29-7 Unit

8. **Well Name & Number**9. **San Juan 29-7 Unit 110N  
API Well No.**

30-039-30551

10. **Field and Pool  
Basin DK/Blanco MV**11. **County and State  
Rio Arriba, NM****12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA****Type of Submission****Type of Action**☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - Casing Report☒ Subsequent Report☐ Recompletion☐ New Construction

RCVD MAR 2 '09

☐ Final Abandonment☐ Plugging☐ Non-Routine Fracturing

OIL CONS. DIV.

☐ Casing Repair☐ Water Shut off

DIST. 3

☐ Altering Casing☐ Conversion to Injection**13. Describe Proposed or Completed Operations**

2/15/09 MIRU HP 282, PT csg @ 600#/30min, OK. MU 8.75" bit, D/O cmt and drilled ahead to 3594', circ hole. RIH w/ 84 jnts of 7" 20# J-55csg set @ 3585'. RU CMT 2/19/09. Preflushed w/ 10bbl GW, 10bbl FW. Pumped Lead 434sx(934cf-166bbl) 75/25 TXI/G w/ .2% Antifoam, .25pps Cellophane, 2% Extender, Tail 92sx(113cf-20bbl) 50/50 POZ/G w/ .1% Antifoam, 2% Bent, .25pps Cellophane, .2% dispersant, .5pps Kolite. Dropped Plug & Displaced w/ 143bbl FW, Circ 62 bbl cmt to surface @ 0100hrs on 2/20/09. ✓

1400hrs on 2/20/09 PT csg 1500#/30min. MU 6.25" bit, D/O cmt and drilled ahead to 7867' TD. TD reached on 2/22/09, circ hole. RIH w/ 191 jnts of 4.5" 11.6/10.5# J-55csg set @ 7856'. RU CMT 2/22/09, Preflushed w/ 10bbl GW, 2bbl FW. Pumped 433sx(630cf-112bbl) 50/50 POZ w/ .1% Antifoam, .25pps Cellophane, 3.5% Gel, 5pps Kolite, .15% Retarder, .25% Uniflac-s. Dropped plug and displaced w/ 124bbl H2O. ND BOP. RD, released 2/23/09. ✓

PT will be conducted by completion rig; results & TOC will appear on next report. ✓

REPORT PRESSURE TEST RESULTS  
FOR 7" CASING

**14. I hereby certify that the foregoing is true and correct.**

Signed

Kelly Jeffery Title Regulatory Technician Date 2/25/09.

(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

NMOC

86

ACCEPTED FOR RECORD

FEB 26 2009

FARMINGTON FIELD OFFICE

BY T. Salpers