

UNITED STATES
DEPARTMENT OF INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

MAR 02 2009

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICE AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use Form 3160-1 for "TO DRILL" for permit for such proposals

Lease Designation and Serial No.
701-02-0014

6. If Indian, Allottee or Tribe Name
Jicarilla Apache Nation

7. If Unit or CA, Agreement Designation

SUBMIT IN TRIPLICATE

1. Type of Well
Oil Well Gas Well X Other

8. Well Name and No.
JAECO 26-3 22 #2A

2. Name of Operator
WILLIAMS PRODUCTION COMPANY

9. API Well No
30-039-30051

3. Address and Telephone No.
PO BOX 640 Aztec, NM 87410-0640

10. Field and Pool, or Exploratory Area
Blanco MV

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
790' FSL & 900' FWL, Sec. 22, T26N, R3W

11. County or Parish, State
Rio Arriba, NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

Notice of Intent
x Subsequent Report
Final Abandonment

TYPE OF ACTION

Abandonment
Recompletion
Plugging Back
Casing Repair
Altering Casing
X Other INTERMEDIATE CASING

Change of Plans
New Construction
Non-Routine Fracturing
Water Shut-Off
Conversion to Injection
Dispose Water
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2/27/09- TD 8 1/4" INT HOLE @ 4228', 0800 HRS

RCVD MAR 16 '09
OIL CONS. DIV.
DIST. 3

2/28/09- RAN 90 JTS, 7", K-55, 8 RD, 23#, LT&C, CSG SET @ 4219', FLOAT INSERT @ 4171' CEMENT 7" INTERMEDIATE CSG. @ 4219' SHOE DEPTH / 7" CASING CEMENTED ON 2/28/09 @ 2000 HRS 2 SLURRY CEMENT JOB / 20 BBLS. WATER SPACER / LEAD = 370 SXS EXTENDACEM+5#SX PHENO SEAL+5% CAL-SEAL CELLO FLAKE + 179.2 BBLS. WATER = 200 BBL OF SLURRY @ 11.5 PPG = 1008CuFt (YIELD+2.723/WGPS=15.333) TAIL=100 SX PREMIUM CMT=0.125#SX POLY FLAKE+ 12.4 BBLS. WATER = 21 BBLS. SLURRY @15.6#/GAL PPG=117.8 Cu Ft (YIELD=1.178 / WGPS=5.2) / DISPLACE WITH 164.BBLS. WATER / BUMP PLUG @ 1300. 54 BBLS OF CEMENT RETURNS TO SURFACE. FLOATS DID NOT HOLD, SHUT IN F/ 4HRS W/ 200 PSI. ✓

3/1/09- INSTALL PLUG & PRESS TEST 3.5" PIPE RAMS & FLOOR VALVE, 250# LOW 5 MIN, 1500# HIGH FOR 10 MIN, OK TEST CSG 1500 PSI 30MIN HIGH, CHANGE OUT PIPE RAMS, TEST PUMP, TEST PLUG & CHARTS USED ✓

14. I hereby certify that the foregoing is true and correct

Signed Larry Higgins
Larry Higgins

Title Drilling COM Date 3/2/09

(This space for Federal or State office use)

Approved by _____

Title _____

Date MAR 11 2009

Conditions of approval, if any

ACCEPTED FOR RECORD
MAR 11 2009
FARMINGTON FIELD OFFICE
BY <u>T. Salvo</u>

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD