RECEIVED
APR 13 2009 submitted in lieu of Form 3160-5 UNITED STATES DEPARTMENT OF THE INTERIOR Bureau of Land Management BUREAU OF LAND MANAGEMENT Famington Field Office Sundry Notices and Reports on Wells 5 SF-079290-A 6. If Indian, All. or Type of Well Tribe Name **GAS** 7. **Unit Agreement Name** San Juan 28-7 Unit Name of Operator ConocoPhillips Well Name & Number Address & Phone No. of Operator 158M 9. PO Box 4289, Farmington, NM 87499 (505) 326-9700 API Well No. 30-039-30238 Location of Well, Footage, Sec., T, R, M 10. Field and Pool Surf: Unit H (SE/NE), 1380' FNL & 220' FEL, Section 23, T28N, R7W, NMPM Blanco MV/Basin DK 11. **County and State** Rio Arriba, NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Submission Type of Action Change of Plans Notice of Intent Abandonment X Other -Casing Report New Construction Recompletion RCVD APR 15'09 Non-Routine Fracturing Subsequent Report Plugging OIL CONS. DIV. Water Shut off Casing Repair Conversion to Injection Final Abandonment Altering Casing DIST. 3 13. Describe Proposed or Completed Operations 3/30/2009 MIRU H&P 281, NU BOP. PT csg 600#/30 min. ok. RIH w/ 8 3/4" bit & tag cmt @ 65', D/O cmt and drilled ahead to 3550' Int TD on 4/2/2009. Circ Hole. RIH w/85 ints of 7" csg, 20#, J-55 ST&C set @ 3539' RU CMT. 4/3/2009 Preflushed w/10bbls GW & 10 bbls FW. Pumped Scavenger w/ 15sx(56cf-10bbl) w/ 75% Type XI / 25% Class G Cement w/ .25 lb/sx Cellophane Flakes, 3% Sodium Medasilicate, 20% Antifoam. Pumped Lead w/ 525sx(1118cf-199bbl) w/ 75% Type XI / 25% Class G Cement w/ .25 lb/sx Cellophane Flakes, 2% Sodium Medasilicate, .20% Antifoam. Pumped Tail w/ 84sx(116cf-21bbl) w/ 50:50 POZ Cement w/.25 lb/sk Cellophane Flake, 5 lb/sk Gilsonite, 2% Bent, .15% Fric Reducer, .1% Antifoam. Drop plug & displace w/ 142bbls of FW. Bump plug. Report Toc behind 7" csg. 4/4/2009 @ 0030hrs PT csg 1500#/30min, ok. 4/4/2009 RIH w/ 6 1/4" bit & tag cmt, D/O cmt and drilled ahead to TD 7845' on 4/5/2009. Circ hole. RIH w/172 Jnts of 4 1/2" csg, 10.5#, J-55, ST&C @ 7843'. RU cement. 4/7/2009 Pumped Scavenger w/ 15sx(27cf-5bbl) w/ 50:50 POZ Cement, .25 lb/sk Cellophane Flake, 5 lb/sk Kolite, 3.5% Bentonite, .25% FL, .15% FR, .15% Retarder, .1% Antifoam. Pumped Tail w/ 305sx(604cf-107bbl) w/ 50:50 POZ Cement, .25 lb/sk Cellophane Flake, 5 lb/sk Kolite, 3.5% Bentonite, .25% FL, .15% FR, .15% Retarder, .1% Antifoam. Drop plug & displace w/ 125 bbls FW. Bump plug. Plug down @ 0720hrs on 4/7/2009. RD&RR on 4/7/2009. ✓ PT will be conducted by completion rig; results and TOC will appear on next report. 14. I hereby certify that the foregoing is true and correct.

Title Staff Regulatory Technician

Date 4/8/2009

Ethel Tally

Signed'