RECEIVED

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

APR 03 2009

Bureau of Land Management

	Sundry Notices and Re	ports on Wells	- Familigion Fie		
1.	Type of Well GAS			5. 6.	Lease Number SF – 078943-A If Indian, All. or Tribe Name
	Name of Operator BURLINGTON			7.	Unit Agreement Name San Juan 29-7 Unit
	HESOURCES OIL	& GAS COMPANY LP	e .		
3.	Address & Phone No. of Ope			- 8.	Well Name & Number San Juan 29-7 Unit 126
	PO Box 4289, Farmington, N	M 87499 (505) 326-9700		9.	API Well No.
_				-	30-039-30592
	Location of Well, Footage, S			10.	Field and Pool Basin DK/Blanco MV
	Surf: Unit K (NWSE), 1800' Bottom: Unit N (SESW), 710				
.1	,,	,,	, , , , , , , , , , , , , , , , , , , ,	11.	County and State Rio Arriba, NM
12. 0			RE OF NOTICE, REPORT, O	THER I	DATA
	Type of Submission Ty Notice of Intent	pe of Action Abandonment	Change of Plans	X	Other - Casing Report
	X Subsequent Report	Recompletion Plugging	New Construction Non-Routine Fracturing		RCVD APR 15'09
	X Subsequent Report	Casing Repair	Water Shut off		OIL CONS. DIV.
	Final Abandonment	Altering Casing	Conversion to Injection		DIST. 3
on 3/ Prefil Cello CaCl w/ 19/ and c 3/19/ 0.25 CaCl surfa 3/26/ LT& 10sxs 260s.	2/2009 AWS 777. NU BOP. 3/13/2009PT Casing 600#/30min, ok. RIH w/8 ½1" bit & tag cmt, D/O cmt and drilled ahead to TD Int 4255' 3/17/2009. Circ Hole. RIH w/101 jnts of 7" csc, 23#, J-55 LT&C set @ 4251' w/ Stage Tool @ 2700'. RU CMT. 3/18/2009 1st STAGE flushed w/ 10 bbls FW, 10 bbls GW, 10 bbls FW. Pumped Scavenger w/ 20sx(56cf-10bbl) Premium Lite Cement w/ 3% CaCl, 0.25 pps lo-Flake,5 pps LCM-1, 0.4% FL-52, 8% bentonite and 0.4% SMS. Pumped Lead w/ 170sx(362cf-64bbl) w/ Premium Lite Cement w/ 3% CI, 0.25 pps Cello-Flake,5 pps LCM-1, 0.4% FL-52, 8% bentonite and 0.4% SMS. Pumped Tail w/ 100sx(138cf-25bbl) w/Type III Cement 1% CaCl, 0.25 pps Cello-Flake and 0.2% FL-52. Plug down around 2345hrs on 3/18/2009. 3/19/2009 Open DV Tool @ 1200# @ 0300hrs circ. Circ 30bbls of cmt to surface. 9/2009 2nd STAGE Preflushed w/ 10 bbls FW, 10 bbls GW, Pumped Scavenger w/ Premium Lite Cement 20sx(56cf-10bbl) w/ 3% CaCl, 5 pps Cello-Flake,5 pps LCM-1, 0.4% FL-52, 8% bentonite and 0.4% SMS. Pumped Lead 390sx(831cf-148bbl) w/ Premium Lite w/ 3% CI, 0.25 pps Cello-Flake,5 pps LCM-1, 0.4% FL-52, 8% bentonite and 0.4% SMS. Plug down @ 0500hrs on 3/19/2009. Circ 50bbls cmt to face. Bump plug & Close DV Tool @ 2700#. 6/2009 RIH W 6 ½1' bit & tag cmt, D/O cmt and drilled ahead to final TD @ 7956' on 3/28/2009. RIH w/ 94 jnts of 4 ½2' csg, 11.6#, L-80, &C & 96 jnts of 4 ½2' csg, 11.6#, J-55, LT&C set @ 7936'. RU cmt. 3/30/2009 Preflushed w/ 10bbls CW & 2bbls FW. Pumped Scavenger as (27cf-5bbls) w/ Premium Lite HS FM Cement w/ 0.25pps Cello-Flake, 0.3% CD-32, 6.25pps LCM-1, 1% FL-52. Plug down @ 0715 RD&RR 3/30/2009. PT will be conducted on next report. TOC and results will appear on next report.				
14	I hereby certify that the foregoing is true and correct. Need PT results on 7" casing				
Sign	9,000	•	Cally Title Staff Regulatory To	echnicia	n Date <u>04/02/2009.</u>
APP CON	s space for Federal or State Of PROVED BY	Title any: son knowingly and willfully to make any depa	its jurisdiction.	8	ACCEPTED FOR RECORD Date APR 1 3 2009 FARMINGTON FIELD OFFICE TL SOMES