## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

## RECEIVED

APR 0 7 2009 ...

	Bureau of Land Management Farmington Field Office
	5. Lease Number SF-078416
1. Type of Well	6. If Indian, All. or
GAS	Tribe Name
2. Name of Operator	7. Unit Agreement Name
ConocoPhillips	
3. Address & Phone No. of Operator	- 8. Well Name & Number Hardie 1N
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9. API Well No.
4. Location of Well, Footage, Sec., T, R, M	30-045-34878
	10. Field and Pool
Surf: Unit L (NW/SW), 2124' FSL & 999' FWL, Section 26, T29N, R8W, NMPM	Basin DK/Blanco MV 11. County and State San Juan, NM
12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, O	THER DATA
Type of Submission Type of Action  Notice of Intent Abandonment Change of Plans	X Other – Csg Report
Recompletion New Construction  X Subsequent Report Plugging Non-Routine Fracturing	RCVD APR 15'09
Casing Repair Water Shut off Final Abandonment Altering Casing Conversion to Injection	OIL CONS. DIV. DIST. 3
13. Describe Proposed or Completed Operations  3/29/2009 MIRU H&P 283. NU BOP. 3/29/2009 PT Csg 600#/30 min. 3/29/2009 RIH w/8 ¾" bit & tag TD Int 3575' on 3/31/2009. Circ Hole. RIH w/86 jnts of 7" csc, 20#, J-55 ST&C set @ 3560' w/ Stage tool STAGE Preflushed w/ 10 bbls FW, 10 bbls MC II, Pumped Scavenger 20sx(56cf-10bbl) w/Premium Lite w/ Premium Lite FM Cement w/ 4% Sodium Metasilicate, 3% CaCl12, 5lbs LCM-1, 8% Bentonite, .4% I Pumped Tail 90sx(124cf-22bbl) Type I-II Cement w/ 1% CaCl, 0.25 pps Cello-Flake and 0.2% FL-52. Dr 4/02/2009 Open Stage Tool @ 2579' and circ. Circ 8 bbls of cmt to surface. 4/03/2009 2nd STAGE Preflushed w/ 10 bbls FW, 10 bbls GW. Pumped Scavenger 20sx(56cf-10bbl) w/F 330sx(703cf-125bbl) Premium Lite FM Cement w/ 4% Sodium Metasilicate, 3% CaCl12, 5lbs LCM-1, 8' Cellophane Flakes. Drop plug & displace w/ 104bbls of FW. Bump plug & Close Stage Tool @ 1718#. Plug down @ 0243 on 4/3/2009. WOC. PT DV Tool & Csg @ 1500#/30Min @ 1230hrs on 4/03/2009. 3/27/2009 RIH W 6 ¼" bit & tag cmt, D/O cmt and drilled ahead to final TD @ 7763' on 4/4/2009. RIH w & 21 jnts of 4 ½" csg, 11.6#, J-55, LT&C set @ 7759'. RU cmt. 4/5/2009 Preflushed w/ 10bbls CW & 21 10sx(27cf-5bbl) Premium Lite HS FM Cement, Pumped Tail 310sx(614cf-109bbl) w/ Premium Lite HS FCD-32, 6.25pps LCM-1, 1% FL-52A. Drop & displace w/ 123 bbls FW. Plug down @ 2115hrs on 4/5/2 PT will be conducted by completion rig; results and TOC will appear on next report.   14. I hereby certify that the foregoing is true and correct.  Signed Ethel Tally Title Staff Regulatory	cmt @ 60', D/O cmt and drilled ahea @ 2579'. RU CMT. 4/02/2009 1st Cement, Pumped Lead 65sx(138cf-25 L-52A, .25lbs Cellophane Flakes. op plug & disp w/ 50bbl FW. Bump remium Lite Cement, Pumped Lead Bentonite, .4% FL-52A, .25lbs Bump plug. Circ 48 bbls cmt to surfaction of 4 ½" csg, 10.5#, J-55, Sbls FW. Pumped Scavenger w/M Cement w/ 0.25pps Cello-Flake, 39009. RD&RR 4/5/2009.
3/29/2009 MIRU H&P 283. NU BOP. 3/29/2009 PT Csg 600#/30 min. 3/29/2009 RIH w/8 ¾" bit & tag TD Int 3575' on 3/31/2009. Circ Hole. RIH w/86 jnts of 7" csc, 20#, J-55 ST&C set @ 3560' w/ Stage tool STAGE Preflushed w/ 10 bbls FW, 10 bbls MC II, Pumped Scavenger 20sx(56cf-10bbl) w/Premium Lite w/ Premium Lite FM Cement w/ 4% Sodium Metasilicate, 3% CaCl12, 5lbs LCM-1, 8% Bentonite, 4% I Pumped Tail 90sx(124cf-22bbl) Type I-II Cement w/ 1% CaCl, 0.25 pps Cello-Flake and 0.2% FL-52. Dr 4/02/2009 Open Stage Tool @ 2579' and circ. Circ 8 bbls of cmt to surface. 4/03/2009 2nd STAGE Preflushed w/ 10 bbls FW, 10 bbls GW. Pumped Scavenger 20sx(56cf-10bbl) w/F 330sx(703cf-125bbl) Premium Lite FM Cement w/ 4% Sodium Metasilicate, 3% CaCl12, 5lbs LCM-1, 8 Cellophane Flakes. Drop plug & displace w/ 104bbls of FW. Bump plug & Close Stage Tool @ 1718#. Plug down @ 0243 on 4/3/2009. WOC. PT DV Tool & Csg @ 1500#/30Mjn @ 1230hrs on 4/03/2009. 3/27/2009 RIH W 6 ¼" bit & tag cmt, D/O cmt and drilled ahead to final TD @ 7763' on 4/4/2009. RIH v 8 21 jnts of 4 ½" csg, 11.6#, J-55, LT&C set @ 7759'. RU cmt. 4/5/2009 Preflushed w/ 10bbls CW & 21 l0sx(27cf-5bbl) Premium Lite HS FM Cement, Pumped Tail 310sx(614cf-109bbl) w/ Premium Lite HS FCD-32, 6.25pps LCM-1, 1% FL-52A. Drop & displace w/ 123 bbls FW. Plug down @ 2115hrs on 4/5/2 PT will be conducted by completion rig; results and TOC will appear on next report.   14. I hereby certify that the foregoing is true and correct.  Signed Ethel Tally Title Staff Regulatory (This space for Federal or State Office use)	cmt @ 60', D/O cmt and drilled ahea @ 2579'. RU CMT. 4/02/2009 1st Cement, Pumped Lead 65sx(138cf-25tL-52A, .25lbs Cellophane Flakes. op plug & disp w/ 50bbl FW. Bump remium Lite Cement, Pumped Lead & Bentonite, .4% FL-52A, .25lbs Bump plug. Circ 48 bbls cmt to surfact of 168 jnts of 4 ½" csg, 10.5#, J-55, Sbls FW. Pumped Scavenger w/ M Cement w/ 0.25pps Cello-Flake, 35009. RD&R 4/5/2009.
3/29/2009 MIRU H&P 283. NU BOP. 3/29/2009 PT Csg 600#/30 min. 3/29/2009 RIH w/8 ¾" bit & tag TD Int 3575' on 3/31/2009. Circ Hole. RIH w/86 jnts of 7" csc, 20#, J-55 ST&C set @ 3560' w/ Stage tool STAGE Preflushed w/ 10 bbls FW, 10 bbls MC II, Pumped Scavenger 20sx(56cf-10bbl) w/Premium Lite w/ Premium Lite FM Cement w/. 4% Sodium Metasilicate, 3% CaCl12, 5lbs LCM-1, 8% Bentonite, .4% I Pumped Tail 90sx(124cf-22bbl) Type I-II Cement w/ 1% CaCl, 0.25 pps Cello-Flake and 0.2% FL-52. Dr. 4/02/2009 Open Stage Tool @ 2579' and circ. Circ & bbls of cmt to surface.  4/03/2009 2nd STAGE Preflushed w/ 10 bbls FW, 10 bbls GW. Pumped Scavenger 20sx(56cf-10bbl) w/F 330sx(703cf-125bbl) Premium Lite FM Cement w/. 4% Sodium Metasilicate, 3% CaCl12, 5lbs LCM-1, 8 Cellophane Flakes. Drop plug & displace w/ 104bbls of FW. Bump plug & Close Stage Tool @ 1718#. Plug down @ 0243 on 4/3/2009. WOC. PT DV Tool & Csg @ 1500#/30Mjin @ 1230hrs on 4/03/2009. 3/27/2009 RIH W 6 ¼" bit & tag cmt, D/O cmt and drilled ahead to final TD @ 7763' on 4/4/2009. RIH & 21 jnts of 4 ½" csg, 11.6#, J-55, LT&C set @ 7759'. RU cmt. 4/5/2009 Preflushed w/ 10bbls CW & 21 10sx(27cf-5bbl) Premium Lite HS FM Cement, Pumped Tail 310sx(614cf-109bbl) w/ Premium Lite HS FCD-32, 6.25pps LCM-1, 1% FL-52A. Drop & displace w/ 123 bbls FW. Plug down @ 2115hrs on 4/5/2 PT will be conducted by completion rig; results and TOC will appear on next report. ✓  14. I hereby certify that the foregoing is true and correct.  Signed Ethel Tally Title Staff Regulatory	cmt @ 60', D/O cmt and drilled ahea @ 2579'. RU CMT. 4/02/2009 1st Cement, Pumped Lead 65sx(138cf-25tL-52A, .251bs Cellophane Flakes. op plug & disp w/ 50bbl FW. Bump remium Lite Cement, Pumped Lead % Bentonite, .4% FL-52A, .251bs Bump plug. Circ 48.bbls cmt to surfact w/ 168 jnts of 4 ½" csg, 10.5#, J-55, Sbls FW. Pumped Scavenger w/ M Cement w/ 0.25pps Cello-Flake, 3009. RD&RR 4/5/2009.