ECHIM O IEE

, ,

NEW MEXICO OH, CONSERVATION COMMISSION Sunta Fe, New Moxico

N. 188	If state land If patented la Address	660 feet (N.)	(S) of the Sout te of SV BV or legal subdivision	Sec. 36	
	(Give location If state land If patented la Address If governmen	n from section or other the oil and gas lease and the owner is	r legal subdivision	lines. Cross out wro	
	If state land If patented is Address If governmen	the oil and gas lease and the owner is	· ————		
	Address If governmen	and the owner is	17 No	Asagument Ne	, m Telo
	Address If governmen		* ** ** ***		
	If governmen				
		it land the permittee	1-		•
	i Address .		18		
		PROPOLISM PR	DUCTS CORPOR	HOITA	
	The lessee is	Previtt, New			* ***
PRIFOLE	UM FRODUCTS O	ORPORATION - B	LAMERT BORD	-	Sacks Coment
7*0.D.	204	Deed	1630	Coment ed	150 Sacks
				,	and A second distance
			before cementing o . 1630 te	er landing c. sing W et.	cstimate that
	ON THIS 40.40 PLACE ORIGINA	RETRACT _ 10.3 L SENT IN 10-11	OTION CONFORM 142 AS TO EXA by yours,	is to sotermoss act location of	it abquirani F Vell no.)
KPORT TO RE		Sincere			
	TRIBOLE to use the follow sine of Casing 780.D. n the above plan ductive oil or gas nformation:	f a bond for this well in conformance PRITECLESIN FRODUCTS O to use the following strings of casis Strategy Welgate Per Foot 7 80. D. 204 In the above plan become advisable ductive oil or gas sand should occur information:	Well CORRECTLY We propose to drill well with dril f a bond for this well in conformance with Rule 39 of the PRIFICLEUM FRODUCTS CORPORATION B. to use the following strings of casing and to land or cer Stra of Weight Per Foot Second Hand 780.D. 20# Used. In the above plan become advisable we will notify you ductive oil or gas sand should occur at a depth of about information:	Well Corrective We propose to drill well with drilling equipment as a bond for this well in conformance with Rule 39 of the General Rules and PRINCISM FRODUCTS CORPORATION BLANKET BOND to use the following strings of casing and to land or cement them as indicated Weight for Food Second Hand Depth 750.D. 204 Used 1630 The above plan become advisable we will notify you before cementing of ductive oil or gas sand should occur at a depth of about 1630 femoformation:	Well Corrective We propose to drill well with drilling equipment as follows BOTA f a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the PRIFOLEM FRODUCTS CORPORATION BLANKET BOND to use the following strings of casing and to land or cement them as indicated: New of Casing Welght for Foot Second Hand Depth Commented 780.D. 204 Used 1630 Commented