Form 3160-5 (Augus 1999)

Conditions of approval, if any are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 200

RI	/ L	ovember 30, 2000		
BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.			5. Lease Serial No. I149IND8475	
			6. If Indian, Allottee EASTERN NA	
SUBMIT IN TRII	PLICATE - Other instruc	tions on reverse side.	7. If Unit or CA/Agr NMNM78391C	eement, Name and/or No.
1. Type of Well — Geo Well — Oth		AN DEO	8. Well Name and No GCU 215).
Oil Well Gas Well Oth 2. Name of Operator	Contact:	CHERRY HLAVA	9. API Well No.	00.04
BP AMERICA PRODUCTION 3a. Address		E-Mail: hlavacl@bp.com 3b. Phone No (include area code	30-045-11622-	
P. O. BOX 3092 HOUSTON, TX 77253		Ph: 281.366.4081 Fx: 281.366.0700	BASIN DAKOT	
4. Location of Well (Footage, Sec., 7	., R., M., or Survey Description) ZZZ	11. County or Parish	, and State
Sec 16 T28N R12W SWSW 0 36.65759 N Lat, 108.12126 W			SAN JUAN CO	DUNTY, NM
12. CHECK APPE	ROPRIATE BOX(ES) TO	O INDICATE NATURE OF 1	NOTICE, REPORT, OR OTHI	ER DATA
TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent	Acidize	Deepen	Production (Start/Resume)	☐ Water Shut-Off
_	☐ Alter Casing	☐ Fracture Treat	Reclamation	□ Well Integrity
☐ Subsequent Report	Casing Repair	□ New Construction	Recomplete	Other Workover Operations
☐ Final Abandonment Notice	☐ Change Plans	☐ Plug and Abandon	☐ Temporarily Abandon	Workover Operations
	Convert to Injection	□ Plug Back	☐ Water Disposal	
Attach the Bond under which the wo following completion of the involved	ally or recomplete horizontally, rk will be performed or provide operations. If the operation re bandonment Notices shall be fil	give subsurface locations and measure the Bond No. on file with BLM/BL sults in a multiple completion or rec	ng date of any proposed work and appi ried and true vertical depths of all per A. Required subsequent reports shall lompletion in a new interval, a Form 3 ding reclamation, have been completed	tinent markers and zones. be filed within 30 days 160-4 shall be filed once
BP America Production Co. re	equests permission to rep	air bradenhead on above me	ntioned well.	
Please see procedure attache	ed. For questions please	call John Papageorge at 281	-366-5721	
CONDITIONS OF APPR Adhere to previously issued stips		SEE A CONDITIO	ITTACHED FOR INS OF APPROVAL	
14. Thereby certify that the foregoing is	s true and correct.			
	Electronic Submission #	25065 verified by the BLM Wel A PRODUCTION CO, sent to th sing by MATTHEW HALBERT o	e Farmington	
Name (Printed/Typed) CHERRY		- •	PRIZED REPRESENTATIVE	
Signature (Electronic S	Submission)	Date 11/13/2	2003	
	THIS SPACE FO	OR FEDERAL OR STATE	OFFICE USE	
Approved By	- by	Title P	x. 15 m	12/3/03

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any design gency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Office



GCU Workover Procedure

Well Name:

GCU 215

Date:

SAP Number

11/11/03

Objective:

Bradenhead repair.

Pertinent Information:

Location:

Sec.16, T28N-R12W

County: State:

San Juan **New Mexico**

Lease:

Meter No. Well Flac: 75363

98567501

Horizon:

Dakota

API#: Engr:

30-045-11622

Phone:

John Papageorge W (281)366-5721

H (713)464-5053

NOTE: Contact Federal and State Agencies for approval prior to performing any cement squeeze work.

1. Check anchors. MIRUSU

- 2. Check and record tubing, casing and bradenhead pressures.
- 3. Blow down well and kill if necessary with 2% KCl water.
- 4. ND wellhead, NU BOPs and diversion spool with 3" outlets and 3"pipe to the blow tank. Pressure test BOPs to 500 psi. Monitor flowing casing pressure with gauge (with casing flowing to blow tank) throughout workover.
- 5. Tag for fill and tally OOH with 2-3/8" production tubing set at 5810'. Visually inspect tubing.
- 6. RIH with bit and scraper for 4-1/2" casing to PBTD and clean out as necessary.
- 7. RIH with CIBP and set at xxxx'.
- 8. Bleed casing to zero while monitoring bradenhead.
- 9. If bradenhead bleeds down with casing: a) set packer to identify leak in casing/tree, b) set cement retainer 50' above hole in casing. Mix and pump cement per Schlumberger procedure. Circulate to surface if possible.
- If bradenhead does not bleed down with casing: a) fill casing with fluid and pressure test to 500 psi. Perforate casing at xxxx. Set cement retainer at xxxx. Mix and pump cement per Schlumberger procedure. Circulate to surface if possible.
- 11. WOC. Drill out cement and pressure test squeeze to 500 psi (while monitoring bradenhead pressure).
- 12. Drill out CIBP and clean out to PBTD.
- Run production tubing. ND BOPs and NU wellhead. Return well to production. 13.

Conditions of Approval:

Notice of Intent: to repair bradenhead

BP AMERICA PRODUCTION CO GCU # 215 990 FSL & 1190 FWL Sec 16. T28N. R12W., API #: 3004511622

1. If perforations are necessary for remedial work in the well bore. Contact the FFO, Matt Halbert @ (505) 599-6350 or Jim Lovato @ (505) 599-6367.