

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

RECEIVED

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

ConocoPhillips

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Surf: Unit O (SW/SE), 165' FSL & 2330' FEL, Section 15, T30N, R5W, NMPM

APR 20 2009
5. Lease Number
SF-078997
Bureau of Land Management
Farmington Field Office
If Indian, All. or
Tribe Name

7. Unit Agreement Name
San Juan 30-5 Unit

8. Well Name & Number
San Juan 30-5 Unit 52N

9. API Well No.
30-039-30648

10. Field and Pool

Basin DK/Blanco MV
11. County and State
Rio Arriba, NM



12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans	<input checked="" type="checkbox"/> Other -	<input type="checkbox"/> Casing Report
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction		
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging	<input type="checkbox"/> Non-Routine Fracturing		
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off		
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection		

13. Describe Proposed or Completed Operations

4/19/2009 NU BOP. RIH w/ 8 3/4" bit & tag cmt, D/O cmt and drilled ahead to 3765' Int TD on 4/21/2009. Circ Hole. RIH w/89 jnts of 7" csg, 20#, J-55 ST&C set @ 3754'. RU CMT. 4/22/2009 Preflushed w/10bbls GW & 11 bbls FW. Pumped Scavenger w/ 15sx(56cf-10bbl) w/ 75% Type XI / 25% Class G Cement. Pumped Lead w/ 467sx(981cf-174bbl) w/ 75% Type XI / 25% Class G Cement w/ .25% Cellophane Flakes, 2% Sodium Medasilicate, .20% Antifoam. Pumped Tail w/ 95sx(122cf-22bbl) w/ 50:50 POZ Cement w/ .25% Cellophane Flake, 5% Gilonite, 2% Bentonite, .15% D65, & 1% D46. Drop plug & displace w/ 151bbls FW. Plug down @ 1714hrs. Circ 40bbls cmt to surface. WOC @ 1800hrs on 4/22/2009.

4/23/2009 @ 0300hrs, PT csg 1500#/30min, ok. 4/23/2009 RIH w/ 6 1/4" bit & tag cmt, D/O cmt and drilled ahead to TD 8086' on 4/24/2009. Circ hole. RIH w/198 jnts of 4 1/2" csg, 11.6#, L-80, LT& C set @ 8085'. RU cement. 4/25/2009 Preflushed w/ 10bbls MF & 2bbls FW. Pumped Scavenger w/ 15sx(27cf-5bbl) w/ 50:50 POZ Cement. Pumped Tail w/ 393sx(566cf-101bbl) w/ 50:50 POZ Cement, .25% Cellophane Flake, 5% Kolite, 3.5% Bentonite. Drop plug & displace w/ 116bbls FW. Plug down @ 16:56hrs. RD&RR on 4/25/2009. ✓

PT will be conducted by Completion Rig. Results and TOC will appear on next report. ✓

14. I hereby certify that the foregoing is true and correct.


Signed

Ethel Tally

Ethel Tally

Title Staff Regulatory Technician

Date 4/27/2009



(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

RECEIVED

fc