

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

**RECEIVED**

MAY 07 2009

Bureau of Land Management  
Farmington Field Office1. Type of Well  
GAS

2. Name of Operator

**BURLINGTON**

RESOURCES OIL &amp; GAS COMPANY LP

3. Address &amp; Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Surf: Unit C (NE/NW), 910' FNL & 1870' FWL, Section 11, T27N, R4W, NMPM  
Bttm: Unit K (NE/SW), 2590' FSL & 1780' FWL, Section 11, T27N, R4W, NMPM5. Lease Number  
SF-080671-A6. If Indian, All. or  
Tribe Name7. Unit Agreement Name  
San Juan 27-4 Unit8. Well Name & Number  
San Juan 27-4 Unit 28C9. API Well No.  
30-039-3058910. Field and Pool  
Blanco MV11. County and State  
Rio Arriba, NM**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

Type of Submission

Type of Action

☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - Casing Report☒ Subsequent Report☐ Recompletion☐ New Construction☐ Plugging☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☐ Final Abandonment☐ Altering Casing☐ Conversion to InjectionRCVD MAY 13 '09  
OIL CONS. DIV.  
DIST. 3**13. Describe Proposed or Completed Operations**

4/21/2009 NU BOP. RIH w/ 8 3/4" bit & tag cmt. D/O cmt and drilled ahead to TD Int 4758' on 4/25/2009. Circ Hole. RIH w/ 11 1/2 jnts of 7" csg, 23# J-55 ST&C set @ 4732' w/ DV Tool @ 3826'. RU CMT. 4/27/2009 1<sup>st</sup> STAGE Preflushed 10bbls FW & 10bbl GW, Pumped Scavenger w/ 20sx(57cf-10bbl) Premium Lite FM Cement, Pumped Lead w/ 36sx(77cf-14bbl) Premium Lite Cement w/ CaCl 3%, LCM-1 5lbs, SMS .4%, FL-52 .4%, Bentonite 8%, CelloFlake .25lbs. Pumped Tail w/ 120sx(166cf-29bbl) Type I-II Cement w/ CaCl 1%, FL-52 .2%, CelloFlake .25lbs. Drop plug & displace w/ 40bbls FW & 145bbls DM. Bump plug. Open DV Tool. Circ 1bbls of cmt to surface. WQC ✓

4/27/2009 2<sup>nd</sup> STAGE Preflushed w/ 10 bbls FW, 10 bbls GW. Pumped Scavenger w/ 20sx(56cf-10bbl) Premium Lite FM Cement, Pumped Tail w/ 540sx(1150cf-204bbl) Premium Lite FM Cement w/ 3% CaCl, 0.25 pps Cello-Flake, 5 pps LCM-1, 0.4% FL-52A, 8% Bentonite and 0.4% SMS. Drop Plug & displace w/ 154bbls H2O. Bump plug & close DV Tool. Circ 38bbls cmt to surface. WQC ✓

4/29/2009 PT DV Tool and csg @ 1500#/30Min. OK. RIH W 6 1/4" bit & tag cmt, D/O DV Tool & cmt and drilled ahead to final TD @ 7171' on 4/30/2009. RIH w/ 11 1/2 jnts, 4 1/2" csg, 11.6#, L-80, LT&C & 59 jnts, 4 1/2" csg, 11.6# J-55, LT&C set @ 7169'. RU cmt. 05/01/2009 Preflushed w/ 10bbls GW & 2bbls FW. Pumped Scavenger w/ 10sx(27cf-5bbl) Premium Lite HS FM Cement, Pumped Tail w/ 170sx(337cf-60bbl) Premium Lite HS FM Cement w/ 0.25pps Cello-Flake, 0.3% CD-32, 6.25pps LCM, 1% FL-52. Drop plug & displace w/ 112bbls FW. Bump plug. Plug down @ 0030hrs on 5/02/2009. RD&RR 5/2/2009. ✓

PT will be conducted by Completion Rig. TOC and results will appear on next report. ✓

**14. I hereby certify that the foregoing is true and correct.**

Signed

*Ethel Tally*

Ethel Tally

Title Staff Regulatory Technician

Date 5/7/2009

(This space for Federal or State Office use)

APPROVED BY

Title

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

ACCEPTED FOR RECORD
Date
MAY 11 2009
FARMINGTON FIELD OFFICE
BY <i>TL Salvess</i>

PC