

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED

MAY 21 2009

## Sundry Notices and Reports on Wells

Bureau of Land Management  
Farmington Field Office

1. Type of Well  
GAS

5. Lease Number  
SF-078997

6. If Indian, All. or  
Tribe Name

2. Name of Operator

7. Unit Agreement Name  
San Juan 30-5 Unit

ConocoPhillips

3. Address & Phone No. of Operator

8. Well Name & Number  
San Juan 30-5 Unit 72M

PO Box 4289, Farmington, NM 87499 (505) 326-9700

9. API Well No.

30-039-30644

4. Location of Well, Footage, Sec., T, R, M

10. Field and Pool  
Basin DK/Blanco MV

Surf: Unit P (SE/SE), 200' FSL & 630' FEL, Section 10, T30N, R5W, NMPM

11. County and State  
Rio Arriba, NM

## 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

## Type of Submission

## Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Other - Casing Report

☒ Subsequent Report

☐ Recompletion

☐ New Construction

RCVD MAY 22 '09

☐ Final Abandonment

☐ Plugging

☐ Non-Routine Fracturing

OIL CONS. DIV.

☐ Casing Repair

☐ Water Shut off

DIST. 3

☐ Altering Casing

☐ Conversion to Injection

## 13. Describe Proposed or Completed Operations

05/04/2009 MIRU AWS 673. NU BOP. 5/5/2009 PT csg 600#/30min, ok. RIH w/ 8 3/4" bit & tag cmt, D/O cmt and drilled ahead to 3630' Int TD on 05/09/2009. Circ Hole. 5/10/2009 RIH w/85 jnts of 7" csg, 20#, J-55 LT&C set @ 3619'. RU CMT. 05/10/2009 Preflushed w/10bbls GW & 10 bbls FW. Pumped Scavenger w/ 19sx(56cf-10bbl) Premium Lite Cement. Pumped Lead w/ 444sx(946cf-168bbl) Premium Lite FM Cement w/ 3% CaCl, .25lbs/sx CelloFlake, 5lbs/sx LCM-1, .4 FL-52, 8% Bentonite, & 4% SMS. Pumped Tail w/ 85sx(117cf-21bbl) Type I-II Cement w/ 1% CaCl, .25lbs/sx CelloFlake, & .2% FL-52. Drop plug & displace w/ 141bbls FW. Bump plug. Circ 70bbls cmt to surface. WOC.

5/11/2009 PT csg 1500#/30min, ok. RIH w/ 6 1/4" bit & tag cmt, D/O cmt and drilled ahead to TD 7980' on 5/16/2009. Circ hole. 5/17/2009 RIH w/185 jnts of 4 1/2" csg, 1 L6#, L-80, LT&C set @ 7971'. RU cement. 05/18/2009 Preflushed w/ 10bbls GW & 2bbls FW. Pumped Scavenger w/ 19sx(27cf-5bbl) Premium Lite HS FM Cement. Pumped Tail w/ 298sx(590cf-105bbl) Premium Lite HS FM Cement w/ .25lbs/sx CelloFlake, .3% CD-32, 6.25 pps LCM-1, & 1.1% FL-52. Drop plug & displace w/ 124bbls FW. Plug down @ 0905hrs. WOC. RD&RR 05/18/2009.

PT will be conducted by Completion Rig. Results and TOC will appear on next report.

## 14. I hereby certify that the foregoing is true and correct.

Signed Ethel Tally Ethel Tally

Title Staff Regulatory Technician Date 5/21/2009

ACCEPTED FOR RECORD

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_

MAY 20 2009

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

FARMINGTON FIELD OFFICE  
BY [Signature]

NMSCD