In Lieu of Form 3160 (June 1990)

LINITED STATES DEPARTMENT OF INTERIOR BUREAU OF LAND MANAGEMENT

SLINDRY NOTICE AND REPORTS ON WELLS

Location of Well (Footage, Sec , T., R , M , or Survey Description)

At sur- 2260' FSL & 600' FEL SEC 6. T31N,R5W

BH- 2310' FSL & 2310' FEL SEC 6, T31N, R5W

REC	EIV	ED
-----	-----	----

FORM APPROVED Budget Bureau No. 1004-0135 Expires March 31, 1993

MAY 2 1 200)

11.

Lease Designation and Serial No

County or Parish, State

R10 Arriba, New Mexico

Do	not use this form for proposals to drill or to deepen or reentry to a different reservoir TO DRILL" for permit for such proposals TO DRILL" for permit for such proposals	iement 1669	NMSF-078767 If Indian, Allottee or Tribe Name
	SUBMIT IN TRIPLICATE	7.	If Unit or CA, Agreement Designation Rosa Unit
	Type of Well Oıl Well Gas Well X Other	8.	Well Name and No. Rosa Unit 72B
!	Name of Operator WILLIAMS PRODUCTION COMPANY	9.	API Well No 30-039-30336
	Address and Telephone No PO Box 640 Aztec, NM 87410-0640	10	Field and Pool, or Exploratory Area BLANCO MV/BASIN DK

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Non-Routine Fracturing Plugging Back Casing Repair Water Shut-Off Final Abandonment Altering Casing Conversion to Injection Dispose Water X Other Surface Casing-AMMENDED INCLUDE CSG TEST LENGTH (Note. Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertunent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)*

4/7/09- TD- 14 1/4" SURF HOLE @ 340, 2000 HRS

RCVD MAY 28 '09 OIL CONS. DIV. DIST. 3

4/8/09-RAN 7 JT.'S, 10 1/4", J-55, 40.5# CSG SET @ 326', FLOAT INSERT @ 284' CMT 10.75" CSG AS FOLLOWS. TEST LINES 1500#, PUMP 10 bbl FW SPACER, 290sx (521 cuft) "Type III" +2% Cal-seal 60 + 1/4 # Poly-e-flake/sx + .3% Versaset + 2% Econolite + 6% salt (Yeild = 1.796 cuft/sx, wt.=13.5#/gal) CIRC 40 BBL'S CMT TO PIT. PLUG DOWN @ 2:37 AM 4/8/2009. CHECK FLOATS - HELD OK

4/9/09- INSTALL TEST PLUG & TEST PIPE RAMS, BLIND RAMS, MUD CROSS VALVES, CHOKE MANIFOLD VALVES, FLOOR VALVE & UPPER KELLY VALVE @ 250# LOW F/ 5 MIN EACH, & 1500# HIGH F/ 10 MIN EACH. 1 VALVE ON KILL LINE SIDE AND 1 VALVE ON CHOKE SIDE LEAKING, RING GASKETS ON BOTH SIDES OF CHOKE STINGER LEAKING, REPAIR LEAKS & RETEST

4/10/09- INSTALL TEST PLUG & TEST PIPE RAMS, BLIND RAMS, MUD CROSS VALVES, CHOKE MANIFOLD VALVES, FLOOR VALVE & UPPER KELLY VALVE @ 250# LOW F/ 5 MIN EACH, & 1500# HIGH F/ 10 MIN EACH. RING GASKET BETWEEN BOP & MUD CROSS LEAKING. REPLACE TWICE & RETEST. TEST GOOD

PULL TEST PLUG & TEST 10-3/4" CSG AGAINST BLIND RAMS TEST 10-3/4" CSG AGAINST BLIND RAMS @ 1500 PSI. FOR 30 MIN. TEST PUMP, CHART RECORDER USED. ALL TESTS GOOD. JOE RUYBBLID WITH BLM WITNESS ALL TESTS

14.	I hereby certify that the foregoing is true and correct Signed Larry Higgins	Title <u>Drilling C O.M</u>	Date 5/21/09 ACCEPTED FOR RECORD
	(This space for Federal or State office use)		MAY 2 6 2009
	Approved by	Title	Date DOFFICE
	Conditions of approval, if any:		FARMINGTON FIELD OFFICE BY

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.