

Certificate Number 15269

COP Deviation Report
SAN JUAN 31-6 UNIT #6F

Operator CONOCOPHILLIPS	Legal WellName SAN JUAN 31-6 UNIT #6F	API / UWI 3003930358	County RIO ARRIBA	State/Province NEW MEXICO
Surface Legal Location 001-030N-007W-E		N/S Dist (ft) 1,720.00	N/S Ref FNL	E/W Dist (ft) 760.00 E/W Ref FWL

Date	MD (ft/KB)	Incl. (°)	Method	Survey Company
11/10/2008	0.00	0.00	MWD	Pathfinder
7/2/2008	129.00	0.75	A1SureShot	Mo-Te Drilling Inc.
7/2/2008	229.00	1.00	A1SureShot	Mo-Te Drilling Inc.
11/10/2008	254.00	1.23	MWD	
11/10/2008	285.00	1.41	MWD	
11/10/2008	315.00	1.32	MWD	
11/10/2008	346.00	1.32	MWD	
11/10/2008	377.00	1.49	MWD	
11/10/2008	407.00	1.93	MWD	Pathfinder
11/10/2008	438.00	2.64	MWD	
11/10/2008	469.00	3.17	MWD	
11/10/2008	499.00	4.22	MWD	
11/10/2008	530.00	5.01	MWD	
11/11/2008	561.00	5.72	MWD	
11/11/2008	592.00	6.24	MWD	
11/11/2008	622.00	7.47	MWD	
11/11/2008	653.00	8.44	MWD	
11/11/2008	684.00	9.08	MWD	
11/11/2008	716.00	9.76	MWD	
11/11/2008	747.00	10.55	MWD	
11/11/2008	779.00	11.34	MWD	
11/11/2008	811.00	12.31	MWD	
11/11/2008	843.00	13.10	MWD	
11/11/2008	875.00	14.18	MWD	
11/11/2008	907.00	15.30	MWD	
11/11/2008	938.00	16.36	MWD	
11/11/2008	970.00	17.24	MWD	
11/11/2008	1,002.00	18.11	MWD	
11/11/2008	1,034.00	19.08	MWD	
11/11/2008	1,066.00	19.87	MWD	
11/11/2008	1,098.00	20.84	MWD	
11/11/2008	1,130.00	21.54	MWD	
11/11/2008	1,193.00	22.60	MWD	
11/11/2008	1,257.00	23.74	MWD	
11/11/2008	1,321.00	24.09	MWD	
11/11/2008	1,384.00	24.18	MWD	

RCVD JUN 9 '09

OIL CONS. DIV.

DIST. 3

I, the undersigned, certify that I acting in my capacity as _____ for ConocoPhillips Company, am authorized by said Company to make this report; and that said report was prepared under my supervision and directions, and that the facts stated herein are true to the best of my knowledge and belief.

[Signature]

Subscribed and sworn to me this June 8, 2009

[Signature]

Notary Public in and for San Juan County, New Mexico

My Commission expires Feb. 28, 2012

Survey Data

Date	MD (ftKB)	Incl (°)	Method	Survey Company
11/11/2008	1,447.00	24.18	MWD	
11/11/2008	1,511.00	23.83	MWD	
11/11/2008	1,574.00	24.36	MWD	
11/11/2008	1,638.00	24.09	MWD	
11/11/2008	1,702.00	24.01	MWD	
11/11/2008	1,766.00	24.53	MWD	
11/11/2008	1,829.00	24.53	MWD	
11/12/2008	1,893.00	24.53	MWD	
11/12/2008	1,957.00	24.45	MWD	
11/12/2008	2,020.00	24.09	MWD	
11/12/2008	2,083.00	23.74	MWD	
11/12/2008	2,147.00	23.57	MWD	
11/12/2008	2,211.00	24.27	MWD	
11/12/2008	2,274.00	24.71	MWD	
11/12/2008	2,338.00	24.27	MWD	
11/12/2008	2,402.00	24.27	MWD	
11/12/2008	2,466.00	23.83	MWD	
11/12/2008	2,529.00	24.01	MWD	
11/12/2008	2,593.00	24.53	MWD	
11/12/2008	2,657.00	24.89	MWD	
11/12/2008	2,721.00	24.71	MWD	
11/12/2008	2,784.00	24.36	MWD	
11/12/2008	2,848.00	24.53	MWD	
11/12/2008	2,912.00	24.27	MWD	
11/12/2008	2,975.00	24.53	MWD	
11/12/2008	3,039.00	24.53	MWD	
11/12/2008	3,103.00	24.62	MWD	
11/12/2008	3,167.00	23.92	MWD	
11/12/2008	3,230.00	23.65	MWD	
11/12/2008	3,294.00	22.51	MWD	
11/12/2008	3,358.00	20.58	MWD	
11/13/2008	3,421.00	18.99	MWD	Pathfinder
11/13/2008	3,485.00	17.85	MWD	Pathfinder
11/13/2008	3,517.00	17.41	MWD	Pathfinder
11/13/2008	3,549.00	17.24	MWD	Pathfinder
11/13/2008	3,575.00	16.97	MWD	Pathfinder
11/13/2008	3,581.00	17.32	MWD	Pathfinder
11/13/2008	3,612.00	17.06	MWD	Pathfinder
11/13/2008	3,644.00	17.24	MWD	Pathfinder

I, the undersigned, certify that I acting in my capacity as _____ for ConocoPhillips Company, am authorized by said Company to make this report; and that said report was prepared under my supervision and directions, and that the facts stated herein are true to the best of my knowledge and belief:

Subscribed and sworn to me this _____

Notary Public in and for San Juan County, New Mexico

My Commission expires _____

Survey Data

Date	MD (ftKB)	Incl (°)	Method	Survey Company
11/13/2008	3,707.00	16.98	MWD	Pathfinder
11/13/2008	3,738.00	17.85	MWD	Pathfinder
11/15/2008	3,777.00	18.40	MWD	Pathfinder
11/15/2008	3,840.00	17.20	MWD	Pathfinder
11/15/2008	3,872.00	16.00	MWD	Pathfinder
11/15/2008	3,904.00	14.50	MWD	Pathfinder
11/15/2008	3,936.00	13.60	MWD	Pathfinder
11/15/2008	3,967.00	12.40	MWD	Pathfinder
11/15/2008	3,998.00	10.60	MWD	Pathfinder
11/15/2008	4,030.00	9.10	MWD	Pathfinder
11/15/2008	4,062.00	7.70	MWD	Pathfinder
11/15/2008	4,094.00	6.20	MWD	Pathfinder
11/16/2008	4,126.00	5.00	MWD	Pathfinder
11/16/2008	4,158.00	4.30	MWD	Pathfinder
11/16/2008	4,190.00	3.40	MWD	Pathfinder
11/16/2008	4,221.00	2.20	MWD	Pathfinder
11/16/2008	4,243.00	1.70	MWD	Pathfinder
4/13/2009	8,265.00	1.00	FINAL BHS	PHOENIX

I, the undersigned, certify that I acting in my capacity as _____ for ConocoPhillips Company, am authorized by said Company to make this report, and that said report was prepared under my supervision and directions, and that the facts stated herein are true to the best of my knowledge and belief.

Subscribed and sworn to me this _____

Notary Public in and for San Juan County, New Mexico

My Commission expires _____

RCVD JUN 9 '09
OIL CONS. DIV.
DIST. 3

December 18, 2008

ConocoPhillips
Geneva Blackwater
3401 E 30th Street, Farmington 87402

RE: ConocoPhillips
San Juan 31-6 #6F
Rio Arriba County, NM
RIG: AZTEC 777
API NO: 30-039-30358
PES FILE NO.: 101007921-NM-NM

We hereby certify that the enclosed Original Field Survey Data contained in this report represents to the best of our knowledge, a true and accurate survey of the well at the time the survey was run.

DIRECTIONAL SURVEY DATA


3 – Directional Survey Report Copies

We appreciate the opportunity to work with you and we look forward to your business support. If you have any questions, I can be reached at (505) 324-0357

Sincerely,



Tom Schmidt
M/LWD Service Coordinator
PathFinder Energy Services




DIRECTIONAL SURVEY COMPANY REPORT:

1. NAME OF SURVEYING COMPANY: PATHFINDER ENERGY SERVICES
2. NAME OF PERSON(S) PERFORMING SURVEY:
A) Justin Hawkins
B) Michael Zaw
3. POSITION OF SAID PERSON(S): (A-B) SURVEYORS (FIELD ENGINEERS)
4. DATE(S) ON WHICH SURVEY WAS PERFORMED: 11/10/08 TO 11/14/08
5. STATE IN WHICH SURVEY WAS PERFORMED: New Mexico
6. LOCATION OF WELL: RIO ARRIBA COUNTY, NM
7. TYPE OF SURVEY(S) PERFORMED: MWD
8. COMPLETE IDENTIFICATION OF WELL:

SAN JUAN 31-6 #6F
RIO ARRIBA COUNTY, NM
RIG: AZTEC 777
API NO: 30-039-30358

9. SURVEY CERTIFIED FROM: 254 TO 3738 MEASURED DEPTH

THIS IS TO VERIFY THAT ATTACHED DOCUMENTS SHOWING THE WELL TO BE DISPLACED AT 1265.02 FEET, ON A BEARING OF 72.85 DEGREES FROM THE CENTER OF THE ROTARY TABLE AT A PROJECTED DEPTH OF 4295 FEET, ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE.




Tom Schmidt
M/LWD SERVICE COORDINATOR


STATE OF New Mexico)
)ss.
COUNTY OF San Juan)

The preceding instrument was acknowledged before me on

December 9th, 2008 by Tom Schmidt.

My Commission Expires: 5-23-2012

Notary Public: 



(seal)

****NOTE:** This Notary Certificate is prepared on a separate page and is to be attached to the Animas Credit Union "Interim Statement".

PathFinder Energy Services, Inc.

BHL Report

Page 01/01
Tie-in Date: 11/09/2008
Date Completed: 11/13/2008

ConocoPhillips
San Juan 31-6 #6F
Rio Arriba COUNTY, NM
Rig:AWS 777

PathFinder Office Supervisor: T. Schmidt
PathFinder Field Engineers: J. Hawkins
M. Zaw
D. Begayé

Survey Horiz. Reference: WELLHEAD
Ref Coordinates: LAT: 36.50.38.5584 N LON: 107.31.41.1816 W
GRID Reference: NAD27 new mexico west Transverse Mercator
Ref GRID Coord: X: 589312.8494 Y: 2126635.6934
North Aligned To: TRUE NORTH
Total Magnetic Correction: 10.12° EAST TO TRUE
Vertical Section Plane: 72.58
Survey Vert. Reference: 15.00' Rotary Table To Ground
Altitude: 6545.00' Ground To MSL

Measured Depth	4295.00	(feet)
Inclination	1.70	(deg)
Azimuth	101.50	(deg)
True Vertical Depth	4053.59	(feet)
Vertical Section	1265.01	(feet)
Survey X cord	590521.65	(feet)
Survey Y cord	2127008.64	(feet)
Survey Lat	36.84505775 N	(deg)
Survey Lon	107.52397085 W	(deg)
Rectangular Corr. N/S	372.95 N	(feet)
Rectangular Corr. E/W	1208.80 E	(feet)
Closure Distance	1265.02	(feet)
Direction of Closure	72.85	(deg)
Dogleg Severity	0.00	(deg/100ft)

PathFinder Energy Services, Inc.

Survey Report

ConocoPhillips
San Juan 31-6 #6F
Rio Arriba COUNTY, NM
Rig:AWS 777
PathFinder Office Supervisor: T. Schmidt
PathFinder Field Engineers: J. Hawkins
M. Zaw
D. Begaye

Survey Horiz. Reference:WELLHEAD
Ref Coordinates: LAT:36.50.38.5584 N LON:107.31.41.1816 W
Reference:NAD27 new mexico west Transverse Mercator
Ref GRID Coord: X: 589312.8494 Y: 2126635.6934
North Aligned To:TRUE NORTH
Total Magnetic Correction:10.12° EAST TO TRUE
Vertical Section Plane: 72.58
Survey Vert. Reference: 15.00' Rotary Table To Ground
Altitude:6545.00' Ground To MSL

Survey Calculations by PathCalc v1.97e using Minimum Curvature

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft) (ft)		Closure Dist Dir (ft) (deg)		DLS (dg/100ft)
ORIGIN OF WELL AT SURFACE										
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00@	0.00	0.00
THE FOLLOWING ARE PATHFINDER MWD SURVEYS.										
254.00	1.23	7.13	253.98	254.00	1.13	2.71 N	0.34 E	2.73@	7.13	0.48
285.00	1.41	11.10	284.97	31.00	1.45	3.41 N	0.45 E	3.44@	7.57	0.65
315.00	1.32	14.79	314.96	30.00	1.81	4.11 N	0.61 E	4.15@	8.48	0.42
346.00	1.32	10.44	345.96	31.00	2.17	4.80 N	0.77 E	4.86@	9.09	0.32
377.00	1.49	19.03	376.95	31.00	2.58	5.53 N	0.96 E	5.62@	9.88	0.87
407.00	1.93	43.68	406.93	30.00	3.25	6.27 N	1.44 E	6.43@	12.94	2.82
438.00	2.64	54.56	437.91	31.00	4.39	7.06 N	2.38 E	7.45@	18.65	2.67
469.00	3.17	56.98	468.87	31.00	5.89	7.94 N	3.68 E	8.75@	24.88	1.75
499.00	4.22	66.59	498.81	30.00	7.79	8.83 N	5.39 E	10.35@	31.40	4.05
530.00	5.01	71.30	529.71	31.00	10.28	9.72 N	7.72 E	12.41@	38.46	2.82
561.00	5.72	71.73	560.57	31.00	13.17	10.64 N	10.47 E	14.93@	44.54	2.29
592.00	6.24	71.38	591.40	31.00	16.40	11.66 N	13.53 E	17.86@	49.25	1.68
622.00	7.47	72.60	621.19	30.00	19.98	12.76 N	16.94 E	21.21@	53.00	4.13
653.00	8.44	71.83	651.89	31.00	24.27	14.08 N	21.02 E	25.30@	56.20	3.15
684.00	9.06	72.14	682.53	31.00	28.99	15.53 N	25.51 E	29.87@	58.66	2.01
716.00	9.76	74.33	714.10	32.00	34.22	17.04 N	30.52 E	34.95@	60.82	2.46
747.00	10.55	76.68	744.61	31.00	39.68	18.40 N	35.81 E	40.26@	62.80	2.88
779.00	11.34	76.86	776.03	32.00	45.74	19.79 N	41.72 E	46.18@	64.62	2.47
811.00	12.31	78.63	807.35	32.00	52.27	21.18 N	48.13 E	52.59@	66.25	3.24
843.00	13.10	79.02	838.56	32.00	59.26	22.54 N	55.04 E	59.47@	67.73	2.48
875.00	14.16	78.88	869.66	32.00	66.76	23.99 N	62.44 E	66.89@	68.98	3.31
907.00	15.30	77.90	900.61	32.00	74.85	25.63 N	70.41 E	74.93@	70.00	3.65

PathFinder Energy Services, Inc.

Survey Report

ConocoPhillips
San Juan 31-6 #6F
Rio Arriba COUNTY, NM
RIG:AWS 777

Page 02/04

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft) (ft)		Closure Dist Dir (ft) (deg)		DLS (dg/100ft)
938.00	16.36	77.20	930.43	31.00	83.27	27.45 N	78.66 E	83.32@	70.76	3.47
970.00	17.24	76.56	961.07	32.00	92.50	29.55 N	87.67 E	92.52@	71.37	2.81
1002.00	18.11	76.64	991.56	32.00	102.19	31.81 N	97.12 E	102.20@	71.87	2.72
1034.00	19.08	76.13	1021.89	32.00	112.37	34.21 N	107.04 E	112.37@	72.28	3.07
1066.00	19.87	74.92	1052.06	32.00	123.02	36.88 N	117.37 E	123.02@	72.56	2.77
1098.00	20.84	74.52	1082.06	32.00	134.15	39.81 N	128.10 E	134.15@	72.74	3.06
1130.00	21.54	74.25	1111.89	32.00	145.71	42.93 N	139.24 E	145.71@	72.87	2.21
1193.00	22.60	73.36	1170.28	63.00	169.37	49.53 N	161.97 E	169.38@	73.00	1.76
1257.00	23.74	73.08	1229.11	64.00	194.55	56.80 N	186.08 E	194.56@	73.03	1.79
1321.00	24.09	72.69	1287.62	64.00	220.50	64.44 N	210.88 E	220.50@	73.01	0.60
1384.00	24.18	72.63	1345.11	63.00	246.26	72.12 N	235.47 E	246.26@	72.97	0.15
1447.00	24.18	72.99	1402.58	63.00	272.06	79.74 N	260.12 E	272.07@	72.96	0.23
1511.00	23.83	72.24	1461.05	64.00	298.10	87.52 N	284.97 E	298.10@	72.93	0.73
1574.00	24.36	73.05	1518.56	63.00	323.82	95.19 N	309.51 E	323.82@	72.90	0.99
1638.00	24.09	73.27	1576.92	64.00	350.08	102.80 N	334.65 E	350.08@	72.92	0.44
1702.00	24.01	73.44	1635.37	64.00	376.16	110.27 N	359.64 E	376.16@	72.95	0.17
1766.00	24.53	72.29	1693.71	64.00	402.46	118.02 N	384.77 E	402.47@	72.95	1.10
1829.00	24.53	72.20	1751.03	63.00	428.62	126.00 N	409.68 E	428.62@	72.90	0.06
1893.00	24.53	71.76	1809.25	64.00	455.18	134.22 N	434.95 E	455.19@	72.85	0.29
1957.00	24.45	71.67	1867.49	64.00	481.71	142.54 N	460.14 E	481.71@	72.79	0.14
2020.00	24.09	71.43	1924.92	63.00	507.60	150.74 N	484.71 E	507.60@	72.73	0.59
2083.00	23.74	71.44	1982.51	63.00	533.14	158.87 N	508.92 E	533.14@	72.66	0.56
2147.00	23.57	71.34	2041.14	64.00	558.81	167.06 N	533.25 E	558.81@	72.60	0.27
2211.00	24.27	71.13	2099.64	64.00	584.75	175.41 N	557.82 E	584.75@	72.54	1.10
2274.00	24.71	71.62	2156.97	63.00	610.86	183.75 N	582.57 E	610.86@	72.49	0.77
2338.00	24.27	73.88	2215.22	64.00	637.39	191.62 N	607.90 E	637.39@	72.50	1.62
2402.00	24.27	72.72	2273.56	64.00	663.69	199.18 N	633.10 E	663.69@	72.54	0.74
2466.00	23.83	71.95	2332.00	64.00	689.77	207.09 N	657.95 E	689.77@	72.53	0.84
2529.00	24.01	72.38	2389.59	63.00	715.31	214.92 N	682.27 E	715.32@	72.52	0.40
2593.00	24.53	72.66	2447.94	64.00	741.62	222.82 N	707.36 E	741.62@	72.52	0.83

PathFinder Energy Services, Inc.

Survey Report

ConocoPhillips
San Juan 31-6 #6F
Rio Arriba COUNTY, NM
RIG:AWS 777

Page 03/04

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft) (ft)		Closure Dist Dir (ft) (deg)		DLS (dg/100ft)
2657.00	24.89	72.91	2506.08	64.00	768.37	230.73 N	732.91 E	768.37@	72.53	0.59
2721.00	24.71	72.60	2564.17	64.00	795.22	238.69 N	758.55 E	795.22@	72.53	0.35
2784.00	24.36	72.38	2621.48	63.00	821.38	246.56 N	783.50 E	821.38@	72.53	0.57
2848.00	24.53	71.84	2679.75	64.00	847.86	254.70 N	808.70 E	847.86@	72.52	0.44
2912.00	24.27	71.57	2738.03	64.00	874.30	263.00 N	833.81 E	874.30@	72.49	0.44
2975.00	24.53	71.65	2795.40	63.00	900.32	271.21 N	858.50 E	900.32@	72.47	0.42
3039.00	24.53	71.39	2853.63	64.00	926.89	279.63 N	883.70 E	926.89@	72.44	0.17
3103.00	24.62	71.53	2911.83	64.00	953.50	288.09 N	908.94 E	953.50@	72.41	0.17
3167.00	23.92	71.46	2970.17	64.00	979.80	296.44 N	933.88 E	979.80@	72.39	1.09
3230.00	23.65	71.83	3027.82	63.00	1005.20	304.44 N	958.00 E	1005.21@	72.37	0.49
3294.00	22.51	71.06	3086.70	64.00	1030.29	312.42 N	981.78 E	1030.30@	72.35	1.84
3358.00	20.58	74.18	3146.23	64.00	1053.78	319.47 N	1004.20 E	1053.79@	72.35	3.51
3421.00	18.99	72.74	3205.51	63.00	1075.10	325.53 N	1024.64 E	1075.11@	72.37	2.64
3485.00	17.85	70.61	3266.23	64.00	1095.32	331.87 N	1043.84 E	1095.33@	72.36	2.07
3517.00	17.41	69.73	3296.72	32.00	1105.00	335.16 N	1052.96 E	1105.01@	72.34	1.61
3549.00	17.24	71.96	3327.27	32.00	1114.52	338.29 N	1061.96 E	1114.53@	72.33	2.14
3581.00	17.32	73.66	3357.83	32.00	1124.03	341.10 N	1071.04 E	1124.04@	72.33	1.60
3612.00	17.06	73.57	3387.44	31.00	1133.19	343.68 N	1079.82 E	1133.20@	72.35	0.84
3644.00	17.24	73.44	3418.02	32.00	1142.62	346.36 N	1088.87 E	1142.63@	72.35	0.58
3675.00	16.97	73.50	3447.65	31.00	1151.74	348.95 N	1097.61 E	1151.75@	72.36	0.87
3707.00	16.97	73.19	3478.26	32.00	1161.08	351.63 N	1106.56 E	1161.09@	72.37	0.28
3738.00	17.85	74.08	3507.84	31.00	1170.35	354.24 N	1115.46 E	1170.36@	72.38	2.97
THE FOLLOWING ARE OILWELL GUIDANCE EM SURVEYS.										
3777.00	18.40	74.00	3544.90	39.00	1182.48	357.58 N	1127.13 E	1182.49@	72.40	1.41
3840.00	17.20	75.30	3604.88	63.00	1201.73	362.68 N	1145.69 E	1201.73@	72.43	2.01
3872.00	16.00	76.30	3635.55	32.00	1210.85	364.93 N	1154.56 E	1210.86@	72.46	3.85
3904.00	14.50	77.50	3666.42	32.00	1219.25	366.84 N	1162.75 E	1219.25@	72.49	4.79
3936.00	13.60	79.60	3697.46	32.00	1226.97	368.39 N	1170.36 E	1226.97@	72.53	3.23
3967.00	12.40	81.60	3727.67	31.00	1233.88	369.53 N	1177.24 E	1233.88@	72.57	4.13
3998.00	10.60	80.70	3758.05	31.00	1239.99	370.48 N	1183.35 E	1239.99@	72.62	5.84

PathFinder Energy Services, Inc.

Survey Report

ConocoPhillips
San Juan 31-6 #6F
Rio Arriba COUNTY, NM
RIG:AWS 777

Page 04/04

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft) (ft)		Closure Dist Dir (ft) (deg)		DLS (dg/100ft)
4030.00	9.10	80.30	3789.57	32.00	1245.41	371.38 N	1188.75 E	1245.41@	72.65	4.69
4062.00	7.70	80.80	3821.23	32.00	1250.04	372.15 N	1193.36 E	1250.04@	72.68	4.38
4094.00	6.20	83.30	3852.99	32.00	1253.86	372.69 N	1197.19 E	1253.86@	72.71	4.78
4126.00	5.00	85.10	3884.84	32.00	1256.92	373.01 N	1200.30 E	1256.92@	72.74	3.79
4158.00	4.30	87.50	3916.73	32.00	1259.44	373.19 N	1202.89 E	1259.44@	72.76	2.27
4190.00	3.40	87.80	3948.66	32.00	1261.51	373.27 N	1205.03 E	1261.52@	72.79	2.81
4221.00	2.20	89.30	3979.62	31.00	1262.97	373.32 N	1206.55 E	1262.98@	72.81	3.88
4243.00	1.70	101.50	4001.61	22.00	1263.66	373.26 N	1207.29 E	1263.67@	72.82	2.94
STRAIGHT LINE PROJECTION TO BIT AT 4295' MD										
4295.00	1.70	101.50	4053.59	52.00	1265.01	372.95 N	1208.80 E	1265.02@	72.85	0.00