

UNITED STATES  
DEPARTMENT OF INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED

JUN 18 2009

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires. March 31, 1993

SUNDRY NOTICE AND REPORTS ON WELLS

Department of Land Management  
Farmington Field Office

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION TO DRILL" for permit for such proposals

Lease Designation and Serial No.  
NMSF-078766

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPPLICATE

1. Type of Well  
Oil Well Gas Well X Other

8. Well Name and No  
Rosa Unit 138D

2. Name of Operator  
WILLIAMS PRODUCTION COMPANY

9. API Well No.  
30-045-34959

3. Address and Telephone No.  
PO Box 640 Aztec, NM 87410-0640

10. Field and Pool, or Exploratory Area  
BLANCO MV/BASIN DK/BASIN MC

4. Location of Well (Footage, Sec, T., R., M., or Survey Description)  
2280 FNL & 820 FEL SEC 17 31N 6W  
1000 FNL & 200 FEL

11. County or Parish, State  
San Juan, New Mexico

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

Notice of Intent

Abandonment

Change of Plans

X Subsequent Report

Recompletion

New Construction

Final Abandonment

Plugging Back

Non-Routine Fracturing

Casing Repair

Water Shut-Off

Altering Casing

Conversion to Injection

X Other Final Casing

Dispose Water

(Note. Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)\*

6/10/09 THRU 6/14/09- DRILL 6 3/4" HOLE

6/15/09- TD 6 3/4" PROD HOLE @ 8373', 1500 HRS

6/16/09- RAN 218 JTS, 5.50", 17#, N-80, LT&C, 8rd, CSG SET @ 8370', FC @ 8330', MARKER JT @ 5583'

6/17/09- PRESS TEST 3500#, PUMP 20 Bbl GEL WATER SPACER, PUMP SINGLE SLURRY CEMENT JOB : 390sx ( 97 Bbl Slurry, 545cuft)  
"FRACCEM" Cmt + 0.8% Halad-9 + 0.1% CFR-3 + 5#/sk Gilsonite + 5.91 gal F.W./sk ( Yield=1.397cuft/sk, Wt = 13.1ppg )  
Flush Cmt Lines, Drop Plug & Displace W/ 195.2 Bbl F.W. Final Press = 1020#, Bump Plug to 1725#, Check Float-OK. Released  
Press & Flow Back 1.2 Bbl = 194 Bbl Displacement. RD HOWCO & RELEASE.  
ND BOPE, SET SLIPS ON 5.50" PROD CASING @ 180,000#, CUT OFF CASING.

NOTE: CASING TEST AND TOC WILL BE REPORTED ON COMPLETION SUNDRY  
DRILLING RIG RELEASED ON 6/17/09 @ 2000 HRS

RCVD JUN 23 '09

OIL CONS. DIV.

DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed Larry Higgins  
Larry Higgins

Title Drilling COM Date 6/18/09

(This space for Federal or State office use)

Approved by \_\_\_\_\_

Title \_\_\_\_\_

Date JUN 19 2009

Conditions of approval, if any:

FARMINGTON FIELD OFFICE

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC